

Model:
SBB-27-23B

Underbar Refrigeration: Solid Mobility Swing Door Back Bar Cooler

SABA



SBB-27-23B

- **CABINET CONSTRUCTION**
Standard, cabinet exterior construction includes attractive, wear resistant vinyl on steel in black finish. Stainless exterior options available.
- **Standard interior stainless steel walls, floor and ceiling.**
- **REFRIGERATION**
Refrigeration system uses R290 refrigerant, which is CFC and HCFC-free for compliance with environmental safety concerns.
- **ELECTRICAL**
Units wired at factory and ready for connection to a 115/60/1 phase, 15 amp dedicated outlet.
- **TEMPERATURE**
Oversized, factory balanced, refrigeration system holds 33°F to 38°F (0.5°C to 3.3°C)
- **SANITATION**
NSF-7 approved for packaged and bottled product.


MODEL FEATURES:

- Standard casters for mobility
- Self-closing doors with key lock
- Magnetic door gasket of one piece construction, removable without tools for ease of cleaning.
- Side knock out plugs for gas lines
- Designed to accommodate a variety of beer kegs

General Specification

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

Model	Doors	Shelves	Cabinet Dimensions (inches / mm)			Capacity		HP	Voltage	Amps	NEMA Config.
			L	D	H	12 oz. Cans	1/2 Barrels				
SBB-27-23B	1	2	23 1/2 596	30 3/4 782	38 3/4 984	30 6-pks	1	1/6+	115/60/1	1.92	5-15P 

● Plug type varies by country.



SABA

Add: 3390 Enterprise Avenue, Hayward, CA 94545-3228

Tel: (510) 293-0189 Fax: (510) 293-0199 E-mail: info@sabacorpusa.com Website: www.sabacorpusa.com

SBB-27-23B Plan View

SABA

