

3-DX Series

Multi-mode Fiber Patch-leads

Standard Duplex range for OM1, OM2 and OM3 grade fiber

ICP-Tek



Features

- 100% tested with test certificate on each bag label
- Low insertion loss 0.2dB typical
- Tight buffered fiber with Kevlar strengthening
- Available in different lengths from 1m to 30m

Specifications

- G50/125um OM3 grade fiber, Aqua colour
- LSOH sheath cable with nominal 2.8mm jacket
- Low insertion loss 0.2dB typical (worst case 0.3dB)
- Available for all standard connector types – LC, SC, ST, FC, MJ, E2000

Ordering Information

3-DX-AA-BB-LE-AA – G50/125um OM3 Multi-Mode Duplex fiber patch-lead, LSOH Aqua colour.

- Substitute connector choices **AA** and **BB** for: -
 - LC = LC (Duplex)
 - SC = SC (Duplex)
 - ST = ST (x 2)
 - FC = FC (x 2)
 - MJ = MTRJ
 - E2 = E2000
- Substitute length **LE** as required: - standard 1m, 2m, 3m, 5m & 10m.
Up to 30m available upon request.

Available from:

Industrial Communication Products Ltd
The Angel Business Centre,
1 Luton Road,
Toddington,
Bedfordshire,
LU5 6DE, UK.3DX_v1

www.industrialcomms.com
sales@industrialcomms.com

Tel: 0203 086 9569
Fax: 0203 002 5648