

**Product:** [DRAGON PTN2206, Chassis w. 6 Interfaces](#) 

**Full Gigabit MPLS-TP Switch with 6 media module slots**



**Product Description**

Full Gigabit MPLS-TP Switch with 6 interface options supporting 10 Gigabit XFP ports, Advanced Packet Transport features, redundant design with redundant CPU and power supply

**Technical Specifications**

**Product description**

Type:	DRAGON PTN2206
Name:	DRAGON PTN2206
Part Number:	942228002
Port type and quantity:	Up to 2 x 10 Gigabit Ethernet and 16 x 1 Gigabit Ethernet, modular design with various module configurations (PTN-4-E1T1-L, PTN-7-SERIAL, PTN-2-OLS, etc.), hot pluggable modules and power supply

**Network size - cascading**

Line - / star topology:	any
-------------------------	-----

**Power requirements**

Operating Voltage:	Built-in power supply - Internal and redundant, 175 W up to 1000 W rated power, PoE up to 480 W
--------------------	---

**Software**

Switching:	Sub 50ms protection switching in all network topologies (MPLS-TP), Non-blocking 64 Gbps, 95 Mpps (Layer 2 throughput), MTU up to 9k, 32k MAC addresses, 4k Layer 2 Multicast entries, 2k VFI, 4k MPLS entries, BFD hardware support
Management:	Auto provisioned and auto setup DCN for management, Full SNMP v3 management (no CLI needed), Management port on each CSM module, 2 input contacts allowing forwarding of local alarms to the TXCare platform, 2 output contacts for local triggering of alarms, Removable memory allowing easy replacement of CSM in the field, Hardware supported OAM, Automatic protection switching via BFD, LSP ping and LSP trace via BFD, Performance monitoring based on Y.1731 Loss and Delay
Diagnostics:	Advanced monitoring capabilities based on MPLS-TP OAM enhancements
Security:	Sticky MAC for easy locking of MAC address per service, MAC and IP based ACL, SNMPv3 encryption and authentication, Disable unused ports, Locked Node ID's, Logical separation of services, Centralized user authentication and central event logging, Audit trail
Management Software:	HiProvision platform for user friendly and fast deployment of the network. Supported by the automatic setup of the DCN and OAM features for continuous monitoring. SNMP v1/v2/v3

**Ambient conditions**

Operating temperature:	-30-+65 °C
Storage/transport temperature:	-30-+75 °C
Relative humidity (non-condensing):	10-95 %

**Mechanical construction**

Dimensions (W x H x D):	354 mm x 132.5 mm x 210 mm
Mounting:	19" Control Cabinet or DIN-Rail
Protection class:	IP20

**Approvals**

Basis Standard:	C-Tick, CE, EN 61131
Safety of industrial control equipment:	IEC 61850-3, IEEE 1613

## Scope of delivery and accessories

---

### Variants

Item #	Type
942228002	DRAGON PTN2206

Update and Revision: Revision Number: 0.36 Revision Date: 08-07-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.