

- EagleOne
 - 02
 - 00
 -
 -
 -
 - DD
 -
 - 0000
 - HH
 - E
 - XX.X
1. Product 2. FE ports 3. GE ports 4. Port 1 type 5. Port 2 type 6. Temp. range 7. Voltage range 8. Approvals 9. SW Pack 10. OEM 11. SW Conf. 12. SW version

1. Product	EagleOne	2 port Security Router
2. FE ports	02	2x 10/100 Mbit/s ports
3. GE ports	00	not available
4. Port 1 type 100 Mbit/s	T1 M2	1x Twisted Pair; RJ45 1x Multimode; D-SC
5. Port 2 type 100 Mbit/s	T1 M2 S2	1x Twisted Pair; RJ45 1x Multimode; D-SC 1x Singlemode; D-SC
6. Temperature range	S T E	Standard 0°C ... +60°C Extended -40°C ... +70°C Extended -40°C ... +70°C including Corformal Coating



7. Voltage range	DD	12 ... 48 VDC; 24 VAC red. input
8. Approvals	Z9 Y9 X9 W9 WX U9 UY UT T9 TY V9 VY VU VT	CE, FCC, C-Tick, EN61131, EN60950 „Z9“ + cUL508 „Z9“ + cUL508, ISA12.12 „Z9“ + ATEX „X9“ + ATEX „Z9“ + GL „U9“ + cUL508 „U9“ + cUL508, ISA12.12 „Z9“ + EN50121-4 „V9“ + cUL508 „Z9“ + IEC61850, IEEE1613 „V9“ + cUL508 „V9“ + cUL508, GL „V9“ + cUL508 + EN50121
9. SW - Package	0000	reserved
10. OEM Type	HH	Hirschmann
11. SW - Configuration	E	Entry (Hirschmann)
12. SW- version	XX.X	newest SW-version