

EKI-2525P EKI-2526PI

INDUSTRIAL
COMMS

5-port Industrial PoE Switch

6-port Industrial PoE Switch with Wide Temperature



Features

- ③ Provides 5/6 Fast Ethernet ports with 4 PoE ports with injector function
- ③ Supports 10/100 Mbps Auto Negotiation
- ③ Provides broadcast storm protection
- ③ Supports Ethernet ESD protection
- ③ Provides Slim size, DIN-rail/Wall mount with IP30 metal mechanism
- ③ Supports Redundant 48 V_{DC} power input and P-Fail relay
- ③ Supports operating temperatures from -10 to 60°C (EKI-2525P)
- ③ Supports wide operating temperature -40 ~ 75°C (EKI-2526PI)

Introduction

The EKI-2525P is a 5-port unmanaged PoE (Power-over-Ethernet) Industrial Ethernet switch and EKI-2526PI is a 6-port unmanaged PoE Industrial Ethernet switch, they support 4 PoE ports which are classified as power source equipments (PSE). The PoE devices makes centralized power supply come true and provides up to 15.4 watts of power per port. Advantech EKI PoE devices can be used to power IEEE 802.3af compliant powered devices (PD) by Ethernet cable and eliminates the need for additional power wiring. Advantech EKI PoE devices come equipped with all the standard features of the EKI family. Furthermore, it offers a 48 V_{DC} redundant power input design (EKI-2525P/EKI-2526PI), and is secured with a double protection mechanism; Power Polarity Reverse Protect and an Overload Current Resettable Fuse. Advantech EKI PoE devices come with compact metal housing that rates IP30 to help against from dusty industrial environments.

Specifications

Communications

- ③ **Standard** IEEE 802.3, 802.3u, 802.3x, 802.3af
- ③ **LAN** 10/100Base-T (X)
- ③ **Transmission Distance** Ethernet: Up to 100 m (EKI-2525P/EKI-2526PI)
- ③ **Transmission Speed** Up to 100 Mbps

Fiber Optics (EKI-252SPI)

- ③ **Single-mode** 1310 nm
- Tx Power: -8/-15 dBm
- Rx Sensitivity: -34 dBm
- Parameters: 9/125 um

Interface

- ③ **Connectors** PoE
- Ports: 4 (Ports 1 ~ 4)
- Ethernet x1 (EKI-2525P)
- Ethernet x2 (EKI-2526PI)
- 6-pin removable screw terminal (power & relay)
- ③ **LED Indicators** P1, P2, P-Fail
- 10/100TX: Link/Activity, Duplex/Collision

Power

- ③ **Power Consumption** EKI-2525P: 65 W
- (Full load PoE)
- EKI-2526PI: 62.6 W (Full load PoE)
- ③ **Power Input** 48 V_{DC} (EKI-2525P/EKI-2526PI),
- redundant dual inputs
- ③ **Power Output** 15.4 W at 48 V (per PoE port)
- ③ **Fault Output** 1 Relay Output

Mechanism

- ③ **Dimensions (W x H x D)** 37 x 140 x 95 mm (1.46" x 5.51" x 3.74")
- (EKI-2525P)
- 48.6 x 140 x 95 mm (1.91" x 5.51" x 3.74")
- (EKI-2526PI)
- ③ **Enclosure** IP30, Metal shell with solid mounting
- kits
- ③ **Mounting** DIN-rail, Wall

Protection

- ③ **Reverse Polarity** Present
- ③ **Overload current** Present

Environment

- ③ **Operating Temperature** -10 ~ 60°C (14 ~ 140°F) (EKI-2525P)
- 40 ~ 75°C (-40 ~ 167°F) (EKI-2526PI)
- ③ **Storage Temperature** -40 ~ 85°C (-40 ~ 185°F)
- ③ **Operating Humidity** 5 ~ 95% (non-condensing)
- ③ **Storage Humidity** 0 ~ 95% (non-condensing)
- ③ **MTBF** 440,132 hours


Certification

- ③ **Safety** UL 60950-1, CAN/CSA-C22.2 No. 60950
- ③ **EMI** FCC Part 15 Subpart B Class A, EN 55022
- Class A
- ③ **EMS** EN 61000-4-2
- EN 61000-4-3
- EN 61000-4-4
- EN 61000-4-5
- EN 61000-4-6
- EN 61000-4-8
- IEC 60068-2-27
- ③ **Shock** IEC 60068-2-32
- ③ **Freefall** IEC 60068-2-6
- ③ **Vibration** IEC 60068-2-6

Dimensions


Unit: mm [inch]

EKI-2525P



Panel Cut-out Dimensions: 104.00 x 140.00 x 36.60 mm (4.10" x 5.52" x 1.44")

EKI-2526PI



Panel Cut-out Dimensions: 104 x 140 x 48.6 mm (4.1" x 5.52" x 1.91")

Ordering Information

③	EKI-2525P	5-port Switch with 4 port-PoE
③	EKI-2526PI	6-port Switch with 4 port-PoE