

EKI-2525M EKI-2526M/S

4+1 100FX Port Multi-Mode/Single Mode Unmanaged Industrial Ethernet Switch
4+2 100FX Port Unmanaged Industrial Ethernet Switch



Features

- ③ Provides 4 x 10/100 Mbps Ethernet ports with RJ45 connector
- ③ Provides 1 x 100 Mbps Multi-mode SC type fiber optic port (EKI-2525M)
- ③ Provides 2 x 100 Mbps Multi-mode SC type fiber optic port (EKI-2526M)
- ③ Provides 2 x 100 Mbps Single-mode SC type fiber optic port (EKI-2526S)
- ③ Supports full/half duplex flow control
- ③ Supports MDI/MDI-X auto crossover
- ③ Provides broadcast storm protection
- ③ Provides redundant 12 ~ 48 V_{DC} power input
- ③ Provides flexible mounting: DIN-rail and Wall mount

Introduction

EKI-2525M/2526M/2526S are industrial-grade Ethernet switches that enable you to expand your industrial network fast and cost-effectively. The EKI-2525M/2526M/2526S have four 10/100 Mbps Ethernet ports, and additionally the EKI-2525M/2526M provides one or two multi-mode fiber-optic ports, while the 2526S provide one or two single-mode single-mode fiber-optic ports. Using fiber-optics, you can prevent noise from interfering with your system and supports high-speed (100 Mbps) and high-distance (up to 30 km) transmissions.

EKI-2525M/2526M/2526S have industrial-grade designs, assuring high reliability and stability in harsh environments, making it a robust bridge between enterprise fiber-optic backbones and Ethernet devices. EKI-2525M/2526M/2526S includes a switch controller that can automatically sense transmission speeds. The RJ45 interface can also be autodetected, so MDI or MDI-X is automatically selected and a crossover cable is not required. All the Ethernet ports have memory buffers that support the store and forward mechanism, assuring all data is transmitted properly.

Specifications

Communications

- ③ **Standard** IEEE 802.3, 802.3u, 802.3x
- ③ **LAN** 10/100Base-T (X), 100Base-FX
- ③ **Transmission Distance** Ethernet: Up to 100m
Multi-mode Fiber: Up to 2km (EKI-2525M/2526M)
Single-mode Fiber: Up to 30 km (EKI-2526S)
- ③ **Transmission Speed** Up to 100 Mbps
- ③ **Optical Fiber**
Wavelength: 1310nm Multi-Mode (EKI-2525M/EKI-2526M)
Tx Power: -14/-20 dBm
Rx Sensitivity: -31 dBm
Parameters: 50/125 um, 62.5/125 um
- ③ **Single-Mode (EKI-2526S)**
Wavelength: 1310 nm
Tx Power: -8/-15 dBm
Rx Sensitivity: -34 dBm
Parameters: 9/125 um

Interface

- ③ **Connectors** 4 x RJ45 ports
1 x SC type fiber connector (EKI-2525M) or
2 x SC type fiber connector (EKI-2526M/S)
- ③ **LED Indicators** P1, P2, P-Fail
10/100TX: Link/Activity, Duplex/Collision

Power

- ③ **Power Consumption** EKI-2525M: Max. 5W
EKI-2526M: Max. 6.41 W
EKI-2526S: Max. 6.45 W
- ③ **Power Input** 12 ~ 48 V_{DC}, redundant dual inputs
- ③ **Fault Output** 1 Relay Output

Mechanism

- ③ **Dimensions (W x H x D)** 37 x 140 x 95 mm (1.46" x 5.51" x 3.74")
- ③ **Enclosure** IP30, Metal shell with solid mounting kits
- ③ **Mounting** DIN-rail, Wall

Protection

- ③ **Reverse Polarity** Present
- ③ **Overload Current** Present

Environment

- ③ **Operating Temperature** EKI-2525M/2526M/2526S: -10~60°C (14~140°F)
- ③ **Storage Temperature** -40 ~ 85°C (-40 ~ 185°F)
- ③ **Operating Humidity** 5 ~ 95% (non-condensing)
- ③ **Storage Humidity** 0 ~ 95% (non-condensing)
- ③ **MTBF** 610,453 hours


Certification

- ③ **Safety** UL 60950-1, CAN/CSA-C22.2 Division 2
- ③ **EMI** FCC Part 15 Subpart B Class A, EN55022 Class A
- ③ **EMs** EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-8 IEC60068-2-27
- ③ **Shock** IEC60068-2-32
- ③ **Freefall** IEC60068-2-6
- ③ **Vibration** IEC60068-2-6

Dimensions


Unit: [mm]

EKI-2525M



Panel Cut-out Dimensions: 104 x 140 x 36.6 mm (4.1" x 5.52" x 1.44")

EKI-2526M/S



Panel Cut-out Dimensions: 104 x 140 x 36.6 mm (4.1" x 5.52" x 1.44")

Ordering Information

③	100FX Multi-mode	EKI-2525M	5-port Ethernet Switch w/ 1-port	③	EKI-2526S-ST	4-port Ethernet Switch w/ 2-port 100FX Single-mode (ST type connector)
③	100FX Multi-mode	EKI-2526M	4-port Ethernet Switch w/ 2-port	③	EKI-2526M-ST	4-port Ethernet Switch w/ 2-port 100FX Multi-mode (ST type connector)
③	100FX Single-mode	EKI-2526S	4-port Ethernet Switch w/ 2-port			

