

EKI-7706G-2F

EKI-7706G-2FI

4GE+2SFP Gigabit Managed Redundant Industrial Switch



Features

- ③ 4 Gigabit Ethernet ports with auto negotiation, MDI/MDI-X function, Full Duplex + 2 SFP ports
- ③ SFP socket for easy and flexible fiber expansion
- ③ Redundancy: X-Ring Pro (ultra-high-speed recovery time, <20 ms), RSTP/SPT (802.1w/1D)
- ③ IXM function enables fast deployment
- ③ Security: 802.1x (Port-based, MD5/TLS/TTLS/PEAP encryption), RADIUS
- ③ Management: SNMP v1/v2c/v3, WEB, Telnet, standard MIB, private MIB
- ③ Wide operating temperature range of -40 ~ 85°C (EKI-7706G-2FI)
- ③ Dual 12~48 V_{DC} power input and 1 x relay output
- ③ Supports Security Pack to fight against internal and external cyber

Introduction

The EKI-7706G-2F and EKI-7706G-2FI support 4 Gigabit Ethernet ports and 2 SFP ports. They provide abundant port options for connecting to various device types and are embedded with Advantech's IXM function, which can benefit users with faster deployment while saving considerably on engineering time and costs. The EKI-7706G series also supports NMS to help IT managers with networking maintenance and failure prevention. The series is equipped with X-Ring Pro, which can achieve ultra-high-speed recovery times of <20 ms, thus ensuring network stability.

Specifications

Interface

- ③ **I/O Port** 4x 10/100/1000BASE-T/TX RJ-45
2 x SFP (mini-GBIC) port
- ③ **Console port** RS-232 (RJ45)
- ③ **Power Connector** 6-pin screw terminal block (including relay)

- ③ redundant dual power input
- ③ 24V_{DC} Max
- ③ **Fault Output** 1 Relay Output 1A @
- ③ **Reverse polarity protection** Support
- ③ **Overload current protection** Support

Physical

- ③ **Enclosure** Metal Shell
- ③ **Protection Class** IP 30
- ③ **Installation** DIN-Rail
- ③ **Dimensions (W x H x D)** 43 x 120 x 84 mm (1.69" x 4.72" x 3.31")
- ③ **Switch Fabric Speed** 12Gbps
- ③ **Jumbo Frame** 9,216 Bytes

LED Display

- ③ **System LED** PWR1, PWR2, SYS, Alarm and R.M.
- ③ **Port LED** Link / Speed / Activity

Environment


- ③ **Operating Temperature** -40 ~ 85 °C (-40 ~ 185 °F) EKI-7706G-2FI
-10 ~ 60 °C (14 ~ 140 °F) EKI-7706G-2F
- ③ **Storage Temperature** -40 ~ 85 °C (-40 ~ 185 °F)
- ③ **Ambient Relative Humidity** 10 ~ 95% (non-condensing)
- ③ **Humidity** 10 ~ 95% (non-condensing)

Power

- ③ **Power Consumption** 5.28W @ 48V_{DC} (System)
- ③ **Power Input** 12~48V_{DC}

Dimensions

Unit: mm[inch]



Panel Cut-out Dimensions: 84 (3.31) x 120 (4.72) x 43 (1.69)

QoS

- ③ **Priority Queue** WRR (Weighted Round Robin), SP (Strict Scheduling Priority) hybrid priority
- ③ **Class of Service** IEEE 802.1p based
CoS, IP TOS, DSCP based CoS
- ③ **Rate Limiting** Ingress rate limit, egress rate limit
- ③ **Link Aggregation** IEEE 802.3ad
dynamic port trunking, static port trunking

Security

- ③ **Port Security** Static, Dynamic IP Source Guard, ARP Spoofing Prevention, Access Control List, DHCP Snooping
- ③ **Authentication** 802.1x (Port-Based, MD5/TLS/TTLS/PEAP Encryption), TACACS+

Management

- ③ **DHCP** Client, server, option 66/67/82
- ③ **Access** SNMP v1/v2c/v3, WEB, Telnet, RMON, standard MIB, private MIB
- ③ **Security access** SSH2.0, SSL
- ③ **Software upgrade** TFTP, HTTP, dual image
- ③ **NTP/SNTP client**

Ordering Information

- ③ **EKI-7706G-2FI-AE** 4GE + 2SFP Port Managed Ethernet Switch w/Wide Temp
- ③ **EKI-7706G-2F-AE** 4GE + 2SFP Port Managed Ethernet Switch

