



FIMP-XL

INDUSTRIAL COMPACT SPLICEBOX


The inner values of the FIMP-XL are really convincing and the installation is quite simple and done very fast.


FIMPXL is ready for splicing and it already contains splice tray, couplings, pigtails and cable gland. Regarding different couplings, you can choose from SMA, ST, SC, LC, FC-PC, SC-RJ, E-2000 and E-2000 COMPACT. The front panel and the splice cassette can be removed for splicing and since the cassette is magnetizable, it can easily be fixed onto a splice unit. The cassette has got a hole for splice units with a bolt.

The powder coated stainless steel housing is also magnetizable so that the splice box can easily be affixed to another housing or to a switch cabinet in case of no different tray. Furthermore, FIMP-XL has got a clip for DIN rail mounting (35mm) and a kit for wall fastening. Thus, there are space-saving and flexible solutions for mounting our FIMP-XL.

Additionally fiber optic cables with MPO can be adapted by using FIMPO. And the optional cap protects your fiber and connectors.

The systems are built up modular. Customizing is possible by different assemblies, colors of the housing or logos.









I



Accessories

Туре ММ	12xST Duplex 62MM	12xSC Duplex 62MM	6xLC Quattro 62MM	12xST Duplex 50MM	12xSC Duplex 50MM	6xLC Quattro 50MM			
Article no.	06100 2206 22069-00	06100 2236 22369-00	06100 2243 22439-00	06100 1216 12169-00	06100 1236 12369-00	06100 1246 00009-00			
Туре ЅМ	12xST Duplex SM	12xSC Duplex SM	12xSC 8°APC Duplex SM	6xLC Quattro SM					
Article no.	06100 3616 36169-00	06100 3706 37069-00	06100 3836 38369-00	06100 3646 00009-00					
Weight	860 g								
DIMENSIONS	Height: 138 mm; Width: 72 mm; Depth: 128 mm								
Operating Temperature	−40 °C − +75 °C								
Humidity	10 % – 95 % relative, non condensing								
Housing	Stainless steel, powder coated								
	Article no.		DESCRIPTION						
	0600E90001		Cable gland M20						
	0600E90002		Nut M20						
	0600E90003		Strain relief						
	0610E40014		Front panel SC Duplex, not assembled						
	0610E40012		Front panel E-2000 COMPACT, not assembled						
	0600E90007		Splice holder						
	0600E90008		Splice protection						
	0600E90009		Cable tie						
	0600E9001	D	Counter sunk screw						
	0600E90011		Screws						
	0600E9001	3	Dual Mount Kit						
	0600E90014		Lens tapping screw for fixing front panel,, Philipps screw, 2,2 x 9,5 mm						

Web: www.industrialcomms.com

Email: sales@industrialcomms.com