

## Industrial Ethernet - Industrial ADSL2+/VDSL2 Router





# **NV-600AI**

Industrial ADSL2+/VDSL2 Router

NV-600AI is an Industrial VDSL2 router equipped with four Gigabit LAN ports. It is compliant to ITU-T G.993.2 and G.993.5 standards and supports VDSL2 profile 30a that features 100Mbps of symmetric data. NV-600AI is perfectly suitable for triple-play applications. Housed in metal DIN rail enclosures, these routers are designed for harsh environments, such as industrial networking and utility market applications.

#### **Features**

- Supports G.993.5 Vectoring and ADSL2+
- Interoperable with major VDSL2 chipsets
- Supports up to VDSL2 profile 30a
- Supports up to 100 Mbps symmetric
- Supports Dying Gasp
- Supports SNMP v1 / v2c / v3

- Redundant dual DC input power 12~48VDC
- Wide operating temperature -20~70C
- Supports power failure alarm by relay
- IP 30 metal housing and DIN rail support
- Supports Dual Firmware Image Backup


#### **Specifications**

Physical	IEEE 802.310Base-T, 802.3u100Base-TX,
Interface	and 802.3z 1000Base-TX
	4x RJ-45 10/100/1000Mbps
	MTU: 1680 bytes (Jumbo frame)
	Reset Button (Factory Reset)
VDSL2 Interface Complies with ITU-T G993.2, G993.5	
	Co nnector: RJ-1 1/Terminal block
	PTM / ATM Transmission
	On-board surge protection
Indicators	LAN: Act/Link, Power
	VDSL2:Link
QoS	8 gueues MFC/DSCP
-	802.1p VLAN priority

Routing	IP Multicast, IGMP Proxy, Snooping
	Static Routing IPv4, IPv6 f orwarding
	DHCP Server/Relay/Client IPv4/IPv6
	DNS Proxy and Relay, NTP Client
Firewall	IPv6 Firewall
	Packet, URL filtering Parental Control, DMZ Host
Power	Redundant dual DC input power
Supply	12~48V (Removable Terminal Block)
Dimensions	182 x 142 x 35.5 mm (7.16" x 5.59" x 1.39")
Weight	About 0.79Kg
Temperature	-20 ~70 °C (Operating), -40 ~70 C°(Storage)
Humidity	5 - 95 % non-condensing
Certification	CE, FCC, RoHS Compliant

ID Multicast ICMD Drawy Chaming

### **Application**



#### **Proper Installation**

Train & Metro Stations > Boat and Submarine Military use > Military Training System > Parking system Weather Station > Amusement part > Farm > Jail & Oil Refinery > Telecom

sales@netsys.com.tw

\*Netsys reserves the right to change specifications without prior notice

Industrial Communication Products Ltd

Tel: +44(0) 203 086 9569

Web: www.industrialcomms.com

Email: sales@industrialcomms.com