

RUGGEDCOM RS900G



Product	Article number								
RUGGEDCOM RS900G	6GK6090-0GS2	.	-	0	.	A	.	-	Z
Power supply									
24 VDC (10 – 36 VDC)				1					
48 VDC (36 – 72 VDC)				2					
HI (88 – 300 VDC / 85 – 264 VAC)				3					
Mounting option									
No mounting kit						A			
Din rail mounting						B			
Panel mounting						C			
Manufacturing modification									
Standard								0	
Conformal coating								1	

Z options	Port 9 & 10
Dual 1000BASE-X SFP, Order SFP Optics Separately	A01
Dual 1000BASE-SX, Multi-mode, LC, 850nm 500nm	A02
Dual 1000BASE-LX, Single-mode, LC, 1310nm 10km	A03
Dual 1000BASE-LX, Single-mode, LC, 1310nm 25km	A04
Dual 1000BASE-LX, Single-mode, SC, 1310nm 10km	A05
Dual 1000BASE-LX, Single-mode, SC, 1310nm 25km	A06

Examples	Order code
RUGGEDCOM RS900G with 48 VDC (36 - 72 VDC), din rail mounting, standard coating and dual 1000BASE-SX, Multi-mode, LC, 850nm 500nm.	6GK6090-0GS22-0BA0-Z A02