

RUGGEDCOM RSG920P



Product	Article number								
RUGGEDCOM RSG920P	6GK6092-0PS2	.	-	0	.	A	.	-	Z
Power supply 1									
LO (9 – 60 VDC)			1						
HI (88 – 300 VDC / 85 – 264 VAC)			3						
Mounting options									
No mounting kit						A			
Din rail mounting option*						B			
Panel mounting option*						C			
Manufacturing modification									
None								0	
Conformal coating								1	
Explosive atmosphere modification								2	

Z options for...	Port 17	Port 18	Port 19	Port 20
No SFP Transceiver	A00	B00	C00	D00
SFP, 100BASE-FX, Multi-mode, LC, 1310 nm, 2 Km	A01	B01	C01	D01
SFP, 100BASE-FX, Single-mode, LC, 1310 nm, 20Km	A02	B02	C02	D02
SFP, 1000BASE-SX, Multi-mode, LC, 850 nm, 500 m	A03	B03	C03	D03
SFP, 1000BASE-LX, Single-mode, LC, 1310 nm, 10 Km	A04	B04	C04	D04
SFP, 1000BASE-LX, Single-mode, LC, 1310 nm, 25 Km	A05	B05	C05	D05
SFP, 1000BASE-LX, Single-mode, LC, 1550 nm, 70 Km	A06	B06	C06	D06

Examples	Order code
RUGGEDCOM RSG920P with HI (88 - 300 VDC / 85 - 264 VAC), panel mounting kit, explosive atmosphere modification, SFP, 1000BASE-LX, Single-mode, LC,1310nm, 25km; SFP, 100BASE-FX, Multi-mode, LC, 1310 nm, 2 Km; SFP, 1000BASE-LX, Single-mode, LC, 1550 nm, 70 Km; and SFP, 100BASE-FX, Single-mode, LC, 1310 nm, 20Km.	6GK6092-0PS2-0CA2-Z A05+B01+C06+D02