

# RUGGEDCOM RS940G



Product	Article number								
RUGGEDCOM RS940G	6GK6094-0GS2	.	-	0	.	A	.	-	Z
Power supply 1									
24VDC (10 – 36 VDC) (+/-)				1					
48VDC (36 – 72 VDC) (+/-)				2					
HI (88 – 300 VDC / 85 – 264 VAC)				3					
Mounting options									
No mounting hardware						A			
Din rail mounting option*						B			
Panel mounting option*						C			
Manufacturing modification									
None								0	
Conformal coating								1	

Z options for...	P7P8
XXXX = None	A00
Dual 10/100/1000BASE-TX, RJ45	A01
Dual 1000BASE-TX SFP (Mini-GBIC). Order SFP Optics Separately.	A02
Dual 1000BASE-SX, Multi-mode, LC, 850nm 500m	A03
Dual 1000BASE-LX, Single-mode, LC, 1310nm 10km	A04
Dual 1000BASE-LX, Single-mode, LC, 1310nm 25km	A05
Dual 1000BASE-LX, Single-mode, SC, 1310nm 10km	A06
Dual 1000BASE-LX, Single-mode, SC, 1310nm 25km	A07

Examples	Order code
RUGGEDCOM RS940G with 24VDC (10 - 36 VDC) (+/-), din rail mounting kit, conformal coating and dual 1000BASE-LX, Single-mode, LC, 1310nm 10km.	6GK6094-0GS21-0BA1-Z A04