

RUGGEDCOM i800 family



Product	Article number				
RUGGEDCOM i800	6GK6008-0AS20-0	.	.	.	- Z
RUGGEDCOM i800NC	6GK6008-0AS10-0				
Management options					
Managed with ROS			M		
Unmanaged			U		
Temperature option					
-20° C to +60° C				T	
-40° C to +85° C				U	
Manufacturing modification					
Standard					0
Conformal coating					1



Product	Article number				
RUGGEDCOM i801	6GK6008-1AS20-0	.	.	.	- Z
RUGGEDCOM i801NC	6GK6008-1AS10-0				
Management options					
Managed with ROS			M		
Unmanaged			U		
Temperature option					
-20° C to +60° C				T	
-40° C to +85° C				U	
Manufacturing modification					
Standard					0
Conformal coating					1



Product	Article number				
RUGGEDCOM i802	6GK6008-2AS20-0	.	.	.	- Z
RUGGEDCOM i802NC	6GK6008-2AS10-0				
Management options					
Managed with ROS			M		
Unmanaged			U		
Temperature option					
-20° C to +60° C				T	
-40° C to +85° C				U	
Manufacturing modification					
Standard					0
Conformal coating					1



Product	Article number				
RUGGEDCOM i803	6GK6008-3AS20-0	.	.	.	- Z
RUGGEDCOM i803NC	6GK6008-3AS10-0				
Management options					
Managed with ROS			M		
Unmanaged			U		
Temperature option					
-20° C to +60° C				T	
-40° C to +85° C				U	
Manufacturing modification					
Standard					0
Conformal coating					1

Examples

RUGGEDCOM i800 managed with ROS with temperature range of -40° C to +85° C and conformal coating.

Order code

6GK6008-0AS20-0MU1-Z