

120V GeoTask Tunable Wet Location Surface Mount Specification Sheet

PROJECT	ТҮРЕ

CATALOG NUMBER (FOR CUSTOM LENGTHS, PLEASE SEE ORDERING EXAMPLE BELOW)

PRODUCT OVERVIEW

Now available with adjustable kelvin temperature (2700K, 3000K, 4000K), GeoTask represents simplicity in design paired with cutting edge technologies that includes EdgeLit lighting that evens out any hot spots or glare. Available in 5", 8" and 12" diameters.

KEY FEATURES

- 120V
- Tunable white (2700K, 3000K, 4000K)
- IP54 wet location
- Edge-Lit technology for diode free illumination
- · ADA compliant when wall mounted
- Dimmable (Triac)
- Shallow mount
- Plastic non-conductive housing face **ELECTRICAL**
- 120V (remote power supply not required)

 OPTICS
- 90+ CRI


CERTIFICATION

- ETL
- Title 24 JA8
- Energy Star

WARRANTY

• 5 year warranty







PRODUCT ORDERING

Catalog Number	Trim Dimensions	Wattage	Lumens	CRI	Finish
GM-RND5-TUN-WH	5" Dia.	10W	550, 600, 650	90+	White
GM-RND8-TUN-WH	8" Dia.	15W	850, 900, 950	90+	White
GM-RND12-TUN-WH	12" Dia.	23W	1450, 1475, 1500	90+	White

