



LIFELINE™ ADVANCE



Exterior Clear Topcoat

LIFELINE ADVANCE Gloss / Satin Clear Topcoat is designed to go over all LIFELINE exterior finishes. In addition to enhancing the beauty of the finish, its advanced formulation imparts an extra measure of water repellency and ultraviolet (UV) resistance along with mold and mildew protection to extend the life of your stain. Since any LIFELINE exterior finish can be applied over an existing coat of LIFELINE ADVANCE Gloss or Satin, future maintenance will be simple and easy to perform.

BREATHABLE ~ WATER-BASED ~ FLEXIBLE

For Application Over Previously Stained Surfaces

STIR WELL BEFORE AND DURING USE

LIFELINE ADVANCE™ Exterior Clear Topcoat

DO NOT APPLY TO BARE WOOD. LIFELINE Advance Gloss or Satin Clear Topcoat is designed to go over all LIFELINE exterior finishes. However over white pigmented stains we recommend using only Advance Satin, not Gloss. In addition to enhancing the beauty of the finish, its advanced formulation imparts an extra measure of water repellency and ultraviolet (UV) resistance along with mold and mildew protection to extend the life of your stain. Since any LIFELINE exterior finish can be applied over an existing coat of LIFELINE Advance Gloss or Satin, future maintenance will be simple and easy to perform.

STEP #1: INSPECTION

Check over your existing finish to make sure it is in good condition. If necessary, apply a new coat of LIFELINE stain or touch up those areas that show signs of wear or weathering.

STEP #2: SURFACE PREPARATION

All surfaces should be free of dirt, dust, mold and mildew. Use appropriate materials to clean and prepare surfaces. If more than a week has passed since the surface was stained, we recommend washing down the logs with an appropriate cleaning solution such as Log Wash™ (2 cups of Log Wash per gallon of water), rinse well and allow to dry before applying LIFELINE Advance. Contact any Perma-Chink Systems office for information about cleaning your logs. **DO NOT USE LIFELINE ADVANCE ON SURFACES THAT HAVE BEEN BRUSHED OR RUBBED WITH STEEL WOOL. IF YOU DO, RUST SPOTS MAY APPEAR UNDER THE FINISH.**

STEP #3: APPLICATION

COVERAGE RATE – Coverage is approximately 800 – 1000 square feet per gallon depending on wood texture. LIFELINE ADVANCE Gloss or Satin may be applied over existing LIFELINE stains, topcoats, caulks, chinking or other sealants. **DO NOT USE THINNERS. STIR THOROUGHLY before and regularly during use.** LIFELINE Advance may be applied with a brush or airless sprayer. **DO NOT APPLY TO HOT SURFACES OR IN DIRECT SUNLIGHT.** Do not apply when the surface temperature is below 40° F or above 90° F. **Back brushing is required** to avoid drips and runs and to achieve optimum performance.

We recommend that you make a test application on a small area to get a feel for the product before you start on an entire wall. Apply no more than one coat of LIFELINE ADVANCE at a time. Dry and cure time will vary with the method of application, type of surface, age and texture of wood. Typically LIFELINE ADVANCE will dry to touch in 30-45 minutes but complete cure requires 72 hours.

LIFELINE ADVANCE should always be applied as a thin coat. Always back brush to ensure even coverage and to avoid visible drips and runs.

STEP #4: CLEANUP

Clean area and equipment immediately with warm, soapy water. For sprayers and other commercial equipment, follow the manufacturer's directions. For removing LIFELINE Advance that has dried, soften with alcohol or mineral spirits and then clean with warm water. Please do not pollute our environment. Dispose of containers and unused material in accordance with local, state, and federal regulations.

STEP #5: MAINTENANCE

Periodic cleaning with an appropriate cleaner such as Log Wash™ helps extend the life of the finish and accentuates the beauty of your home. We recommend that log walls be washed down at least twice a year. Wood checking, cracking and shrinkage may eventually expose unprotected wood. Apply periodic maintenance coat only as needed paying special attention to the south and west sides of the home as they may have greater exposure to the elements.

STEP #6: STORAGE

Store LIFELINE Advance out of direct sunlight and **protect from freezing.** Although LIFELINE Advance is freeze-thaw stable, if the product is accidentally frozen, allow to thaw, mix well and check for suitability of use before applying.

Contact any Perma-Chink Systems office for additional information about applying and maintaining LIFELINE stains and topcoats.



LIMITED WARRANTY

Perma-Chink Systems, Inc. warrants and represents that Perma-Chink Systems Family of Products will conform to the description and specifications previously set forth and be free from defects in material and workmanship when shipped to the buyer. EXCEPT WHEN HEREIN EXPRESSLY STATED, THERE ARE NO WARRANTIES, EXPRESSED OR IMPLIED, BY OPERATION OF LAW OR OTHERWISE, APPLICABLE TO THE PERMA-CHINK LOG HOME PRODUCT. PERMA-CHINK SYSTEMS EXPRESSLY DISCLAIMS ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.