Check Mate 2

Stress Crack and Check Filler

- Bonds tightly to wood.
- Prevents water from getting into logs causing rot.
- Stretches as checks open and close.
- Prevents air infiltration into home.
- Can be used in gaps up to one inch wide.
- Easy to use.
- Soap and water clean up.
- Accepts colored stain.

Fills and seals cracks and checks in logs, timbers and siding.

CHECK MATE 2 forms a tough, smooth elastic seal that prevents water from getting into the wood and cold air into the home through cracks or checks in logs, timbers, and siding. Although caulks may seem an obvious choice for this application, they are limited in their ability to withstand the rigorous conditions posed by the repeated opening and closing of a check from season to season. It is especially important to seal upward-facing checks that accumulate water.

Application Instructions

Begin by cleaning the check or crack of any dust, dirt oil, solvent or previous sealer. If the check is upward-facing or has allowed previous water penetration, pour some Shell-Guard® RTU into it and allow to dry before proceeding. This will kill any decay fungi present and prevent further deterioration of the log.

Using masking tape, mask off the wood on either side of the check. For checks 1/4" wide or larger, insert appropriately sized backer rod. Cut the tip of the tube to the approximate size of the check. CHECK MATE 2 may then be applied into the check using a standard caulk gun. CHECK MATE 2 must have good contact with wood on either side of the check. Be sure the crack or check is completely sealed from end to end. Tool surface smooth with a wet finger or trowel and remove overflow immediately with a damp cloth. Masking tape should be removed while the CHECK MATE 2 is still wet.

Clean Up: Wash hands and tools with soap and warm water.

Coverage: One tube of CHECK MATE 2 will fill 11 to 16½ linear feet of a gap ½" wide.

11 fl. 0z. (325 ml.)

CAUTION: Do Not Take Internally 2/07



LIMITED WARRANTY

PERMA-CHINK SYSTEMS, Inc. warrants that Check Mate 2, when applied according to manufacturer's specifications and instructions, is free from defects and will perform as described in the manufacturer's publications. PERMA-CHINK SYSTEMS, Inc. entire responsibility under this warranty will be to replace materials that have proven to be defective, provided that not more than five years have elapsed since the original purchase.