



## ELASTOMERIC SMOOTH PAINT

- Restores Original Beauty to Synthetic Chinking
  - Flexibility Allows Movement with Existing Chinking
  - Will Not Crack, Chip or Peel
  - Resists UV Light and Water Penetration
  - Safe Latex Base Allows Easy Water Cleanup
- 
-

# CHINK-PAINT™ SMOOTH

## GENERAL INFORMATION

- White, # 207
- Stone, # 211
- Light Gray, # 212
- Sandstone, # 215
- Beige, # 216
- Tan, # 219
- Brown, # 223
- Medium Gray, # 224
- Other  
# \_\_\_\_\_

Chink-Paint Smooth is a highly elastomeric smooth latex coating for renewing the appearance or changing the color of synthetic log home chinking. Its high degree of elasticity enables it to expand and contract with synthetic chinking without cracking or peeling. It has excellent water resistance and is also mildew resistant. Chink-Paint Smooth is available in all standard Perma-Chink colors in both one and five gallon pails.

Using Chink-Paint Smooth is often helpful in giving a “face-lift” to log homes. In the past, when applying maintenance coats of stain (which can discolor synthetic chinking), it was necessary to mask off the chink joint or do a tedious brush application of the stain. Now, using Chink-Paint Smooth, you can spray apply LIFELINE over chinking, log and all. After the stain has dried, you can then go back and brush apply the Chink-Paint Smooth to the joints – a real labor and time saver.

## APPLICATION INSTRUCTIONS

The substrate should be clean, free of oils or water repellents and completely dry before application. Any dirt or discolorations should be removed with our Wood ReNew or Log Wash. Thoroughly rinse and allow to dry before applying Chink-Paint Smooth.

- Chink-Paint Smooth should be thoroughly stirred before use and occasionally during use.
- Use a synthetic bristle brush slightly smaller than the joint size to be painted.
- Any spills, drips or runs should be cleaned up immediately with soap and water or a wet cloth.
- Clean tools and brushes with soap and water.
- Do not apply when the temperature is below 40° F or above 100° F.
- Do not allow product to freeze.
- Store unused portion in tightly sealed container away from high heat or freezing temperatures.
- Keep out of reach of children and pets.

## Coverage:

Approximately  
200-250 sq. ft.  
per gallon.

### LIMITED WARRANTY

Perma-Chink Systems, Inc. warrants and represents that Perma-Chink Systems Family of Products will conform to the description and specifications previously set forth and be free from defects in material and workmanship when shipped to the buyer. EXCEPT WHEN HEREIN EXPRESSLY STATED, THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, BY OPERATION OF LAW OR OTHERWISE, APPLICABLE TO THE PERMA-CHINK LOG HOME PRODUCT. PERMA-CHINK SYSTEMS EXPRESSLY DISCLAIMS ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

**PERMA-CHINK®**  
**SYSTEMS, INC.**