

WOOD guard ITF®



INTERIOR TRANSPARENT FINISH

ACRYLIC TRANSPARENT LATEX

- CLEAR • IDEAL FOR LOG HOMES • HIGHLIGHTS WOOD GRAIN
- WATER REPELLENT • BREATHABLE FINISH

KEEP OUT OF REACH OF CHILDREN WARNING

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

Manufactured for:

ISK Biocides, Inc.

416 East Brooks Road • Memphis, TN 38109

901-344-5350

IBD-PL-405A
80072

6/20

WOODguard ITF®

Causes skin irritation.
Causes serious eye irritation.
Suspected of causing cancer.



Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Wash hands thoroughly after handling.
Wear protective gloves/eye protection/face protection.
IF ON SKIN: Wash with plenty of soap and water.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
If skin irritation occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
If exposed or concerned: Get medical advice/attention.
Take off contaminated clothing and wash before reuse.
Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations.

For product emergencies, call Chemtrec at
1-800-424-9300

 **WARNING: Cancer -**
www.P65Warnings.ca.gov

DIRECTIONS FOR USE

WOODguard ITF® Interior Transparent Finish contains a high-density, acrylic transparent latex and gives a transparent, breathable finish. It has an initial “milky” appearance, which forms a clear, protective coating. This product is non-flammable and has very little odor. Use this product on interior log surfaces, paneling, unpainted doors and trim. Specifically designed for raw wood. Not suggested for floors.

Surface Preparation: Lacquer, shellac, wax, grease, dirt, mold and old finishes should be removed before application. Sand clean, dry wood with an 80 to 120-grain sand paper to obtain a uniform appearance. Ensure that the wood surface is thoroughly dry before application (less than 18% moisture content). Remove all surface dust with a damp rag.

- Stir well before and occasionally during use. For best results, do not apply below 50°F.
- Apply a **thin** coat in the direction of the grain, working the material into the fibers of the wood. Expect coverage of approximately 500 square feet to the gallon for smooth wood; 250 square feet per gallon for rough wood on the first coat. The second coat will cover a greater surface area than the first.
- Maintain a wet edge.
- Brush, roll or spray application is suitable.
- Promptly clean all tools, rags, etc. with warm, soapy water.
- Wait at least one hour or until dry to the touch before very gently sanding with a 180-grain sandpaper. Remove all superficial dust with a damp rag before applying a second coat. Two coats are sufficient. Do not use steel wool.
- WOODguard ITF may be tinted with Universal or Water-based Machine Colorants by qualified professional paint store personnel. **NEVER** use an oil based pigment to tint ITF. A light semi-transparent stain can be obtained using between 0.5 and 1.5 ounces of pigment per gallon. **NEVER** exceed 1.5 ounces of pigment per gallon to avoid streaking and other appearance issues. Solid colors cannot be achieved. Consult your dealer for assistance.
- When pigmented, this product can be used as a wiping stain. Brush in the direction of the grain, and wipe off within several minutes. For deep intensity, brush on additional coats.
- VOC-compliant

WARRANTY AND LIMITATION OF DAMAGES

Seller warrants to those persons lawfully acquiring title to this product that at the time of the first sale of this product by seller this product conformed to its chemical description and that it was reasonably fit for the purposes stated on the product label when used both in accordance with the Direction for Use appearing on the product label and under normal conditions of use. Buyers and users of this product assume the risk of all loss or damage from use or handling of this product that results from their failure to read and comply with the Directions for Use of this product which appear on the product label. SELLER MAKES NO OTHER EXPRESS OR IMPLIED WARRANTY, INCLUDING ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS OR OF MERCHANTABILITY, AND NO AGENT OF SELLER IS AUTHORIZED TO DO SO. Unless expressly prohibited by state law, the liability of seller for any breach of warranty shall not exceed the purchase price of the product as to which a claim is made.