



Sicamu, Inc.
1066 Strong Road
Quincy, Fl, 32351
850-2706283

SECTION I. IDENTIFICATION

Name of the Manufacturer: SICAMU Inc.

Commercial name: SQ Tire Shine

Address:
Manufacturer:
1066 Strong Road, Quincy, Fl, 32351
Telf.: +1 (850) 270.62. 83
Fax: +1 (850) 875.45.18

Type of product: Silicone based tire shine.

SECTION II. HAZARD IDENTIFICATION

Is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids category 1

Skin corrosion/irritation category 2

2.1 Classification of the substance or mixture: Specific target organ toxicity (single exposure) (narcotic effects) category 3

Aquatic hazard (acute) category 1

Aquatic Hazard (long term) category 1

2.2 Label elements:



Danger, extremely flammable liquid and vapor. May form explosive mixture with air, causes skin irritation, may cause drowsiness and dizziness, very toxic to aquatic life, very toxic to aquatic life with long lasting effects.



Sicamu, Inc.
1066 Strong Road
Quincy, FL, 32351
850-2706283

Read label before use. Keep out of reach of children and pets. If medical advice is needed, have product container or label at hand.

Keep away from heat, sparks, open flame and hot surfaces. No smoking, use non-sparking tools. Take precautionary measures against static discharge, keep container tightly closed. Use only outdoors, or well ventilated areas. Avoid release to the environment, breathing vapors. Wash hands after handling

POTENTIAL HEALTH EFFECTS

| | |
|---------------------------------|-----------------------------------------------------------------------------------------|
| Eye contact: | It causes red eyes and serious irritation. Rinse with abundant water. |
| Skin contact: | It may cause irritation. Remove clothes. Rinse with water and soap. |
| Ingestion or inhalation: | Remove person to well ventilated area. Call a poison center if dizziness occurs. |
| Ventilation: | It's recommended to use this product in open areas or places with adequate ventilation. |

SECTION III. COMPOSITION/INFORMATION ON INGREDIENTS

| Name | CAS | % Weight |
|----------------------|------------|-----------------|
| n-Heptane | 142-82-5 | 63-81% |
| Polydimethylsiloxane | 63148-62-9 | 37-19% |

SECTION IV. FIRST-AID MEASURES

| | |
|----------------------|---------------------------------------------------------------------------------------------------------|
| Eye contact: | Rinse with water for 15 minutes. Remove contact lenses. Get medical attention. |
| Skin contact: | Rinse skin with soap and water. Clean clothes before using them again. Get medical attention if needed. |
| Inhalation: | Move to open area, get medical attention if needed. |
| Ingestion: | Do not induce vomit. Rinse mouth with water, if symptoms develop contact a doctor. |



Sicamu, Inc.
1066 Strong Road
Quincy, FL, 32351
850-2706283

Most important symptoms and effects

Treat symptomatically. Eyes are most sensitive part of the body, while handling the concentrate. Protective gear is recommended.

SECTION V. FIRE-FIGHTING MEASURES

Extinguishing media: Use water spray, foam or carbon dioxide (CO₂). Do not use water jet.

Special fire fighting procedures: Eliminate all ignition sources. Use fire extinguishers on the ignition source. Use appropriate fire extinguishing gear. Avoid flow of materials to sewers.

| NFPA | Health | Flammability | Instability | Physical Hazards |
|------|--------|--------------|-------------|------------------|
| | 2 | 3 | 0 | NA |

SECTION VI. ACCIDENTAL RELEASE MEASURES

General measures: Isolate from fire

For non-emergency personal: gloves, protective goggles, protective clothes. Evacuate and avoid unnecessary risks

For emergency responder: equip cleanup crew with proper protection.

Methods and material for containment and pickup: for small amounts pick up with absorbent materials, dispose according to regulations. For large amounts, pump off product, spills should be contained, though product is not flammable and readily biodegradable.

SECTION VII. HANDLING AND STORAGE

| | | |
|-----------------------------|-------------------|------------------|
| Storage temperature: | Max: 49°C (120 F) | Min: 0 °C (32 F) |
|-----------------------------|-------------------|------------------|

Handling and storage:

Storage in a dry, cool, ventilated area.

Prevent leaks.

Keep away from sparks and ignition sources.



Sicamu, Inc.
1066 Strong Road
Quincy, FL, 32351
850-2706283

| | |
|--|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | <p>Do not inhale, ingest or spray to the eyes.</p> <p>Keep out of the reach of children.</p> <p>Do not puncture or burn the container.</p> <p>Do not use on running machines.</p> <p>Product should not enter in contact with acids or strong oxidizing agents.</p> |
|--|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

SECTION VIII. EXPOSURES CONTROL/PERSONAL PROTECTION

| | |
|-------------------------------------|--------------------------------------------------------------------------------------------------------------|
| Eye protection: | Recommended when using fully concentrated product. |
| Skin protection: | Recommended when using fully concentrated product. |
| Respiration and ventilation: | Ensure adequate ventilation. |
| Ingestion: | Product should never be ingested. If ingested do not incite vomit, prevent swallowing or sucking into lungs. |
| Exposure limits: | Not established for product as a whole |

SECTION IX. PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|--------------------------------|---------------------------|------------------------------------|-------------|
| Boiling point (°C): | Aprox 100°C at 100 kPa | Specific weight (water =1): | 0.7 gr/cc |
| Vapor pressure (mmHg): | 4.6 kPa | Color: | Transparent |
| Vapor density (Air =1): | 3.46 | Odor: | Lime |
| pH @ 100%: | Not applicable | State: | Liquid |
| Volatiles % (volume): | 70% | Viscosity: | |
| Water solubility: | Not soluble | pH : | NA |
| Pressure: | Not applicable | | |



Sicamu, Inc.
1066 Strong Road
Quincy, FL, 32351
850-2706283

SECTION X. STABILITY AND REACTIVITY

| | |
|-----------------------------|----------------------------------------------------------------------------------|
| Stability: | Stable. |
| Conditions to avoid: | Do not expose to open flame, do not puncture. Do not mix with alkaline products. |
| Incompatibilities: | Oxidizing materials. |

SECTION XI. TOXICOLOGICAL INFORMATION

| | |
|------------------------------------------|-----------------------------------------------------------------------|
| Accute eye contact: | Will cause severe eye irritation. No data for the product as a whole. |
| Accute and chronicl skin contact: | May cause irritation. No data for the product as a whole. |
| Accute and chronicl inhalation: | May cause irritation. No data for the product as a whole. |
| Accute and chronicl ingestion: | May cause irritation. No data for the product as a whole. |
| Exposure limits: | Not stablished for product as a whole |

SECTION XII. ENVIRONMENTAL INFORMATION

Acute toxicity in water, with high bioaccumulative potential



Sicamu, Inc.
1066 Strong Road
Quincy, FL, 32351
850-2706283

SECTION XIII. DISPOSAL INFORMATION

Disposal:

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers

SECTION XIV. TRANSPORT INFORMATION

Heptane

DOT, TDG, IATA:
UN number: UN1206, Shipping name: heptanes
Transport hazard class: 3, packing group: II
Environment: no
IMDG:
UN number: UN1206, Shipping name: heptanes
Transport hazard class: 3, packing group: II
Environment: yes
Marine pollutant mark is not required if transported in sizes smaller than 5 liters.

SECTION XV. REGULATORY INFORMATION

US Federal Regulations: TSCA 8(a) Pair: heptane, TSCA 12(b) one time export: heptane,



Sicamu, Inc.
1066 Strong Road
Quincy, FL, 32351
850-2706283

SECTION XVI. OTHER INFORMATION

Distributed by: Authorized dealers.

Written by: Antonio Pons, Technical Director, VP of Operations

Date: June 13, 2016

Guarantee waiver:

This information is accurate and reliable to the best knowledge of Sicamu Inc. No representation, warranty or guarantees are made to its accuracy, reliability or completeness. All users are encouraged to review this MSDS in the context of how to use and handle this product. Users are responsible for any interpretation and/or use of this information and of this product.

If clarification or further information is required, the user is responsible for contacting Sicamu Inc. to receive any additional information that he may require.

Our responsibility for products sold is subject to our standard terms and conditions. A copy of which is available on request.