

TE-CD 18/40 Li-i-Solo



18V ½" Cordless Drill Driver with Carrying Case

Article no.	4513945

UPC 7-72995-01752-2

Features

- A member of the Power X-Change family, 1 x 18V battery is necessary for operation
- Practical belt clip for efficient and safe operation
- 2-speed gearing for powerful drilling and screwing
- Speed electronics for material and application suitable working
- Always ready-for-use due to Li-ion technology without discharging
- Complete with LED lamp to illuminate the work area
- Extremely easy to work with due to ergonomic design and soft grip surfaces
- Supplied in E-Box case
- Recommended for maximum results 2.0 or 2.5 Ah battery
- Battery and charger sold separately

Technical data

Number of gears 2

Idle speed (gear 1)
 Idle speed (gear 2)
 0-400 RPM
 0-1500 RPM

Max. torque 354 in/lbs
Number of torque steps 21 settings

Drill chuck ½"| single sleeve

Logistic data

Product weight
Gross weight single packaging
Dimensions single packaging
7.875" x 3.25" x 7.625"
Pieces per export carton
Gross weight export carton
Dimensions export carton
12.75" x 9" x 8.625"
Container quantity (20'/40'/40'HC)
6800

One Battery for All	screwing (pieces)
1.5 Ah	230
2.0 Ah	305
2.5 Ah	380
3.0 Ah	460
4.0 Ah	610
5.2 Ah	770
6.0 Ah	920





















TP-CD 18 Li-BL-Solo



18V ½" Cordless Drill Driver

Article No. 4513893

UPC 7-72995-01755-3

Features

- A member of the Power X-Change family, 1 x 18V battery is necessary for operation
- Brushless motor more power for prolonged operation
- High-grade ½" metal drill chuck
- Practical belt clip for efficient and safe operation
- 2-speed gearing for powerful driving and fast drilling
- Quick-stop for changing tools quickly and easily
- Ergonomic design with soft grip surfaces
- Less strain on the joints during operation thanks to additional handle
- Complete with LED lamp to illuminate the work area
- Recommended for maximum results 2.0 or 2.5 Ah battery
- Battery and charger sold separately

Technical data

Idle speed (gear 2)

Number of gears 2

Idle speed (gear 1) 0-500 RPM

Max. torque 531 in/lbs

Number of torque steps 20 settings

Drill chuck ½"| single sleeve

0-1800 RPM

Logistic data

Product weight 2.86 lbs Gross weight single packaging 4.11 lbs

Dimensions single packaging 10" x 3.125" x 8.5"

Pieces per export carton 3 pcs. Gross weight export carton 13.6 lbs

Container quantity (20'/ 40'/40'HC) 3645 / 7290 / 8475



One Battery for All	screwing ¹ (pieces)
1.5 Ah	265
2.0 Ah	350
2.5 Ah	440
3.0 Ah	530
4.0 Ah	700
5.2 Ah	920
6.0 Ah	1060





















TE-CD 18/48 Li-i-Solo



18V ½" Cordless Hammer Drill/Driver

Article No. 4513937

UPC 7-72995-01751-5

Features

- A member of the Power X-Change family, 1 x 18V battery is necessary for operation
- Impact drilling function for universal operation
- 2-speed gearing for powerful drilling and screwing
- Practical belt clip for efficient and safe operation
- Complete with LED lamp to illuminate work area
- Extremely easy to work with ergonomic design and soft grip surfaces
- Recommended battery for maximum results 2.0 or 2.5 Ah battery
- Battery and charger sold separately

Technical data

•	Number of gears	2
---	-----------------	---

Idle speed (gear 1) 0-400 RPM

Idle speed (gear 2) 0-1500 RPM

Max. torque Number of torque steps 23 settings

Drill chuck 1/2" | single sleeve

390 in/lbs

Drilling capacity in concrete 13/32"

Impact rate (gear 1) 0-6400 BPM

Impact rate (gear 2) 0-24000 BPM

Logistic data

Product weight Gross weight single packaging Dimensions single packaging Dimensions export carton Container quantity (20'/40'/40'HC) 3.1 lbs 4 lbs 8" x 3.125" x 9.375" 15.125" x 10.25 " x 8.625" 5076 | 10164 | 0

Battery Runtime

1) 6x60 mm

One Battery for All	screwing ¹ (pieces)
1.5 Ah	230
2.0 Ah	310
2.5 Ah	380
3.0 Ah	460
4.0 Ah	620
5.2 Ah	780
6.0 Ah	910
Test setup:	



















TE-CD 18/40-1 Li (2 x 2.0 Ah)



18V ½" Cordless Drill Driver Kit

With 2 x 2.0 Ah Batteries, 30 Min Charger & Carry Case

Article No.	4513979
-------------	---------

UPC 7-72995-01753-9

Features

- A member of the Power X-Change family
- 2-speed gearing for powerful drilling and screwing
- Practical belt clip for efficient and safe operation
- Complete with LED lamp to illuminate the work area
- Extremely easy to work with ergonomic design and soft grip surfaces
- Supplied with two 2.0 Ah batteries and 30 minute charger
- Comes in a carry case

Technical data

Number of gears

• Battery 18 V | 2.0 Ah| Li-lon

2

Charging time 30 min

Idle speed (gear 1) 0-400 RPM

Idle speed (gear 2) 0-1500 RPM

Max. torque 354 in/lbs

Number of torque steps 21 settings

Drill chuck ½"| single sleeve

Logistic data

Pieces per export carton 4 pcs.
Gross weight export carton 36.74 lbs
Product weight 4.84 lbs
Gross weight single packaging 8.55 lbs

Dimensions single packaging 13.75" x 4" x 16.625"

Dimensions export carton 17.8125" x 14.625" x 14.8125"

Container quantity (20'/40'/40'HC) 1768 | 3668 | 4300

Battery Running Time

One Battery for All	screwing ¹
	(pieces)
1.5 Ah	230
2.0 Ah	305
2.5 Ah	380
3.0 Ah	460
4.0 Ah	610
5.2 Ah	770
6.0 Ah	920
est setup:	
) screws - 6x60 mm	

















TE-TK 18 Li Kit



18V Cordless ½" Drill/Driver & ¼" Impact Kit With 2 x 2.0 Ah Batteries, 30 Minute Charger & Carry Bag

Article No.	4257245
AFFICIA NIO	4/5//45
AICICIC INO.	763/673

UPC 7-72995-01754-6

Kit-Included

- 2 x 18V 2.0 Ah batteries
- Charger
- 18V 1/4" Cordless Impact Driver (4510060- TE-CI 18/1 Li)
- 18V ½" Cordless Drill Driver (4513945- TE-CD 18/40 Li)

A member of the Power X-Change family

Ergonomic design and soft grip surfaces

2-speed gearing for powerful drilling and screwing

Complete with LED lamp to illuminate the work area

Recommended for maximum results 2.0 or 2.5 Ah battery

Practical belt clip for efficient and safe operation

Einhell soft bag (4530010)

Features (4513945)

Logistic Data

- Pieces per export carton: 2 pcs. Gross weight export carton: 27.5 lbs
- Dimensions export carton: 20.5" x 13.75" x 12.375"


940 / 1940 / 2290


Container quantity (20'/40'/40'HC)


Features (4510060)


- - Hammer screwdriver for effortlessly tightening large/long screw
 - Low reverse torque reduces strain on the wrists during operation
 - Short, lightweight design with ergonomic Soft grip surfaces
 - 1/4" hex. bit (Recommendation: impact-resistant bits)
 - Speed control for fine adjustment on delicate jobs
 - 3 powerful LED to illuminate the work area
 - Rugged aluminum housing and rubber supports for protection
 - Recommended battery for maximum results 2.0 or 2.5 Ah battery
























TE-CI 18/1 Li-Solo



18V 1/4" Cordless Impact Driver

4510060

UPC 7-72995-01757-7

Features

- A member of the Power X-Change family, 1 x 18V battery is necessary for operation
- Practical belt clip for efficient and safe operation
- Hammer screwdriver for effortlessly tightening large/long screw
- Low reverse torque reduces strain on the wrists during operation
- Short, lightweight design with ergonomic Soft grip surfaces
- 1/4" hex. bit (Recommendation: impact-resistant bits)
- Speed control for fine adjustment on delicate jobs
- 3 powerful LED included for good all round illumination
- Rugged aluminum housing and rubber supports for protection
- Recommended battery for maximum results 2.0 or 2.5 Ah battery
- Battery and charger sold separately

Technical data

•	No load speed	0 - 2300 RPM
•	Impacts per minute	0 – 2900 IPM
•	Tool collet (hex.)	¼" Bit holder
•	Type of bit interlock	Mechanic locking sleeve

• Max. torque 1240 in/lbs

Logistic data

1) wheel nuts

Product weight	2.57 lbs
Gross weight	3.27 lbs
Pieces per export carton	10 pcs.
Gross weight export carton	34.5 lbs
Dimensions Export Carton	16.75" x 14" x 9"
Container quantity (20'/40'/40'HC)	7780 / 0 / 0

One Battery for All	(pieces)
1.5 Ah	140
2.0 Ah	185
2.5 Ah	230
3.0 Ah	280
4.0 Ah	370
5.2 Ah	520
6.0 Ah	560



















TP-CI 18 Li BL-Solo



18V 1/4" Cordless Impact Driver

Article No.	4510045
-------------	---------

UPC 7-72995-01758-4

Features

- A member of the Power X-Change family, 1 x 18V battery is necessary for operation
- Brushless motor more power and longer life time
- Practical belt clip for efficient and safe operation
- Impact driver-for effortless tightening of large/long screws
- 1/4" hex. bit (Recommendation: impact-resistant bits)
- Speed control for fine adjustment on delicate jobs
- Short, lightweight design with ergonomic soft grip surfaces
- Special impact mechanism protects the wrist from torsional forces
- 3 powerful LED to illuminate the work area
- Recommended battery for maximum results 2.0 or 2.5 Ah battery
- Battery and charger sold separately

Technical data

No load speed 0 - 2900 RPM

Type of bit interlock Mechanic locking sleeve

Tool collet (square)
 1/4"

Tool collet (hex) ¼" Bit holderMax. torque 1594 in/lbs

Logistical data

•	Product weight	2.35 lbs
•	Gross weight	2.75 lbs
•	Pieces per export carton	4 pcs.
•	Gross weight export carton	12.1 lbs
•	Dimensions Export Carton	12.5" x 6.75" x 8.625"
•	Container quantity (20'/40'/40'HC)	9024 16400 19200

One Battery for All	fastening and releasing (pieces)
1.5 Ah	210
2.0 Ah	280
2.5 Ah	350
3.0 Ah	420
4.0 Ah	560
5.2 Ah	730
6.0 Ah	840
est setup:	
wheel nuts	

















TP-CW 18 Li-Solo



18V 1/2" Cordless Impact Wrench & Driver

Article No. 45

UPC 7-72995-01756-0

Features

- A member of the Power X-Change family, 1 x 18V battery is necessary for operation
- Brushless motor more power and prolonged operation
- Powerful high-torque cordless impact wrench
- Practical belt clip for efficient and safe operation
- Small and light for comfortable operation
- Robust 1/2" external square drive mount
- Ergonomic soft grip surfaces
- Complete with 3 LED to illuminate the work area
- Complete with ¼" bit adapter for screw driving
- Recommended battery for maximum results 2.0 or 2.5 Ah battery
- Battery and charger sold separately

Technical data

No load speed
 2900 RPM

Tool collet (hex.) ¼"

• Tool collet (square) ½"

- Max. torque 1770 in/lbs

Logistic data

Product weight 2.42 lbs
Gross weight 3.08 lbs
Pieces per export carton 4 pcs.
Gross weight export carton 13.6 lbs
Dimensions Export Carton 15.75 " x 7.5 " x 9.25 "
Container quantity (20'/40'/40'HC) 6048 / 12540 / 0

One Battery for All	fastening and releasing (pieces)
1.5 Ah	75
2.0 Ah	100
2.5 Ah	125
3.0 Ah	150
4.0 Ah	200
5.2 Ah	260
6.0 Ah	300

























TE-CD 18 Li-Solo



18V 1/2" Cordless Hammer Drill

Article No. 4513961

UPC 7-72995-01750-8

Features

- A member of the Power X-Change family, 1 x 18V battery is necessary for operation
- 2 functions: Drilling/impact drilling
- Rugged ½"quick-change drill chuck for easy tool change
- Electronic speed control for fine adjustment
- Ergonomic soft grip surfaces with additional handle
- Additional handle with ribs for secure fastening
- Reverse function for drilling and screwing
- Continuous operation lock for comfortable and easy operation
- Infinitely adjustable drilling depth stop made of solid metal
- Recommended battery for maximum results 2.0 or 2.5 Ah battery
- Battery and charger sold separately

Technical Data

•	No load speed	0-2600 RPM
•	Impact rate	41,600 BPM
•	Drilling capacity, wood	1"
•	Drilling capacity, concrete	1/2"
•	Drilling capacity, metal	3/8"
•	Drill chuck	1/2"

Logistic Data

Product weight 3.52 lbs
 Dimensions single packaging 2.875" x 11.875" x 8"

• Pieces per export carton 8 pcs.

Gross weight export carton 35.2 lbs
Dimensions export carton 27.5" x 13.75" x 9"

Container quantity (20'/40'/40'HC) 3840 | 7640 | 8448

	1.5 Ah	2.0 Ah	2.5 Ah	3.0 Ah	4.0 Ah	5.2 Ah	6.0 Ah
>>> 1)	45 pcs.	60 pcs.	75 pcs.	90 pcs.	120 pcs.	156 pcs.	180 pcs.





HEROCCO 18/20



18V 3/4" SDS-Plus Cordless Rotary Hammer

Article No.	4513906

UPC 7-72995-01760-7

Features

- A member of the Power X-Change family, 1 x 18V battery is necessary for operation
- Brushless motor more power and prolonged operation
- 4+1 functions: Drilling/impact drilling/chiseling with & w/o lock
- Pneumatic impact mechanism for effortless drilling in concrete
- Universal SDS-plus chuck with semi-automatic function
- Speed electronics for fine adjustment on delicate jobs
- Low-vibration operations by vibration-cushioned main handle
- Ergonomic soft grip surfaces with additional handle
- Infinitely adjustable drilling depth stop made of solid metal
- Comes with LED lamp to illuminate the work area
- Magnetic bit adapter for screwing
- Supplied with E-Box case
- Recommended battery for maximum results 4.0 Ah battery
- Battery and charger sold separately

Technical data

•	No load speed (gear 1)	0-1200 RPM
•	Impact rate (gear 1)	0-5500 BPM
•	Impact power	1.6 ft/lbs
•	Max. torque	160 in/lbs
•	Drilling capacity in concrete	3/4"

Logistic data

Gross weight export carton

Tool weight
Gross Weight

Dimensions single packaging
Pieces per export carton

Dimensions export carton

Container quantity (20'/40'/40'HC)

41.8 lbs
4.66 lbs
9.63 lbs
15.75" x 14.125" x 4.75"
4 pcs.
22" x 16.75" x 15.125"
1120 | 2320 | 2720



		MIII
One Battery for All	screwing ¹ (pieces)	drilling ² (pieces)
1.5 Ah	250	65
2.0 Ah	335	87
2.5 Ah	417	108
3.0 Ah	500	130
4.0 Ah	670	174
5.2 Ah	870	225
6.0 Ah	1000	260



















TE-DY 18 Li-Solo



18V Cordless Drywall Screwdriver

Article No.	4259985
-------------	---------

UPC 7-72995-01759-1

Features

- A member of the Power X-Change family, 1 x 18V battery is necessary for operation
- Adjustable depth stop for precise depth setting
- Low-fatigue operation thanks to continuous operation setting
- Integrated pressure coupling for user-friendly screw driving
- Ergonomic soft grip surfaces
- Complete with LED lamp to illuminate the work area
- Quick and intuitive bit change thanks to the magnetic bit holder
- Practical belt clip for efficient and safe operation
- Comes in E-Box case
- Recommended battery for maximum results 2.0 or 2.5 Ah battery
- Battery and charger sold separately

Technical Data

Voltage 18 V

No-load speed 0 - 4000 RPM
Tool holder 1/4" Bit holder

Logistic Data

Product weight 2.15 lbs
Gross weight 6.1 lbs

Dimensions single packaging 13.625" x 4.375" x 13.125"

Pieces per export carton 4 pcs.
Gross weight of export carton 26.29 lbs

Dimensions export carton 18" x 14.375" x 13.625" Container quantity (20'/40'/40'HC) 1500 | 3112 | 3780

Battery Runtime

1		1.5 Ah	2.0 Ah	2.5 Ah	3.0 Ah	4.0 Ah	5.2 Ah	6.0 Ah
))) ⁽¹⁾	800	1100	1350	1600	2200	2800	3300
		pcs.						

1) Screwing 5/32" x 1" screws into drywall (max. qty)

















TE-CS 18/165 Li-Solo



18V 6-1/2" Cordless Circular Saw

Article No.	4331215
-------------	---------

UPC 7-72995-01764-5

Features

- Member of the Power X-Change family, 1 x 18V battery is necessary for operation
- Easy adjustment without tools (cutting depth, tilt angle)
- Dust extractor adapter to keep the work place clean
- Ergonomic soft grip surfaces
- Complete with LED lamp to illuminate the work area
- Recommended battery for maximum results 4.0 Ah battery
- Battery and charger sold separately

Technical Data

No-load speed Saw blade

Number of saw teeth

Cutting depth at 90°Cutting depth at 45°

6-1/2" x 5/8" x 1/16"

24 tooth 2-1/8"

4200 RPM

1-3/8"

Logistic Data

Length 16-1/2"
Width 13-1/8"
Height 12-1/4"
Gross weight single packaging 5.72 lbs
Product weight 5.5 lbs
Pieces per export carton: 2 pcs.

Export carton dimensions: 18.75" x 15.75" x 13.125"

Gross weight export carton: 18.4 lbs

• Container quantity (20'/40'/40'HC): 900 / 1900 / 2180

	1.5 Ah	2.0 Ah	2.5 Ah	3.0 Ah	4.0 Ah	5.2 Ah	6.0 Ah
>>> 1)	82 ft.	108 ft.	131 ft.	160 ft.	210 ft.	270 ft.	321 ft.







TP-CS 18/190 LI BL-Solo



18V 7-1/4" Cordless Circular Saw

Article No. 4331211

UPC 7-72995-01763-8

Features

- A member of the Power X-Change family, 1 x 18V battery is necessary for operation
- Brushless motor more power for prolonged operation
- Easy adjustment without tools (cutting depth, tilt angle)
- Complete with LED lamp to illuminate the work area
- Ergonomic soft grip surfaces
- Dust extraction adapter to keep the workplace clean
- Parallel stop for precise cuts
- Recommended battery for maximum results 4.0 Ah battery
- Battery and charger sold separately

Technical Data

No-load speed 3800 RPM Saw Blade 7-1/4" \times 5/8" \times 3/16" Number of saw teeth 24 teeth Cutting depth at 45° 1-3/4" Cutting depth at 90° 2-1/2"

Logistic Data

Product weight 7.1 lbs
Gross weight single packaging 9.9 lbs
Dimensions single packaging 15" x 9" x 12.625"
Pieces per export carton 2 pcs.
Gross weight export carton 20.7 lbs
Dimensions export carton 18.75" x 15.5" x 13.375"
Container quantity (20'/40'/40'HC) 800 | 1700 | 2000

Battery Runtime				
One Battery for All	sawing ¹ (m)			
1.5 Ah	18			
2.0 Ah	24			
2.5 Ah	30			
3.0 Ah	37			
4.0 Ah	49			
5.2 Ah	63			
6.0 Ah	73			





















TE-AP 18/22 Li-Solo



18V Cordless Reciprocating Saw

Article No. 4326307

UPC 7-72995-01761-4

Features

- Member of the Power X-Change family, 1 x 18V battery is necessary for operation
- Tool-free blade changes for quick application
- Adjustable soleplate for optimum blade use
- Ergonomic soft grip surfaces
- Rubber supports to protect the housing
- Comes with 6"- 7 TPI wood saw blade
- Recommended battery for maximum results 2.0 or 2.5 Ah battery
- Battery and charger sold separately

Logistic Data

Product weight
Gross weight single packaging
Dimensions single packaging
Pieces per export carton
Gross weight export carton
Dimensions export carton
Container quantity (20'/40'/40'HC)

3.52 lbs
4.4 lbs
16.375" x 3.125" x 6.5"
6 pcs.
31.41 lbs
19.5" x 18.625" x 15.4375"
1704 | 3408 | 4500

Battery Runtime

	1.5 Ah	2.0 Ah	2.5 Ah	3.0 Ah	4.0 Ah	5.2 Ah	6.0 Ah
>>> 1)	140 pcs.	180 pcs.	240 pcs.	290 pcs.	370 pcs.	570 pcs.	580 pcs.

1) Round timber 1-3/8" max. number of cuts per battery charge.





Tool-free saw blade change

No load speed 0 - 2600 RPM Stroke length 7/8"
Cutting depth in wood 4"
Cutting depth in steel 1/4"

Yes

















TE-AP 18/28 Li-BL-Solo



18V Cordless Reciprocating Saw

Article No.	4326311
-------------	---------

UPC 7-72995-01762-1

Features

- A member of the Power X-Change family, 1 x 18V battery is necessary for operation
- Brushless motor more power for prolonged operation
- Rotatable main handle for maximum flexibility
- Anti-vibration function ensures low vibration during operation
- Adjustable soleplate for optimum blade use
- Tool-free blade changes for rapid application
- Ergonomic soft grip surfaces
- Comes with 6"- 7 TPI wood blade
- Recommended battery for maximum results 2.0 or 2.5 Ah battery
- Battery and charger sold separately

Technical Data

No load speed 0 - 2500 RPM Stroke length 1-1/8" 8" Cutting depth in wood Cutting depth in plastic 13/16" Cutting depth in steel 1/2" Tool-free saw blade change Yes

Logistic Data

24.2 lbs Gross weight export carton Dimensions export carton 18.125" x 14.5" x 9.5" Product weight 4.53 lbs Gross weight single packaging 5.96 lbs Dimensions single packaging 17.5" x 6.875" x 4.375" Pieces per export carton 4 pcs. Container quantity (20'/40'/40'HC) 2600 | 5400 | 6300







One Battery for All	sawing (pieces
1.5 Ah	170
2.0 Ah	226
2.5 Ah	332
3.0 Ah	417
4.0 Ah	556
5.2 Ah	723
6.0 Ah	834



















Varrito-Solo



18V Cordless Oscillating Multi-Tool

Article No. 4465165

UPC 7-72995-01767-6

Features

- Member of the Power X-Change family, 1 x 18V battery is necessary for operation
- Quick release for tool-free change of equipment
- Comfortable accessory change thanks to magnetic tool fixation
- Speed electronics for material and application
- Oscillation decoupled battery uptake for reduction of vibration
- Ergonomic soft grip surfaces
- 12-pin-tool universal blade adaptor for flexible positioning of equipment
- Recommended battery for maximum results 2.0 or 2.5 Ah battery
- Battery and charger sold separately

Technical data

Angle of oscillation Oscillating speed No load speed Sandpaper size 3.2° (total) 22000 - 40000 OPM 11000 - 20000 RPM 3.5" x 3.5" x 3.5"

Standard Accessories-Included

- Triangular grinding/sanding plate
- 9 x grinding/sanding paper (3 x 60 Grit, 80 Grit, 120 Grit)
- Scraper
- Plunge-cut saw blade for wood and plastic (HCS)
- BIM plunge-cut saw blade for metal
- Segment saw blade for wood, plastic and soft metal (HSS)
- Diamond segment saw blade for tile joints

Logistical data

Gross weight single packaging
Dimensions single packaging
Pieces per export carton
Gross weight export carton
Dimensions export carton
Container quantity (20'/40'/40'HC)

3.56 lbs 3" x 6.5" x 10.5" 10 pcs. 6.5 lbs 22.4375" x 16" x 7.5"

5920 | 12000 | 13000

Battery Running Time

One Battery for All	sawing*	sanding? (min.)	cutting ³ (pieces)	cutting* (pieces)
1.5 Ah	23		540	100
2.0 Ah	30		720	134
2.5 Ah	38		900	166
3.0 Ah	45		1080	200
4.0 Ah	60		1440	268
5.2 Ah	78		1890	340
6.0 Ah	90		2160	400





















TE-OS 18/150 Li-Solo



18V Cordless Palm Detail Sander

Article No.	4460721
Article No.	4460/21

UPC 7-72995-01770-6

Features

- Member of the Power X-Change family, 1 x 18V battery is necessary for operation
- Ergonomich soft grip surfaces
- Small, compact and easy to handle
- Ideal for sanding corners and small surfaces
- "Extreme Fix" fastening for quick change of sanding paper
- High removal rate with "Extreme Fix" due to reduced slippage
- Solid, rugged aluminum fan impeller for smooth running
- Active dust extraction keeps the work area clean
- Recommended battery for maximum results 2.0 or 2.5 Ah battery
- Battery and charger sold separately

Technical Data

•	No load speed	12000 RPM
•	Oscillating speed	24000 OPM
•	Oscillating circuit	1/16"
•	Sanding area	6" x 6" x 4"
•	Sanding paper size (velcro)	6" x 6" x 4"

Standard Accessories-Included

- Vacuum cleaner adapter
- 6 sheets of abrasive paper (3 x 120 Grit | 3 x 240 Grit)

Logistic Data

Product weight 1.76 lbsGross weight single packaging 2.42 lbs

Dimension single packaging 10.125" x 6.125" x 4.375"

Piece per export carton 8 pcs.
Gross weight export carton 21.8 lbs

Dimension export carton 20.25" x 10.4375" x 13.375"

Container quantity (20'/ 40'/ 40'HC) 4224 | 8448 | 9856

Battery Runtime

 Bellindinilladine							6.0 Ah
)))	23 min	27 min	34 min	40 min	55 min	70 min	80 min

¹⁾ Battery capacity

Optional Accessory


4460736 15 pc. Sandpaper Kit

(5 x 60 Grit, 5 x 120 Grit, 5 x 180 Grit)

UPC 7-72995-01799-7









TE-RS 18 Li-Solo



18V 5" Cordless Random Orbit Sander

Article No. 4462012

UPC 7-72995-01771-3

Features

- Member of the Power X-Change family, 1 x 18V battery is necessary for operation
- Electronic speed control
- Finest finish & high sanding performance due to eccentric concept
- Ergonomic soft grip surfaces
- Hook and loop fastening for holding the abrasive paper securely
- Both integrated and connection for external dust extraction
- Comes with an abrasive sanding paper (80 Grit)
- Recommended battery for maximum results 2.0 or 2.5 Ah battery
- Battery and charger sold separately

Technical Data

•	Oscillating speed	14,000 – 22,000 OPM
•	No load speed	7,000 - 11,000 OPM
•	Oscillating circuit	5/64"
•	Backing pad diameter	5"
•	Sanding paper diameter	5"

Logistic Data

Product weight 2.53 lbs
Gross weight 3.28 lbs
Dimensions single packaging 7" x 6" x 7"
Pieces per export carton 8 pcs.
Gross weight of export carton 26.2 lbs

Dimensions export carton 24.75" x 7.5" x 15"

Container quantity (20'/40'/40'HC) 5096 | 10240 | 11840

Battery Runtime

One Battery for All	sanding
Professional Control of the Control	(min.)
1.5 Ah	15
2.0 Ah	20
2.5 Ah	25
3.0 Ah	30
4.0 Ah	40
5.2 Ah	52
6.0 Ah	60

Optional Accessory

4460737 25 pc. Sandpaper Kit (9 x 60 Grit, 8 x 120 Grit, 8 x 180 Grit) UPC 7-72995-01801-7



















TE-JS 18/80 Li-Solo



18V Variable Speed Cordless Jigsaw

Article No. 4321233

7-72995-01768-3

Features

UPC

- Member of the Power X-Change family, 1 x 18V battery is necessary for operation
- Very smooth operation for exact cutting
- Selectable pendulum action for fast cutting
- Tool-free universal blade holder
- Includes dust blow-off function for optimum visibility
- Complete with LED lamp to illuminate the work area
- Integrated plastic sliding element for sensitive workpieces
- Ergonomic soft grip surfaces
- Complete with chip guard for cuts without splintering
- Recommended battery for maximum results 2.0 or 2.5 Ah battery
- Battery and charger sold separately

Technical Data

•	Max. strokes per minute	0-2400 SPM
•	Stroke length	1"
•	Cutting depth in wood	3-1/4"
•	Cutting depth in plastic	1/2"
•	Cutting depth in steel	5/32"
•	Max. bevel capacity	47°
•	Tool-free saw blade change	Yes

Logistic Data

Pieces per export carton 5 pcs.

Gross weight export carton 26.1 lbs
Product weight 3.85 lbs

Gross weight single packaging 5 lbs

Dimensions single packaging 9.25" x 3.5" x 8.875"

Container quantity (20'/40'/40'HC) 4575 | 9480 | 11115

One Battery for All	sawing ¹ (m)
1.5 Ah	7
2.0 Ah	9.5
2.5 Ah	11
3.0 Ah	14
4.0 Ah	20
5.2 Ah	30
6.0 Ah	32





















TE-PL 18/82 Li-Solo



18V 3-1/4" Cordless Portable Planer

Article No.	4345401
UPC	7-72995-01783-6

Features

- Member of the Power X-Change family, 1 x 18V battery is necessary for operation
- Powerful hand-held planer for jobs with a chip depth of up to 1/16"
- Large knife shaft for optimum planing results
- Automatic park rest protecting the planing knife and workpiece
- Solid aluminum sole plates for flat results
- Sole plate with 1 V-shaped groove for easy chamfering of edges
- Ergonomic soft grip surfaces
- Recommended battery for maximum results 2.0 or 2.5 Ah battery
- Battery and charger sold separately

Technical Data

•	No load speed	1500 RPM
•	Planing width	3-1/4"
•	Planing depth	5/64"
•	Rabbet depth	5/16"

Standard Accessories-Included

- Parallel guide for straight and precise planning work
- Rabbet depth stop for easy production of heels
- 2 x TCT-Planing blades (reversible blades) for high surface quality

Logistic Data

Product weightGross weight5.34 lbs6 lbs

Dimension packaging 12" x 7.5" x 7.625"

Piece per export carton 4 pcs.Gross weight export carton 37.4 lbs

• Dimension export carton 15.5" x 13.375" x 16"

Container quantity (20'/40'/40'HC) 1800 | 3848 | 4900

Battery Runtime

Ш	1,5 Ah	2,0 Ah	2,5 Ah	3,0 Ah	3,0 Ah 1P	4,0 Ah	5,2 Ah	6,0 Ah
))) ⁽⁾	52 ft.	82 ft.	92 ft.	121 ft.	118 ft.	157 ft.	190 ft.	255 ft.

1) Planing in Spruce wood (Depth: 1/32" / Width: 2"), max. length in 3.28 ft. with one battery fully charged.





TE-AG 18/115 Li-Solo



18V 4-1/2" Cordless Angle Grinder

Article No. 4431122

UPC 7-72995-01766-9

Features

- Member of the Power X-Change family, 1 x 18V battery is necessary for operation
- Soft start function and restart safeguard to make it safer to use
- Overload cut-out for a long service life
- Modified air guidance for better cooling and longer service life
- Very smooth operation thanks to separation of motor and gearing
- Disc guard with quick adjust facility
- Robust aluminum gear housing
- Ergonomic soft grip surfaces
- Additional handle can be fitted flexibly in 3 positions
- Cutting disc not included
- Recommended battery for maximum results 2.5 Ah battery
- Battery and charger sold separately

Technical Data

• Disc size 4-1/2"

No-load speed 8500 RPM

Max. cutting depth 1.1"

Spindle thread 5/8" – 11 UNC

Arbor 7/8"

Logistic Data

Gross weight of export carton

Dimensions export carton

Product weight

Gross weight

Gross weight

Dimensions single packaging

Pieces per export carton

Container quantity (20'/40'/40'HC)

31.68 lbs

18.125" x 13.75" x 11"

2.66 lbs

4.8 lbs

11.4375" x 5.5" x 4.25"

6 pcs.

3497 | 7252 | 8806

One Battery for All	cutting' (pieces)
1.5 Ah	15
2.0 Ah	20
2.5 Ah	25
3.0 Ah	30
4.0 Ah	40
5.2 Ah	60
6.0 Ah	70

















Axxio 18/125 Solo



18V 5" Cordless Angle Grinder

Article No.	4431143
-------------	---------

UPC 7-72995-01765-2

Features

- A member of the Power X-Change family, 1 x 18V battery is necessary for operation
- Brushless motor more power for prolonged operation
- Soft start function and restart safeguard to make it safer to use
- Overload cut-out for a long service life
- Very smooth operation thanks to separation of motor and gearing
- Disc guard with quick adjust facility for flexible working
- Robust aluminum gearing housing
- Ergonomic soft grip surfaces
- Dust protection guard protects the item from invading dust
- Additional handle can be fitted in 2 positions
- Cutting disc not included
- Recommended battery for maximum results 2.5 or 4.0 Ah battery
- Battery and charger sold separately

Technical Data

• Disc size 5"

No-load speed 3800 RPM

Max. cutting depth 1.29"

Spindle thread 5/8" – 11 UNC

• Arbor 7/8"

Logistic Data

Product weight
Gross weight
4.24 lbs
Gross weight of export carton
Dimensions export carton
Dimensions single packaging
Pieces per export carton
Container quantity (20'/40'/40'HC)
3.16 lbs
4.24 lbs
28.8 lbs
15.375" x 13" x 10.625"
15.375" x 4.75" x 4.75"
6 pcs.
4752 | 9834

Battery Runtime

							6.0 Ah
>>> 1)	22 pcs.	33 pcs.	37 pcs.	46 pcs.	61 pcs.	85 pcs.	92 pcs.

1) Cutting ½" round steel

















CE-CB 18/254 Li-Solo



18V 10" Cordless Car Polisher

Article No. 2093303

UPC 7-72995-01773-7

Features

- Member of the Power X-Change family, 1 x 18V battery is necessary for operation
- Brushless electric motor
- 2-in-1 product: Polishing and buffing with a single tool
- Electronic speed control via LCD display
- Ergonomic handle for an optimum hold and controlled operation
- Ergonomic soft grip surfaces
- Hook-and-loop fastener for changing the attachments quickly
- Spindle locking system for easy attachment of the polishing disc
- Recommended battery for maximum results 2.0 or 2.5 Ah battery
- Battery and charger sold separately

Technical Data

Rotation speed 2500 RPM

Diameter 10"

Logistic Data

Product weight 4.24 lbs

Gross weight 5.56 lbs

Dimension single carton: 10.625" x 10.25" x 8.75"

Pieces per export carton: 4 pcs.

Pieces per export carton: 4 pcs.

Gross weight of export carton: 23.9 lbs

• Dimensions of export carton: 20.875" x 11" x 18.125"

Container quantity (20'/40'/40'HC): 1672 / 3280 / 3800

Battery Runtime

One Battery for All	polishing (min.)
1.5 Ah	56
2.0 Ah	81
2.5 Ah	93
3.0 Ah	112
4.0 Ah	127
5.2 Ah	200
6.0 Ah	222

Optional Accessory

2093096 2 pc. Polishing Bonnets Kit (1 textile bonnet, 1 synthetic bonnet)
UPC 7-72995-01803-1



4.4

















CE-CP 18/180 Li E



18V 7" Cordless Polisher-Orbital Sander

Article No. 2093325

UPC 7-72995-01774-4

Features

- Member of the Power X-Change family, 1 x 18V battery is necessary for operation
- Brushless motor more power for longer running time
- 2-in-1 product: polishing and grinding/sanding with a single tool
- Electronic speed control via LCD display
- Ergonomic handle for an optimum hold and controlled operation
- Slimline design with ergonomic soft grip surfaces
- Hook-and-loop fastener for changing the attachments quickly
- Spindle locking system for easy attachment of the polishing disc
- Large polishing disc with 7" diameter for speedy progress
- Recommended battery for maximum results 2.5 Ah battery
- Battery and charger sold separately

Technical Data

Battery Voltage 18 V
 Diameter of sanding plate 7"

No load speed 500 – 3000 RPM 5/8" – 11 UNC

Standard Accessories-Included

- 1 foam attachment
- 1 synthetic polishing bonnet
- 3 sanding papers (1 x 60 Grit, 80 Grit, 120 Grit)

Logistic Data

Product weight 3.5 lbs
Gross weight 7.15 lbs
Pieces per export carton 4 pcs.
Gross weight export carton 20.2 lbs

Dimensions export carton 17" x 15.125" x 11.625"
Container quantity (20'/40'/40'HC) 2120 | 4660 | 5480

Battery Runtime

-	1.5 Ah						
>>> 1)	17 min	20 min	25 min	35 min	43 min	54 min	65 min

1) For best performance select a 2.5 Ah battery

Optional Accessory

2093239 9 pc. 7" Polishing/Sanding Kit

Comes with:

- 1 foam attachment
- 2 synthetic polishing bonnets
- 6 sanding papers (2 x 60 grit, 80 grit, 120 grit)

UPC 7-72995-01804-8











TE-HA 18 Li-Solo



18V Cordless Heat Gun

Article No. 4520502

UPC 7-72995-01769-0

Features

- Member of the Power X-Change family, 1 x 18V battery is necessary for operation
- High-power hot air gun with 2 temperature settings
- LED display for showing the selected temperature setting
- Overheating protection for safe operation
- Mechanical nozzle ejector for easy removal of nozzle attachments
- Swing-out metal hook for flexible work and storage
- Ergonomic soft grip surfaces
- Recommended battery for maximum results 2.0 or 2.5 Ah battery
- Battery and charger sold separately

Technical Data

18 V | Li-Ion Voltage Number of temperature settings Temperature at setting 1 350 °C Temperature at setting 2 550 °C Air flow rate at setting 1 & 2 200 L/min

Standard Accessories-Included

Reducer nozzle, wide jet nozzle, reflector nozzle

Logistic Data

- Product weight Gross weight single packaging
- 6.75" x 8.5" x 3.125" Dimensions single packaging
- Pieces per export carton
- Gross weight export carton
- Dimensions export carton
- Container quantity (20'/40'/40'HC)

1.76 lbs 2.75 lbs

8 pcs. 17.6 lbs

14.125" x 13.375" x 9.25" 8136 | 16848 | 19752

	1,5 Ah	2,0 Ah	3,0 Ah	4,0 Ah	5,2 Ah	6,0 Ah
>>> 1)	6 min	9 min	13 min	17 min	22 min	25 min

¹⁾ Running time with temperature at setting 2





TE-CB 18/180 Li



18V Cordless Compact Blower

Article No. 3408005

UPC 7-72995-01772-0

Features

- A member of the Power X-Change family, 1 x 18V battery is necessary for operation
- Low and high power settings
- Versatile for work site, workshop or garden
- Air flow up to 180 km/h
- Air flow setting 1- 130 km/h
- Air flow setting 2- 180 km/h
- Ergonomic soft grip surfaces
- Recommended battery for maximum results 2.0 or 2.5 Ah battery
- Battery and charger sold separately

Technical Data

• Battery 18V

No load speed (low) 1- 11,500 RPM (high) 2- 15,500 RPM

Max. air speed 180 km/h

Logistic Data

Product weight
Gross weight
Pieces per export carton
Gross weight export carton
18.4 lbs

Dimensions export carton 18.25" x 12.25" x 16. 5"

Container quantity (20'/40'/40'HC) 2580 / 5250 / 6300

Battery Runtime

	1.5 Ah	2.0 Ah	2.5 Ah	3.0 Ah	4.0 Ah	5.2 Ah	6.0 Ah
)))) 1)	31 min	39 min	48 min	62 min	68 min	100 min	124 min

1) Performance at setting 1 per battery charge



















TC-SY 18/60 Li Solo



18V Cordless HVLP Handheld Paint Sprayer

Article No.	4260027

UPC 7-72995-01780-5

Features

- A member of the Power X-Change family, 1 x 18V battery is necessary for operation
- Hand-held system for small and medium-sized working areas
- Adapted for spraying of lacquers and glazes
- Removable spray head for cleaning
- Paint flow regulation for ideal adaptation of paint application
- Adjustable air cap for vertical, horizontal and round jets
- Ergonomic soft grip surfaces
- Practical hanging device for space-saving storage
- Recommended battery for maximum results 2.5 Ah battery
- Battery and charger sold separately

Technical Data

•	Battery	18 V
•	Flow rate	650 ml/min
•	Max. viscosity	60 DIN-sec
•	Tank volume	800 m l

Standard Accessories- Included

- 2 nozzles (2 & 2.5 mm) for different viscosities of lacquer and glaze
- Purification brush for cleaning the uptake
- Purification needle for cleaning the spray nozzle
- 100 ml viscosity cup for examination of viscosity
- Lid for paint container
- 800 ml paint container with measurement scale

Logistic Data

- Product weight
- Gross weight single packaging
- Dimensions single packaging
- Pieces per export carton
- Gross weight export carton
- ✓ Dimensions export carton
- Container quantity (20'/40'/40'HC)

2.6 lbs 3.34 lbs

9.625" x 6.5" x 11"

4 pcs. 18.7 lbs

20" x 13.75" x 11.625"

2124 / 4408 / 5168

	1.5 Ah	2.0 Ah	2.5 Ah	3.0 Ah	4.0 Ah	5.2 Ah	6.0 Ah
	22 m ²	30 m ²	38 m ²	45 m ²	60 m ²	78 m ²	90 m ²

¹⁾ Lacquering wood, wood lacquer, viscosity 60 DIN-sec





PRESSITO



18V Dual Function Corded/Cordless Inflator/Deflator

Article No. 4020463

UPC 7-72995-01782-9

Features

- A member of the Power X-Change family,1 x 18V battery is necessary for operation
- Hybrid function: for use with a power cable/rechargeable battery
- High-pressure pump for inflating car tires, cycle tires, balls
- Low-pressure pump for inflating air mattresses
- Low-pressure suction function for deflating air mattresses
- Easy-to-operate manual digital pressure indicator
- High-pressure pump with adjustable pressure settings up to 160 PSI
- With auto shutoff function when adjusted pressure is reached
- Integrated storage holder for the 3-piece inflation adapter set
- Recommended battery for maximum results 4.0 Ah battery
- Battery and charger sold separately

Technical Data

•	Power supply	18V & 120 V 60 Hz
•	Suction capacity high pressure pump	0.74 CFM
•	Output power at 0 PSI	0.54 CFM
•	Output power at 60 PSI	0.35 CFM
•	Output power at 100 PSI	0.28 CFM
•	Max. operating pressure	160 PSI
•	Hose lengths (low/high)	12.2" / 28"

Logistic Data

Product weight 4.62 lbs
Gross weight 5.72 lbs
Pieces per export carton 4 pcs.
Gross weight export carton 25 lbs

Dimensions export carton 15.375" x 12.25" x 18.125"

Container quantity (20'/40'/40'HC) 1960 / 4200 / 4800

Battery Runtime

		2.0 Ah					
>>> 1)	20 min	30 min	37 min	45 min	60 min	85 min	90 min

¹⁾Operating time per battery charge in idle mode





X-CHANGE + USE WITH POWER CABLE



TE-AC 36/6/8 Li



36V 1.6 Gallon Cordless Compact Air Compressor

Article No.	4020455
-------------	---------

UPC 7-72995-01781-2

Features

- Member of the Power X-Change family, 2 x 18V batteries are necessary for operation
- Oil-free, service-free motor for low maintenance requirements
- Mobile, high-performance cordless compressor with a 1.6 Gallon tank
- Ergonomic design and handle for easy transport
- Applications up to 135 PSI can be set using the pressure reducer
- Pressure gauge & quick-release coupling for regulated pressure
- Vibration-damped feet for standing securely
- Safety valve protects user
- Drain cock enables user-friendly maintenance
- Recommended batteries for maximum results 2 x 4.0 Ah batteries
- Batteries and charger sold separately

Technical Data

•	Motor speed	16000 RPM
•	No load speed	3200 RPM
•	Intake capacity	4.58 CFM
•	Output power 0 PSI	3.17 CFM
•	Output power 60 PSI	1.94 CFM
•	Output power 100 PSI	1.34 CFM
•	Max. operating pressure	135 PSI
•	Tank capacity	1.6 Gallon (6 L)
•	No. of cylinders	1

Standard Accessories-Included

- 8 foot high-quality compressed air fabric hose
- Blow-out gun, tire pressure gauge and 8-piece adapter set

Logistic Data

•	Product weight	21.34 lbs
•	Gross weight	25.3 lbs
•	Pieces per export carton	1 pc.
•	Gross weight of export carton	26 lbs

Dimensions export carton 17.3125" x 12.75" x 14.5"

Container quantity (20'/40'/40'HC) 510 / 1050 / 1210

Battery Runtime

	1.5 Ah	2.0 Ah	2.5 Ah	3.0 Ah	4.0 Ah	5.2 Ah	6.0 Ah
>>> 1)	20 pcs	25 pcs	29 pcs	40 pcs	50 pcs	60 pcs	80 pcs
>>> 2)	330 pcs	400 pcs	435 pcs	660 pcs	800 pcs	900 pcs	1320 pcs

1) Tank pressure inflating cycles per battery charge

²⁾ Soft wood – max. quantity of stapling (1/2" staples) per battery charge









TE-VC 18 Li-Solo



18V Cordless Handheld Vacuum

Article No.	2347124
UPC	7-72995-01776-8

Features

- A member of the Power X-Change family, 1 x 18V battery is necessary for operation
- Dust container with a volume of 540 ml
- Can clean filters under running water
- Space-saving storage thanks to the integrated wall bracket
- Recommended battery for maximum results 2.5 Ah battery
- Battery and charger sold separately

Technical Data

• Suction power max. 17.5 CFM

• Volume 540 ml (18.3 oz.)

Logistic Data

Product weight 2 lbsGross weight single packaging 3.7 lbs

Dimensions single packaging 18.5" x 5.125" x 7.625"

Pieces per export carton 4 pcs.

Gross weight export carton 18 lbs

Dimensions export carton
 19.25" x 11.5" x 16.125"

Container quantities (20'/40'/40'HC)
 1,920 / 3,984 / 4,668

Standard Accessories-Included

- Floor nozzle for hard floors and smooth surfaces
- Crevice nozzle for hard-to-reach areas
- Upholstery nozzle for cleaning upholstery and fabrics
- Extension tube (18") for cleaning floors

Battery Runtime

	1.5 Ah						
>>>	12 min	16 min	18 min	23 min	31 min	40 min	46 min

Max. idling time per battery charge







TE-VC 18/10 Li



18V 2.6 Gallon (10L) Cordless Wet/Dry Vacuum

Article No.	2347165

UPC 7-72995-01777-5

Features

- A member of the Power X-Change family, 1 x 18V battery is necessary for operation
- Easy to empty 2.6 Gallon (10L) thanks to quick-release fasteners
- Ergonomic design and carry-handle for easy transport
- Highly versatile wet and dry vacuuming possible
- Blow connection for blow-cleaning of hard-to-reach areas
- Included accessories can be stored directly on the equipment
- One-hand operation thanks to intelligent On/Off switch position
- Recommended battery for maximum results 4.0 Ah battery
- Battery and charger sold separately

Technical Data

Volume
Suction power max.
Suction hose length
Suction hose diameter
Sound pressure level
Sealed suction (water lift)
2.6 Gallon (10L)
42.4 CFM
2.3 to 6.6 feet
1-3/8"
72 dB
33"

Standard Accessories-Included

- Extendible hose with a total length of 6.6 feet
- 2-in-1 crevice/brush nozzle and 2-in-1 upholstery/universal nozzle
- Foam filter, filter bag and paper dust bag

Logistic Data

Product weight 6.8 lbs
Gross weight 8.14 lbs
Pieces per export carton 1 pc.

Dimensions of packaging 16" x 10.5" x 12.875" Container quantity (20'/40'/40'HC) 843 / 1753 / 2004

Battery Runtime

-		2.0 Ah					
)))	8 min	10 min	12 min	17 min	21 min	26 min	30 min

For best performance use a battery with at least 2.5 Ah

Optional Accessories

2351136 5 pc. 10L Foam Filters Kit UPC 7-72995-01805-5

2351261 5 pc. 10L Dust Bags Kit UPC 7-72995-01814-7ù











¹⁾Operating time per battery charge in idle mode

TC-VC 18/20 Li S



18V 5.3 Gallon (20L) Cordless Wet/Dry Vacuum

Article No.	2347137
-------------	---------

UPC 7-72995-01778-2

Features

- A member of the Power X-Change family, 1 x 18V battery is necessary for operation
- 5.3 Gallon (20L) stainless steel tank
- Blow connection for blow-cleaning hard-to-reach areas
- 4 castors for good mobility
- Practical accessories holder for clean stowage and operations
- Hose system with 1-3/8" diameter maintains high air and dirt flow
- Recommended battery for maximum results 4.0 Ah battery
- Battery and charger sold separately

Technical Data

•	Volume	5.3 Gallon (20L)
•	Suction power max.	53 CFM
•	Suction hose length	4.9 feet
•	Suction hose diameter	1-3/8"
•	Sound pressure level Lpa	72 dB
•	Sealed suction (water lift)	33"

Standard Accessories-Included

- Plastic suction hose and three-part extension tube
- Big combination nozzle, crevice nozzle & upholstery nozzle
- Foam filter, pleated filter and paper dirt bag

Logistic Data

•	Product weight	7.9 lbs
•	Gross weight	12.3 lbs
•	Pieces per export carton	1 pcs.
•	Gross weight packaging	12.3 lbs

Dimensions packaging 13.125" x 13" x 21.625"

Container quantity (20'/40'/40'HC) 476 / 980 / 1120

Battery Running Time

	1.5 Ah						
))) ¹⁾	8 min	10 min	11 min	16 min	20 min	25 min	32 min

For best performance use a battery with at least 4.0 Ah

Optional Accessories

2351137	5 pc. 20L Foam Filters Kit (UPC 7-7299501807-9)
2351168	5 pc. 20L Dust Bags Kit (UPC 7-7299501812-3)
2351142	1 pc. 20L Fabric Filter (UPC 7-7299501806-2)
2351192	5 pc. 20L High Efficiency Dust Bags Kit (UPC 7-7299501809-3)
2351118	1 pc. Pleated Filter with Lid (UPC 7-7299501811-6)
2351236	3 pc. Nozzle Kit (UPC 7-7299501810-9)



















¹⁾ Operating time per battery charge in idle mode

TE-VC 36/30 Li-S



36V 8 Gallon (30L) Cordless Wet/Dry Vacuum

Article No.	2347141
-------------	---------

UPC 7-72995-01779-9

Features

- Member of the Power X-Change family, 2 x 18V batteries are necessary for operation
- 2 speeds (ECO/BOOST) for optimal battery use
- High suction power with simultaneous wireless freedom
- 8 gallon (30L) stainless steel tank
- Blow connection for blow-cleaning hard-to-reach areas
- 2 large wheels and 2 castors for better mobility
- Practical accessories holder for clean stowage and operations
- Water drain screw for draining water
- Telescopic stainless steel suction tube 1-3/8"
- Air regulator on the handle
- Recommended batteries for maximum results 4.0 Ah batteries
- Battery and charger sold separately

Technical Data

• 9	Suction	power	max.	56 CFM
-----	---------	-------	------	--------

Volume
 8 Gallon (30L)

Suction hose length 8.2 ft.

Suction hose diameter 1-3/8"

Sound pressure level 76 dB

Sealed suction (water lift) Boost Sealed suction (water lift) ECO 40"

Standard Accessories-Included

- Heavy-duty 1-3/8" suction hose (8.2 ft.)
- Big comfort nozzle for carpets/smooth floors
- Foam filter, pleated filter and dust bag

Logistic Data

Product weight 17.6 lbs Gross weight single packaging 25.7 lbs

Dimensions single packaging 18.25" x 15.125" x 25"

Pieces per export carton 1 pcs.

Container quantities (20'/40'/40'HC)
 222 / 456 / 608

Battery Runtime

	1.5 Ah	2.0 Ah	2.5 Ah	3.0 Ah	4.0 Ah	5.2 Ah	6.0 Ah
>>> 1)	8 min	11 min	13 min	16 min	22 min	28 min	33 min
>>> ²⁾	6 min	8 min	10 min	12 min	16 min	21 min	24 min

Recommendation for best results: 4.0 Ah batteries or higher

- 1) Max. idling time per battery charge in ECO mode
- 2) Max. idling time per battery charge in BOOST mode

Optional Accessories

2351137 5 pc. 30L Foam Filters Kit (UPC 7-72995-01807-9)

2351176 5 pc. 30L Dust Bags Kit (UPC 7-72995-01813-0)

2351142 1 pc. 30L Fabric Filter (UPC 7-72995-01806-2)

2351196 5 pc. 30L High Efficiency Dust Bags Kit (UPC 7-72995-01808-6)

2351118 1 pc. Pleated Filter with Lid (UPC 7-72995-01811-6)

2351236 3 pc. Nozzle Kit (UPC 7-72995-01810-9)



















TE-TS 36/210 Li-Solo



36V 8-1/4" Cordless Table Saw

Article No.	4340451
-------------	---------

UPC 7-72995-01784-3

Features

- A member of the Power X-Change family, 2 x 18V batteries are necessary for operation
- Portable, mobile, with no annoying power cord
- Sturdy aluminum table
- Small and compact, ideal for limited space or mobile use
- The soft start function protects both the motor and the gear unit
- Ultra-sturdy rip fence for exact longitudinal cuts
- High-grade carbide-tipped saw blade, developed for cordless saws
- Infinitely height adjustable saw blade for extra safety
- Extractor connection on housing and saw blade guard for less mess
- Holders for stowing away all the attachments on the equipment
- Recommended batteries for maximum results 4.0 batteries
- Batteries and charger sold separately

Technical Data

•	No load speed Saw blade Number of teeth Bevel range	3.800 RPM 8-1/4" 40 teeth 90° - 45°
•	Angle stop	-60° - +60°
•	Maximum cutting height 90/45° Max cutting width right Main table dimensions	2-3/4" / 1-3/4" 24-1/2" 18-7/8" x 18-3/8"
•	Max. support surface Diameter of extraction connection	18-7/8" x 21-1/8" 1-3/8"

Logistical Data

•	Gross weight	39.1 lbs
•	Product weight	28.8 lbs
•		25.6"
•	Width	22.5"
•	Height	13"
•	Pieces per export carton	1 pc.

Dimensions packaging 25.25" x 23.25" x 12.6" Container quantity (20'/40'/40'HC) 216 / 474 / 552

Battery Runtime

					4,0 Ah		
))) ²	45 lfm	60 lfm	71 lfm	92 lfm	122 lfm	160 lfm	184 lfm

For best performance select batteries with at least 4.0 Ah

- 1) Battery capacity (2x batteries are necessary)
- 2) OSB panel ¾"- max. cutting reach per charged battery





TC-SR 18 Li BT-Solo



18V Cordless Bluetooth Speaker

Article No.	4514151
-------------	---------

UPC 7-72995-01775-1

Features

- A member of the Power X-Change family, 1 x 18V battery is necessary for operation
- Easy connection with the device thanks to Bluetooth
- AUX connection for connecting an MP3 player, mobile phone, etc.
- USB connection for charging a mobile phone, tablet or MP3 player
- Intuitive control panel makes it easy to use
- Battery and charger sold separately

Technical data

Output voltage USB
 Output current USB
 Output power speakers
 Max. Volume
 Output frequency
 0,12 kHz - 20 kHz

• Bluetooth version 5.0

Logistic data

Length 4.25" Width 3.5" Height 3.875" Product weight 278 g Pieces per export carton 12 pcs. Gross weight export carton 13.2 lbs 12.5" x 12.25" x 9.5" Dimensions export carton Container quantity (20'|40'|40'HC) 53088 | 107688 | 123072

Battery Runtime	

(III)	1,5 Ah 43h	2,0 Ah	2,5 Ah	3,0 Ah	4,0 Ah	5,2 Ah	6,0 Ah
>>> 1)	43h	57h	72h	86h	114h	148h	171h





TE-CP 18 Li USB



18V USB Battery Adaptor

Article No. 4514142

UPC 7-72995-01785-0

Features

- A member of the Power X-Change family, 1 x 18V battery is necessary for operation
- 2 USB ports for charging two devices simultaneously
- External power source for charging a mobile phone, tablet or MP3
- 1 USB port with 2.1A for fast charging
- LED status indicator
- Charging time depends on the battery capacitance of the device
- Recommended battery for maximum results 2.5 Ah battery
- Battery and charger sold separately

Technical data

•	Voltage input	18V
•	Voltage output	5V
•	Amount of USB-ports	2
•	Output of USB port 1	1.0 A
•	Output of USB port 2	2.1 A

Logistic data

Tool weight 0.13 lbs 0.2 lbs Gross weight Pieces per export carton 60 pcs.

Dimensions export carton 13.75" x 13.125" x 11.375" 15.8 lbs

Gross weight export carton

Container quantity (20'/40'/40'HC) 43200 / 94800 / 0

One Battery for All	charging*
	(h)
1.5 Ah	8
2.0 Ah	12
2.5 Ah	13.5
3.0 Ah	16
4.0 Ah	24
5.2 Ah	32
6.0 Ah	36











Power-X-Change Batteries & Chargers



Power X-Change Batteries

2.0 Ah -18V Power X-Change Battery

Article No.

4511480

UPC 7-72995-01791-1



5.2 Ah -18V Power X-Change Battery

Article No.

4511499

UPC



4.0-6.0 Ah -18V Power X-Change Battery

Article No.

4511904

UPC

7-72995-01793-5



2 x 4.0 Ah -18V Power X-Change Battery Twinpack

Article No.

4511603

UPC

7-72995-01794-2



Power X-Change Chargers

30 Min. Power X-Change Single Port Charger

Article No.

4512080

UPC

7-72995-01795-9



Article No.

4512090

UPC

7-72995-01796-6

Power X-Change Starter Kits

2.5 Ah -18V Power X-Change Battery & Charger Starter Kit

Article No.

4512131

Charge time: 50 minutes

UPC 7-72995-01797-3

4.0 Ah -18V Power X-Change Battery & Charger Starter Kit

Article No.

4512132

Charge time: 75 minutes

UPC 7-72995-01798-0

2 x 4.0 Ah -18V Power X-Change Batteries & Dual Port Charger Starter Kit

Article No.

4512133

Charge time: 75 minutes

UPC 7-72995-01839-0







E-Case S-F

E-Case S-F Small Tool Case

Article No.	4540022

UPC 7-72995-01786-7

Features

- Practical case system for storage and transport of tools + accessories
- Locking system for connecting stacked cases, ensures easy storage and transport
- Scratch-free transport thanks to 2x foam inserts included
- Splash-proof design for safe storage and transport
- High-quality polypropylene ensures heat resistance, stiffness and impact resistance
- 2 x foldable, ergonomic handles for comfortable transportation
- Equipped with padlock hole to secure case

Technical data

Inside dimensions: 16.3" x 10.7" x 3.7"
 Outside dimensions: 17.5" x 13" x 5.125"

Maximum payload: 55 lbsWeight: 3.74 lbs

Standard Accessories-Included

• 2 x Foam inserts for bottom and lid

Logistic data

Product weightGross weight

Dimensions of individual packaging

Pieces per export carton

Gross weight export carton

Dimensions of export carton

Container quantity (20'/40'/40'HC)

3.74 lbs 4.3 lbs

17.5" x 13" x 5.125"

4 pcs. 18.6 lbs

18.25" x 14" x 22.25" 1232 | 2576 | 0

Optional Accessories

4540025 E-case Compartments Kit UPC 7-72995-01789-8




4540026 Perforated Foam Kit UPC 7-72995-01790-4















E-Case L

E-Case L Large Rolling Tool Case

Article No.	4540023
-------------	---------

UPC 7-72995-01787-4

Features

- Member of the modular E-Case-System from Einhell: practical case system for storage/transport of machines and tools
- Locking system for connecting stacked cases ensures easy storage and transport
- High-quality polypropylene ensures heat resistance, stiffness and impact resistance
- Robust and durable construction allows a payload of up to 264 lbs
- Easy transport thanks to telescopic, extra-wide handle
- 6" large wheels enable comfortable rolling on any surface
- Splash-proof design for transport during any weather condition
- Padlock hole applicable as anti-theft device

Technical data

• Inner dimensions 16.375" x 10.75" x 12.625"

264 lbs

Max. load

Product weight 13.77 lbs

Logistic Data

Product weight 13.77 lbs

Pieces per export carton 1 pc.

Dimensions packaging
 19.25" x 18.25" x 29"

Container quantity (20'/40'/40'HC)
 360 / 720 / 864

Standard Accessories- Included

- 1 x E-Case L
- 1 x Hand Tool Tray
- 1 x Label
- 2 x Spacer clips

Optional Accessories

4540022 E-case S-F UPC 7-72995-01786-7

Einhell

4540025 E-case Compartments Kit UPC 7-72995-01789-8




4540026 Perforated Foam Kit UPC 7-72995-01790-4













E-Case Tower

E-Case Tower Rolling Tool Case

4540024

UPC 7-72995-01788-1

Features

- Member of the modular E-Case-System from Einhell: practical case system for storage/transport of machines and tools
- Locking system for connecting stacked cases ensures easy storage and transport
- High-quality polypropylene ensures heat resistance, stiffness and impact resistance
- Robust and durable construction allows a payload of up to 264 lbs
- Easy transport thanks to telescopic, extra-wide handle
- 6" large wheels enable comfortable rolling on any surface
- Splash-proof design for transport during any weather condition
- aoldable + ergonomic handle for comfortable carrying up to 198 lbs,
 e.g. while pulling out of car trunk
- Padlock lock applicable as anti-theft device

Technical data

• Inner dimensions 16.3" x 10.7" x 3.7" (E-Case S-F)

16.375" x 10.75" x 12.625" (E-Case L)

Max. total load 264 lbsProduct weight 22.3 lbs

Logistic data

Product weight 22.3 lbs

Pieces per export carton 1 pc.

Dimensions packaging
 16.125" x 18.25" x 28"

Container quantity (20'/40'/40'HC)
 210 / 435 / 522

Standard Accessories- Included

- 1 x E-Case S-F comes with Foam inlay (top and lid)
- 1 x E-Case S-C comes with compartments (2 x large, 3 x middle, 4 x small)
- 1 x E-Case L comes with Tool Tray
- 3 x Labels
- 2 x Spacer Clips





E-Case Perforated Foam

E-Case Perforated Foam Kit for E-Case S-F

Article No. 4540026

UPC 7-72995-01790-4

Features

- Applicable for the Einhell E-Case System
- Individual + precise adjustment possible thanks to small-scale grid
- Storage of sensitive equipment like cameras or measuring devices
- Pre-cut grid allows easy adjustment by hand
- Includes 1 x adjustable raster foam insert

Logistic data

Gross weight

Product weight 0.5 lbs

Dimensions single packaging 16.5" x 11" x 3.625"

0.66 lbs

Pieces per export carton 12 pcs.

Gross weight of export carton 9.24 lbs

Dimensions export carton 22" x 16.125 " x 17"

Container quantity (20'/40'/40'HC) 3624 | 7548 | 8664











E-Case Compartments Kit

E-Case Compartments Kit for E-Case S-F

Article No.

4540025

UPC

7-72995-01789-8

Features

- Even more flexibility thanks to additional plastic compartments: 2 x long, 3 x medium, 4 x short
- Short compartments ideal for screws and nails
- Application possible together with foam insertion of the lid

Technical data

Dimensions plastic axle "long": 10.875" x 3.75" x .1875"
Dimensions plastic axle "medium": 5.375" x 3.75" x .1875"
Dimensions plastic axle "short": 2.5" x 3.75" x .1875"

Logistic Data

Product weight 0.77 lbs
Gross weight 1.1 lbs

Dimensions of individual packaging
 11.125" x 3.9375" x 2.875"

Pieces per export carton 24 pcs.Gross weight export carton 24.64 lbs

Dimensions of export carton 17" x 13.625" x 18.875"
 Container quantity (20'/40'/40'HC) 8256 / 17184 / 21480



