



Building Product Information

Clearlite Acrylic Drop in Baths

Version: 1 : August 2023

Class 1

Product Name Pacific, Matisse, Dina, Kahlo, Varo

Product Line

Product Identifier Baths

Product Description

Clearlite Drop in Baths are suitable for residential and commercial applications. They are manufactured from thermoformed Sanitary grade Acrylic and reinforced with a fibreglass sandwich laminate. Available only in white

Sizes

- Dina : 1200x820mm
- Pacific : 1655x740mm & 1525x740mm
- Matisse : 1655x740mm
- Kahlo: 1675x750mm & 1800x800mm
- Varo: 1675x750mm & 1800x800mm

Features

- The Pacific, Matisse and Dina baths feature a fully moulded 20mm tall upstand.
 - The Kahlo & Varo baths can have optional factory fitted 15mm powder coated aluminium upstands
 - Drainage to the waste will be no less than a 1:50 gradient
 - All baths except the Dina are available with an optional timber support frame
 - Baths can be used as Shower over bath when an optional acrylic wall liner, Bath panel or enclosure is specified
-

Relevant Building Code Clauses

- B2 - Durability
 - E3 - Internal Moisture
 - G1 - Personal Hygiene
 - G12 - Water Supplies
-

Contribution to Compliance

- E3/AS1 3.2.2– Baths have a full 20mm perimeter upstand or a factory fitted upstand that an impervious wall liner can be sealed against preventing water penetration
- B2/AS1 - Durability: Clearlite baths with normal maintenance meets the Durability requirements of Nominated Building Elements for Plumbing & Pipe fixtures of not less than 5 years
- Clearlite baths are designed to AS/NZS 2023-1995 Baths for Ablutionary Purposes
- G12.3.5 - Requires hot water for personal washing, showering or bathing

When used as a shower over bath the following additions apply

- E3/AS3.3.1.3 -Shower over baths
- E3/AS1 3.3.1.2- Shower wall linings
- F2 AS1 1.1.1- Human Impact

Scope of Use

- Clearlite drop in baths are for internal installations only.
- They are suitable for residential and commercial applications

Conditions of Use

- The bath's top perimeter flange must be installed level to ensure drainage.
- The bath's top perimeter and floor must be supported to prevent any deflection
- For safety reasons hot water temperature must be limited to 55 ° C
- Any Plumbing must be carried out by a certified Plumber

Additional Information

Installation information visit - <https://clearlite.co.nz/pages/installation-instructions>

Warranty & Maintenance information visit - <https://clearlite.co.nz/pages/warranty>

Contact Details

Manufacture Location	New Zealand
Legal and trading name	OPR Ltd trading as Clearlite Bathrooms
Address for service	54-58 Hillside Rd, Glenfield, Auckland 0627
Website	www.clearlite.co.nz
Email	iinfo@clearlite.co.nz
Phone number	(09) 4443780
Manufacturers NZBN	9429038152573

Warnings and Bans

This building product is not subject to warning or ban under section 26 of the Building Act 2004