



## Building Product Information

### Clearlite Back to Wall Bath

---

**Version: 2** : March 2024

#### Class 1

**Product Name** Varo Back to Wall Bath

**Product Line**

**Product Identifier** Baths

---

### Product Description

The Varo back to wall bath is manufactured from thermoformed Sanitary grade acrylic and reinforced with a fibreglass sandwich construction laminate. Drainage to the waste will be no less than a 1:50 gradient.

- The Varo bath is offered in two sizes - 1525mmx740mm and 1675x750mm.
  - Available in left hand and right hand versions ( 1675mm can also be used in an Alcove Installation)
  - The 1525mm bath includes an integrated side skirt on the front and on one end and comes with a metal support frame with adjustable feet.
  - The 1675mm bath includes an integrated skirt on its front and ends. It comes with a metal support frame with adjustable feet.
  - The bath can be factory fitted with 30mm Powder coated Aluminium upstands
  - It may be specified with a full shower over bath package which includes the bath, wall liner and bath swing
- 

### Relevant Building Code Clauses

- B2 - Durability
  - E3 - Internal Moisture
  - G1 - Personal Hygiene
  - G12 - Water Supplies
-

## Contribution to Compliance

- E3/AS1 3.2.2– Baths have a full 30mm perimeter upstand or a factory fitted upstand that an impervious wall liner can be sealed against preventing water penetration
- B2/AS1 - Durability: Clearlite baths with normal maintenance meets the Durability requirements of Nominated Building Elements for Plumbing & Pipe fixtures of not less than 5 years
- Clearlite baths are designed to AS/NZS 2023-1995 Baths for Ablutionary Purposes
- G12.3.5 - Requires hot water for personal washing, showering or bathing

When used as a shower over bath the following additions apply

- E3/AS3.3.1.3 -Shower over baths
- E3/AS1 3.3.1.2- Shower wall linings
- F2 AS1 1.1.1- Human Impact

---

## Scope of Use

- Clearlite back to wall baths are for internal installations only.
- They are suitable for residential and commercial applications

---

## Conditions of Use

- The bath's top perimeter flange must be installed level to ensure drainage.
- For safety reasons hot water temperature must be limited to 50 ° C
- Any Plumbing must be carried out by a certified Plumber

---

## Additional Information

Installation information visit - <https://clearlite.co.nz/pages/installation-instructions>

Warranty & Maintenance information visit - <https://clearlite.co.nz/pages/warranty>

---

## Contact Details

<b>Legal and trading name of Importer</b>	OPR Ltd trading as Clearlite Bathrooms
<b>Importer Address for</b>	54-58 Hillside Rd, Glenfield, Auckland 0627
<b>Importer Website</b>	<a href="http://www.clearlite.co.nz">www.clearlite.co.nz</a>
<b>Importer Email</b>	<a href="mailto:info@clearlite.co.nz">info@clearlite.co.nz</a>
<b>Importer Phone number</b>	(09) 4443780
<b>Manufacturers NZBN</b>	9429038152573

---

## Warnings and Bans

This building product is not subject to warning or ban under section 26 of the Building Act 2004