



## Building Product Information

### Bolero Vanity Series

---

**Version:** 1 : August 2023

#### Class 1

**Product Name** Bolero

#### Product Line

**Product Identifier** Vanities

---

### Product Description

The Bolero vanity is available in a range of sizes and configurations. It consists of a cabinet matched with a top (washbasin) of Cast mineral Composite.

The Bolero cabinet is constructed from low formaldehyde moisture resistant board finished with a low pressure laminate (melamine). The board is sourced from New Zealand's sustainable FSC certified Radiata pine plantations. Edges are taped with colour matching edge tapes bonded with PUR bonding technology providing a heat resistant, moisture resistant and near seamless bond

Configurations include

- Classic Floor (Doors & Drawers)
- Classic Wall (Doors & Drawers)
- Wall Open
- Single Drawer
- Single Drawer Open
- Double drawer Wall
- Double Drawer Floor

Mineral composite top sizes

- 750x460mm
- 900x460mm
- 1200x460mm
- 1500x460mm Double basin

## Relevant Building Code Clauses

- G1 - Personal Hygiene
  - B2 - Durability
  - G12 - Water Supplies
  - F2 - Hazardous Building materials
- 

## Contribution to Compliance

- G1. 3.2- The Composite tops are impervious to water and stain resistant.
  - G1 AS1 - 2.6.1- AS/NZS 1730:1996-Washbasins
  - B2/AS1 - Durability: The vanity with normal maintenance meets the Durability requirements of Nominated Building Elements for Plumbing & Pipe fixtures of not less than 5 years
  - G12.3.5 - Requires hot water for personal washing, showering or bathing
  - F2.3.1 - Clearlite vanities are constructed from low emission E1 standard board
- 

## Scope of Use

- Clearlite Vanities are for internal installations only.
  - They are suitable for use in Residential and Commercial applications.
- 

## Conditions of Use

- Vanity cabinets require walls to be plumb and flat.
  - While constructed from moisture resistant board it is recommended the room be well ventilated
  - Do not position the vanity cabinet in the direct path of any water, any spillages must be wiped up immediately
  - Cabinets must be installed level and without any twist for doors and drawers to operate
  - Cabinets must be attached to the walls using suitable hardware fixed into solid fixings such as studs or noggs
  - When installed, the cabinet must be sealed to the wall.
  - When installed, the vanity top must be sealed to the wall and cabinet
  - Any Plumbing must be carried out by a certified Plumber
-

## Additional Information

Installation information visit - <https://clearlite.co.nz/pages/installation-instructions>

Warranty & Maintenance information visit - <https://clearlite.co.nz/pages/warranty>

Building Product Information for the individual components visit - <https://clearlite.co.nz/pages/bpir>

---

## Contact Details

<b>Manufacture Location</b>	New Zealand
<b>Legal and trading name</b>	OPR Ltd trading as Clearlite Bathrooms
<b>Address for service</b>	54-58 Hillside Rd, Glenfield, Auckland 0627
<b>Website</b>	<a href="http://www.clearlite.co.nz">www.clearlite.co.nz</a>
<b>Email</b>	<a href="mailto:info@clearlite.co.nz">info@clearlite.co.nz</a>
<b>Phone number</b>	(09) 4443780
<b>Manufacturers NZBN</b>	9429038152573

---

## Warnings and Bans

This building product is not subject to warning or ban under section 26 of the Building Act 2004

---