



Building Product Information

Pinnacle Pro Vanity Series

Version: 1 : August 2023

Class 1

Product Name Pinnacle Pro

Product Line

Product Identifier Vanities

Product Description

The Pinnacle Pro vanity is available in a range of sizes and configurations. It consists of a cabinet matched with a Solid Surface benchtop.

Any of the Clearlite VC Basins (sold separately) can be mounted on the Pinnacle Pro vanity. For flexibility the Benchtops are provided undrilled for Plumbing . Other Manufacturers Basins/vessels can also be mounted on the unit.

The Pinnacle Pro cabinet is constructed from low formaldehyde moisture resistant board finished with a low pressure laminate (melamine). The board is sourced from New Zealand’s sustainable FSC certified Radiata pine plantations. Edges are taped with colour matching edge tapes bonded with PUR bonding technology providing a heat resistant, moisture resistant and near seamless bond

Configurations include

- Single Drawer
- Single Drawer Open (excludes 1500mm Double basin)
- Double drawer Wall

Solid Surface Benchtops

- 750x460mm
- 900x460mm
- 1200x460mm
- 1500x460mm

Relevant Building Code Clauses

- G1 - Personal Hygiene
 - B2 - Durability
 - G12 - Water Supplies
 - F2 - Hazardous Building materials
-

Contribution to Compliance

- G1. 3.2- The Benchtops are impervious to water and stain resistant.
 - B2/AS1 - Durability: The Vanity with normal maintenance meets the Durability requirements of Nominated Building Elements for Plumbing & Pipe fixtures of not less than 5 years
 - G12.3.5 - Requires hot water for personal washing, showering or bathing
 - F2.3.1 - Clearlite vanities are constructed from low emission E1 standard board
-

Scope of Use

- Clearlite Vanities are for internal installations only.
 - They are suitable for use in Residential and Commercial applications.
-

Conditions of Use

- Vanity cabinets require walls to be plumb and flat.
 - While constructed from moisture resistant board it is recommended the room be well ventilated
 - Do not position the vanity cabinet in the direct path of any water, any spillages must be wiped up immediately
 - Cabinets must be installed level and without any twist for doors and drawers to operate
 - Cabinets must be attached to the walls using suitable hardware fixed into solid fixings such as studs or noggs
 - When installed, the cabinet must be sealed to the wall.
 - When installed, the bench top must be sealed to the wall and cabinet, basins must be sealed to the benchtop.
 - Any Plumbing must be carried out by a certified Plumber
-

Additional Information

Installation information visit - <https://clearlite.co.nz/pages/installation-instructions>

Warranty & Maintenance information visit - <https://clearlite.co.nz/pages/warranty>

Building Product Information for the individual components visit - <https://clearlite.co.nz/pages/bpir>

Contact Details

Manufacture Location	New Zealand
Legal and trading name	OPR Ltd trading as Clearlite Bathrooms
Address for service	54-58 Hillside Rd, Glenfield, Auckland 0627
Website	www.clearlite.co.nz
Email	info@clearlite.co.nz
Phone number	(09) 4443780
Manufacturers NZBN	9429038152573

Warnings and Bans

This building product is not subject to warning or ban under section 26 of the Building Act 2004
