



Building Product Information

Clearlite Sureseal Shower Trays

Version: 1 : August 2023

Class 1

Product Name Clearlite Sureseal Shower Trays

Product Line

Product Identifier Showers

Product Description

Clearlite Sureseal trays are for internal use only and are suitable for residential and commercial applications. Clearlite Sureseal trays are manufactured from thermoformed Sanitary grade Acrylic and reinforced with a fibreglass sandwich laminate. Waterproofing of floors is not required in the immediate area that the tray will cover. The trays have a full 20mm perimeter upstand and can be used with acrylic wall liners or with tiles. Drainage to the waste will be no less than a 1:50 gradient.

Sizes

- Square sizes - 900x900mm, 1000x1000mm,
- Rectangular sizes 900x760mm, 900x1000mm & 1200x900mm
- Round sizes 900x900mm, 1000x1000mm & 1200x800mm
- Angle Corner sizes 900x900mm & 1000x1000mm
- Centre waste (corner waste options available on selected sizes)

The trays are supplied with a Clearlite 40mm Easyclean waste trap

Relevant Building Code Clauses

- E3 - Internal Moisture
 - B2- Durability
 - G1 - Personal Hygiene
 - G12– Water Supplies
-

Contribution to Compliance

- E3/AS1 3.3.1- Clearlite shower trays and Wall linings are impervious to water
- E3/AS1 3.3.2 2- Clearlite shower trays have a full 20mm perimeter upstand with a minimum fall to waste of 1:50. When used with acrylic wall Linings the junctions will be constructed in accordance with Fig 4b (E3/AS1)
- B2.3.1 - Durability: Clearlite shower trays with normal maintenance meets the Durability requirements of Nominated Building Elements for Plumbing & Pipe fixtures of not less than 5 years
- Clearlite Shower trays are designed to AS 3558-1996 Shower Bases and Modules
- G1.3.2—Avoids Harbours dirt or germs
- G12.3.5 - Requires hot water for personal washing, showering or bathing

Scope of Use

Clearlite Shower trays are for internal installations only. They are suitable for residential and commercial applications.

They are designed to be used in conjunction with Clearlite Wall Liners and Door sets. They can be installed on Timber or Concrete floors. Any floor coverings should be laid up to the tray not under it. (e.g Tiles & Vinyl)

Conditions of Use

- Floors must be level and flat to ensure proper drainage
- The tray's underside feet must be fully supported
- Only the Sealants provided by the manufacturer must be used in the installation
- Any Plumbing must be carried out by a certified Plumber

Additional Information

Installation information visit - <https://clearlite.co.nz/pages/installation-instructions>

Warranty & Maintenance information visit - <https://clearlite.co.nz/pages/warranty>

Contact Details

Manufacture Location	New Zealand
Legal and trading name	OPR Ltd trading as Clearlite Bathrooms
Address for service	54-58 Hillside Rd, Glenfield, Auckland 0627
Website	www.clearlite.co.nz
Email	info@clearlite.co.nz
Phone number	(09) 4443780
Manufacturers NZBN	9429038152573

Warnings and Bans

This building product is not subject to warning or ban under section 26 of the Building Act 2004