



MORE PRODUCTIVE MEETINGS.

P300 INTELLIMIX® AUDIO CONFERENCING PROCESSOR

The P300 IntelliMix® Audio Conferencing Processor quickly and easily integrates with Microflex® Advance™ Array Microphones, providing a high-quality audio conferencing solution with extremely intelligible meeting sound.



AUDIO PERFORMANCE

Proprietary IntelliMix DSP algorithms provide echo- and noise-free conferencing audio, for better interaction and natural communication with remote participants.



SIMPLICITY

Pre-defined templates for system configuration reduce programming time and allow installation within seconds.



INTUITIVE CONNECTIONS

Industry-first mute sync functionality for better operation with leading third-party software codecs.



SHURE NETWORK AUDIO ENCRYPTION

AES-256 encryption technology can help protect confidential content.

+ FEATURES

IntelliMix® DSP: Acoustic echo cancellation, noise reduction and automatic gain control for up to 8 Dante channels

10 Dante input channels, 2 output channels

14 x 6 Matrix Mixer

Versatile Connectivity: Single Ethernet connectivity, 2 analog audio inputs / 2 outputs, USB 2.0, 3.5mm Mobile input (1/8")

Power over Ethernet plus (PoE+)

Designer 3.1 Configuration Software compatible

Third-party control system compatible



shure.com

© 2019 Shure Incorporated



ANIUSB-MATRIX USB AUDIO NETWORK INTERFACE

The ANIUSB-MATRIX USB Audio Network Interface with Matrix Mixing provides a versatile hub for collaboration in small to medium-size meeting rooms, suitable for both room video conference systems and soft codec solutions. The device presents a budget-friendly companion to Microflex® Advance™ Array Microphones, for AV conferencing applications that leverage the integrated processing functionality of existing video codecs in the room.

+ FEATURES

- 4 Dante audio inputs / 2 outputs
- 1 analog audio input / 1 output
- USB 2.0
- 6 X 4 Matrix Mixer
- Per channel Equalizer, Mute, Limiter, Gain
- Browser-based remote control
- Single Ethernet connectivity
- 10 configuration presets
- Third-party control system compatible
- Power over Ethernet (PoE)

