

BC-5X5S

5 Mini Coax High-Resolution & 5 Single-Strand Bulk Cable



Kramer's BC-5X5S is a high-resolution, 28AWG 75 Ω 5 mini-coaxial cable with 5 additional 28AWG single strands and an outer shield. Its unique design is ideal for building into 5 BNC or 15-pin HD (VGA/UXGA) cables and routing computer graphic video signals in professional AV systems

FEATURES

Quality Construction - Each coax has a 28AWG solid center conductor and dual shield design consisting of copper braid and aluminum Mylar foil. A dual layer outer shield surrounds the other components and consists of a copper braid and aluminum Mylar foil. Coax jackets are color-coded red, green, blue, yellow, black. Rugged and flexible jacket with internal rip cord and sequential markings every meter

Extra Single Strands - Extra strands allow passing of extra pins for ID bit support in 15-pin HD cables

Universal Compatibility - Compatible with Kramer's compression connectors as well as typical crimp systems



TECHNICAL SPECIFICATIONS

COAX Center Conductor: 28AWG 7/36 tinned copper

Dielectric: Foam polyethylene

Shield: (A) 85% braid 38AWG tinned copper. (B) Aluminum Mylar foil 25% overlap rate

Inner Jacket: PVC

Jacket Colors: Red, green, blue, yellow, black

DIAMETERS Center Conductor: 0.38mm (0.015in)

Dielectric: 1.6mm (0.063in)

Individual Coax: 2.75mm (0.108in)

ELECTRICAL Impedance: 75Ω

DC Resistance: $237\Omega/km$ ($72.2\Omega/1000ft$)

Capacitance: 60pF/m (18.3pF/ft)

Velocity of Propagation: 78%

Temperature: -20° to 75°C (-4° to 167°F)

Attenuation (dB/100ft): 0.6dB@1MHz, 1.2dB@3.6MHz, 1.4dB@5MHz,

1.7dB@7MHz, 2dB@9MHz, 2.1dB@10MHz, 3.8dB@30.0MHz, 5.1dB@50.0MHz,

7.6dB@100MHz

SINGLE STRAND Conductor: 28AWG 7/36 tinned copper

Jacket: HD polyethylene

Diameter: 0.82mm (0.032in)

Jacket Colors: Red, orange, brown yellow & black

OVERALL Shield: (A) 85% braid 36AWG tinned copper.

(B) Aluminum Mylar foil 25% overlap rate

Outer Jacket: PVC

Outer Jacket Color: Dark gray with white lettering

Outer Diameter: 10.0mm (0.393in)

REGULATORY UL: CL2

CSA: FT4

RoHS: 2011/65/EU



CONFIGURATIONS

BC-5X5S-100M

5 Conductor Mini-Coax (28 AWG) + 5 Single Strand Bulk Cable