

# BS-1034EN

## WALL MOUNT SPEAKER

The BS-1034EN is a voice alarm certificated 2 way speaker. With a wide frequency range, it is suitable for announcements and music. The speaker's design, fits architecturally sophisticated environments. The speaker's proportions are based on the Golden Ratio. The BS-1034EN is a wall-mounted speaker, that comes with a plug-in speaker receptacle and a M4 screw terminal input connector allows easy installation.



Article number:BS-1034EN  
 Alternative products: BS-1015BSB,  
 BS-1015BSW

### Specifications

Sensitivity (1#W, 1#m)	89 dB 500 Hz- 5 kHz, pink noise
Frequency response	120 Hz - 20 kHz
Max. SPL (1 m)	94 dB 10 W, 1 m (100 Hz - 10 kHz, pink noise)
Directivity Angle catalogue output	500 Hz: 360°/300° 1 kHz: 150°/130° 2 kHz: 115°/160° 4 kHz: 100°/80°
Rated input (high impedance)	10 W
Tappings	100 V line: 1 kΩ (10 W) / 2 kΩ (5 W) / 3.3 kΩ (3 W) / 10 kΩ (1 W) 70 V line: 500 Ω (10 W) / 1 kΩ (5 W) / 2 kΩ (2.5 W) / 3.3 kΩ (1.5 W) / 10 kΩ (0.5 W)
Speaker component	Low: 5" cone-type High balanced dome tweeter
Finish	HIPS resin, off-white (RAL 9010 or equivalent),
Operating temperature	- 10 °C to +50 °C (14 °F to 122 °F)

# BS-1034EN

WALL MOUNT SPEAKER

Appearance

