



# PE-304/604/BU/WU

Pendant speaker



**Ultra lightweight for  
high-ceiling venues.**

# PE-304/604/BU/WU

## Pendellautsprecher

These pendant speakers are HIPS resin bass-reflex enclosure with a 12 cm (5") cone-type woofer and a balanced-dome tweeter. They are intended to be installed suspended from a ceiling – they are very lightweight, with a stylish design inspired by modern lighting fixtures, allowing them to harmoniously blend in with a room design.

- Remarkably lightweight with stylish design inspired by modern lighting fixtures
- Ideally suited for BGM & announcements
- 8 Ω and 25 V/70 V/100 V operation
- Input impedance is easily changed with a rotary switch on the top of the speaker
- With speaker cable, GRIPPLE® hanging wire & safety wire pre-attached, for faster, easier and more secure installation

### APPLICATION EXAMPLES



Airports



Factories



Shopping malls



Office buildings

### SPEZIFIKATIONEN

	PE-304BU/304WU	PE-604BU/604WU
Enclosure	Bass-reflex type	
Rated Input	30 W (100 V, 70 V line, 8 Ω), 3.7 W (25 V line)	60 W (100 V, 70 V line, 8 Ω), 7.5 W (25 V line)
Rated Impedance	100 V line: 330 Ω (30 W), 1kΩ (10 W), 3.3kΩ (3 W), 10kΩ (1.3 W) 70 V line: 170 Ω (30 W), 330Ω (15 W), 1kΩ (5 W), 3.3kΩ (1.5 W), 10 kΩ (0.6 W) 25 V line: 170 Ω (3.7 W), 330Ω (1.9 W), 1kΩ (0.6 W), 3.3kΩ (0.2 W), 10 kΩ (0.1 W) Low impedance: 8 Ω	100 V line: 170 Ω (60 W), 330Ω (30 W), 670 Ω (15 W), 3.3 k Ω (3 W) 70 V line: 83 Ω (60 W), 170 Ω (30 W), 330 Ω (15 W), 670 Ω (7.5 W), 3.3 kΩ (1.5 W) 25 V line: 83 Ω (7.5 W), 170 Ω (3.7 W), 330 Ω (1.9 W), 670 Ω (0.9 W), 3.3 kΩ (0.2 W) Low impedance: 8 Ω
Sensitivity (1 W, 1 m)	90 dB (330 Hz – 3.3 kHz, pink noise)	
Frequency Response	95Hz bis 20kHz (-10dB)	110Hz bis 20kHz (-10dB)
Speaker Component	12 cm (5") cone-type + balanced-dome tweeter (coaxial)	
UL Code	UL1480 UUMW, ULC-S541	
Operating temperature	-10°C to +50°C	
Finish	PE-304BU: Enclosure: HIPS resin, black Grille: Surface-treated steel plate mesh, black, paint PE-304WU: Enclosure: HIPS resin, white (RAL 9010 equivalent); Grille: Surface-treated steel plate mesh, white (RAL 9010 equivalent), paint	PE-604BU: Enclosure: HIPS resin, black Grille: Surface-treated steel plate mesh, black, paint PE-604WU: Enclosure: HIPS resin, white (RAL 9010 equivalent) Grille: Surface-treated steel plate mesh, white (RAL 9010 equivalent), paint
Dimensions	ø186 x 275 (H) mm (ø7.32" x 10.83") (not including wires and cable)	
Weight	2 kg (not including wires and cable)	2.9 kg (not including wires and cable)
Accessory	GRIPPLE® No. 1 x 1, GRIPPLE® No. 2 x 1, Release key (for GRIPPLE®) x 1, Safety wire (ø 1.5 mm (ø 0.06")) x 1, Hanging wire (ø 2 mm (ø 0.08 ") x 1, Speaker Cable (4-core FPL listed cable 4.6 m (15.09ft) x 1	

\*GRIPPLE® No. 1 and GRIPPLE® No. 2 are hangers for suspending the speaker. GRIPPLE® is a registered trademark of Gripple Limited, England.

Specifications are subject to change without notice. Printed in Germany (1408) 833TEEC252