

<b>CERINȚE MINIME</b>	
Tip	Mixer – Preamplificator stereo cu 2 zone
Tensiune de alimentare	220V/50Hz
Consum de energie	Maximum 20VA
Intrari	Minimum 4x Intrari pe conector phoenix; Minimum 2x Intrari stereo pe conector RCA.
Iesiri	Minimum 2x Iesiri pe conector phoenix
Control	Interfata RS232
Raspuns in frecventa	Minimum intervalul 10Hz – 50kHz
THD	< 0,01 %
Impedanta de intrare	RCA – 20 k $\Omega$ (nebalansat) Phoenix – 47k $\Omega$ (balansat)
Nivelul de intrare	Linie –10dB Mic –50dB
Iesire	Zona – 1 nivel maxim de iesire + 15dB, impedanta – 10k $\Omega$ Zona – 2 nivel maxim de iesire + 15dB, impedanta – 10k $\Omega$
Intrari prioritare	Intrarea 4
Control tonuri	Bass $\pm$ 12dB, Inalte $\pm$ 12dB
HUM & Zgomot	-87dB
Interferenta intre canale	-50dB @ 1kHz
Dimensiuni	Maximum 45x483x200mm
Greutate	Maximum 4kg
Culoare	Negru (RAL 9017)
Garantie	Minimum 2ani