

<b>CERINȚE MINIME</b>	
Tip	Procesor de sunet digital
Tensiune de alimentare	100 - 240 VAC $\pm$ 10%, 50/60 Hz
Consum de energie	Maximum 55W
Raspuns in frecventa	Minimum intervalul 20 Hz la 20 kHz (+0/-3 dB)
Intrari mic/linie	Minimum 4x, conectori 4x XLR/TRS combo
CMRR (1 kHz, 0 dBFS):	>46 dB
Alimentare Phantom Power	48V
THD	<0.01 %
Intrari BGM	Minimum 3x, conectori RCA
THD	<0.004 %
Nivel de iesire	17.7 dBu (15.5 dBV)
Intrari logice	Conector Phoenix cu 2 poli (metric)
8CS si WCP (RS485):	Conector statie de apel Minimum 1x RJ45, Conector panou de control de perete Minimum 1x RJ45
Amplificator	Minimum 2x, conector RJ45, Nivel nominal 1V, Impedanta <100 ohm
Ethernet (10/100 Mbit/s)	Minimum 1x, conector RJ45
Dimensiuni	Maximum 46 x 440 x 359mm
Culoare	Negru (RAL 9017) si Argintiu (RAL 9006)
Greutate	Maximum 7kg
Temperatura de functionare	Minimum intervalul -10°C la 45°C
Garantie	Minimum 2ani