

CERINȚE MINIME	
Tip	Display IPS Videowall
Utilizare	24/7, de interior
Diagonala	49"
Rezolutie	Minimum 1920x1080pixeli
Raport de aspect	16:9
Refresh	Minimum 60Hz
Luminozitate	Minimum 500niti
Contrast	Minimum 1000:1
Unghi de vizualizare	Orizontal 178°, Vertical 178°
Timp de raspuns	Maximum 8ms
Durata de viata	Minimum 50000ore
Orientare	Landscape si Portret
Conectivitate	Minimum 2x Intrari HDMI (HDCP 2.2); Minimum 1x Intrare DisplayPort (HDCP 2.2); Minimum 1x Intrare DVI-D (HDCP 1.4); Minimum 1x Intrare audio; Minimum 1x Intrare RS-232; Minimum 1x Intrare RJ45 (LAN); Minimum 1x Intrare IR; Minimum 1x USB2.0 Tip A; Minimum 1x lesire DisplayPort; Minimum 1x lesire audio; Minimum 1x lesire RS-232;
Memorie interna	Minimum 8GB
Senzori	Senzor de temperatura; Senzor BLU; Senzor de acceleratie (giroscopic)
Tensiunea de alimentare	AC 100-240V~, 50/60Hz
Consum de energie	Maximum 120W
Temperatura de functionare	Minimum intervalul 0°C la 40°C
Dimensiuni	Maximum 1078x608x90mm
VESA	600x400mm
Greutate	Maximum 18kg
Accesorii incluse	Telecomanda, Cablu alimentare, Cablu RS-232, Cablu LAN, Cablu DisplayPort, Receptor IR, Manual
Garantie	Minimum 2ani