

CERINȚE MINIME	
Tip	Display interactiv
Diagonala	86"
Tehnologie de panou	IPS
Raport de aspect	16:9
Rezolutie	Minimum 3840x2160pixeli
Refresh	Minimum 60Hz
Luminozitate	Minimum 440nit
Contrast	Minimum 1200:1
Unghi de vizualizare	Orizontal 178° X Vertical 178°
Adancimea culorii	10 biti (8 biti + FRC)
Timp de raspuns	Maximum 8ms
Durata utilizare	Minimum 50000ore
Utilizare	16/7
Orientare	Landscape
Culoare bezel	Negru
Dimensiuni	Maximum 1958x1160x100mm (W x H x D)
Greutate	Maximum 60kg
VESA	800x600mm
Temperatura de functionare	Minimum intervalul 0 - 40°C
Tensiunea de alimentare	100-240 V ~, 50/60 Hz, 4.0 A
Consum de energie	Maximum 580W
Certificare	Siguranta: CB / NRTL; EMC: FCC Clasa "A" / CE / KC; ErP/ Energy Star: Da / Da.
Slot OPS	Da
Conectivitate	Minimum 3x Intrari HDMI HDCP 2.2; Minimum 1x Intrare RGB (VGA); Minimum 1x Intrare audio; Minimum 1x Intrare RS-232C; Minimum 1x Intrare RJ45 (LAN); Minimum 4x USB 3.0 Tip A; Minimum 1x USB 2.0 Tip A; Minimum 1x USB Tip C (USB-PD, DP-Alt); Minimum 1x lesire HDMI; Minimum 1x lesire audio analogica; Minimum 1x lesire audio digitala; Minimum 2x USB Touch; Minimum 1x lesire RJ45 (LAN)
Difuzoare incorporate	Minimum 2x15W
Accesorii incluse	Cablul de Alimentare 3m, Cablul USB (Tip A-Tip B) 5m, Cablul HDMI 3m, Stilou x 2 Buc., Manual de Utilizare, Ghid de Pornire Rapida (QSG), Cutie din Carton, Telecomanda, Modul Wi-Fi
Touch	Dimensiunea obiectului disponibil pentru atingere: Ø2 mm Timp de raspuns: ≤5 ms

	Precizie: ± 1 mm Interfata: USB 2.0 Grosimea sticlei de protectie: 3T (Anti-reflexie) Transmisia sticlei de protectie: 88% Sistem de operare suportat: Windows 7 / 8 / 10 / Linux / Mac / Android (Suporta atingere cu un singur punct pe Linux / Mac) Puncte de atingere multipla: Maxim 40 de puncte
SoC	Minimum Quad Core A55
GPU	Mali G52MP2
Stocare interna	Minimum 32GB
RAM	Minimum 4GB
Wi-Fi	802.11a/b/g/n/ac/ax (Wi-Fi 6)
LAN	Gigabit LAN
Bluetooth	Minimum 5.0
Garantie	Minimum 2ani