

CERINȚE MINIME	
Tip	Display IPS Digital Signage
Utilizare	24/7, de interior
Diagonala	98"
Rezolutie	Minimum 3840x2160pixeli
Raport de aspect	16:9
Luminozitate	Minimum 500nit
Contrast	Minimum 1300:1
Unghi de vizualizare	178° vertical, 178° orizontal
Timp de raspuns	Maximum 8ms
Orientare	Landscape si portret
Conexiuni	Minimum 2x Intrari HDMI (HDCP 2.2/1.4); Minimum 1x Intrare HDMI (HDCP1.4); Minimum 1x Intrare DisplayPort (HDCP 2.2/1.3); Minimum 1x Intrare DVI-D (HDCP 1.4); Minimum 1x Intrare audio; Minimum 2x USB 2.0 Tip A; Minimum 1x lesire DisplayPort; Minimum 1x lesire audio.
Control extern	Minimum 1x RS232C In/out; Minimum 1x RJ45; Minimum 1x Intrare IR.
Dimensiuni	Maximum 2192 × 1247 × 84mm (W × H × D)
VESA	800x400mm
Greutate	Maximum 82kg
Stocare interna	Minimum 8GB
Senzori	Senzor de temperatura; Senzor de luminozitate automata; Senzor de current.
Wi-Fi	Incorporat
Temperatura de functionare	Minimum intervalul 0°C la 40°C
Tensiune de alimentare	AC 100 - 240 V ~, 50 / 60Hz
Consum de energie	Maximum 560W
Difuzoare	Minimum 2x 10W
Accesorii incluse	Telecomanda, Cablu alimentare, QSG, Receptor de senzor infraroșu / lumina, Cablu DP 1.8m, Adaptor Phone la RS232C, EYE-BOLT
Garantie	Minimum 2ani