

CERINȚE MINIME	
Tip	Display IPS Digital Signage
Utilizare	16/7, de interior
Diagonala	75"
Rezolutie	Minimum 3840x2160pixeli
Refresh	Minimum 60Hz
Raport de aspect	16:9
Luminozitate	Minimum 330nit
Contrast	Minimum 1200:1
Unghi de vizualizare	178°/178° (H/V)
Timp de raspuns	Maximum 8ms
Orientare	Landscape si portret
Wi-Fi integrat	Da
Wake on LAN	Da
Conectivitate	Minimum 3x Intrari HDMI (HDCP 2.2/1.4); Minimum 2x Intrari USB2.0 Tip A; Minimum 1x lesire Audio.
Control extern	Minimum 1x RS232C In/Out (4 Pin Phone Jack); Minimum 1x Intrare RJ45.
Stocare interna	Minimum 8GB
Senzori	Senzor de temperatura; Senzor de luminozitate automata.
Dimensiuni	Maximum 1678 x 964 x 60mm
VESA	400x400mm
Greutate	Maximum 32kg
Tempertura de functionare	Minimum intervalul 0 °C la 40 °C
Tensiune de alimentare	AC 100-240V~, 50/60Hz
Consum de energie	Maximum 220W
Accesorii incluse	Telecomanda, Cablu alimentare, Adaptor Phone la D-Sub9, Suport de cablu
Garantie	Minimum 2ani