

CERINȚE MINIME	
Tip	Display LCD profesional
Utilizare	16/7
Diagonala	43"
Tehnologie de panou	IPS cu retroiluminare Direct LED
Rezolutie	Minimum 3840x2160pixeli
Rezolutii suportate (minimum)	1280 x 720pixeli; 1920 x 1080pixeli; 1920 x 1200pixeli; 3840 x 2160pixeli; 4096 x 2160pixeli; 640 x 480pixeli; 720 x 480pixeli; 720 x 576pixeli.
Zona de afisare	Minimum 941x529mm
Raport de aspect	16:9
Distanta dintre pixeli	Maximum 0.245mm
Luminozitate	Minimum 350cd/m ²
Contrast	Minimum 1200:1
Unghi de vizualizare	178° orizontal, 178° vertical
Adâncimea de culoare	1.073 (10bit)
Timp de raspuns	Maximum 8ms
Refresh	Minimum 60Hz
Orientare	Landscape
Media player	Integrat
Formate de imagine suportate	JPG
Formate video suportate	MPG (MPEG1/2/4, max res 1080p@30Hz); MP4 (MPEG2/4, H.263, H.264, HEVC/H.265, max res 3840x2160@60Hz); TS (MPEG2, H.264, HEVC/H.265, max res 3840x2160@60Hz); audio: LPCM, MP3, AAC; WMV (video H.264, Windows Media Video 9, max res 1080p@30Hz, audio WMA 9, WMA 10 Pro)
Formate audio suportate	MP3
Conectivitate	
Intrare video analogica	Minimum 1x VGA; Minimum 1x Compozit;
Intrare video digitala	Minimum 3x HDMI
Intrare audio analogica	Minimum 1x Jack 3,5mm
Control extern	Minimum 1x LAN; Minimum 1x RS232.
USB	Minimum 1x USB Tip A (USB Media Player 5V/500 mA); Minimum 1x USB Tip C (Sursa de alimentare pentru dispozitive externe 5V/3A).
Iesire audio analogica	Minimum 1x Jack 3,5mm
Iesire audio digitala	Minimum 1x SPDIF
Senzori	Senzor integrat de lumină ambientală;

	Senzor integrat de temperatura.
Difuzoare încorporate	Minimum 2x 10W
Tensiune de alimentare	100-240 V AC; 50/60 Hz;
Consum de energie	Maximum 72W
Dimensiuni	Maximum 971 x 560 x 71mm (W x H x D)
VESA	400x200mm
Greutate	Maximum 11kg
Temperatura de functionare	Minimum intervalul 0°C la 40°C
Accesorii incluse	Baterii, Telecomanda, Cablu alimentare, Cablu HDMI, Manual de utilizare
Garantie	Minimum 2ani