

CERINȚE MINIME	
Tip	Display LCD profesional
Utilizare	18/7
Diagonala	86"
Tehnologie de panou	IPS cu retroiluminare Direct LED
Rezolutie	Minimum 3840x2160pixeli
Rezolutii suportate (minimum)	1280 x 720pixeli; 1920 x 1080pixeli; 1920 x 1200pixeli; 3840 x 2160pixeli; 4096 x 2160pixeli; 640 x 480pixeli; 720 x 480pixeli; 720 x 576pixeli.
Zona de afisare	Minimum 1895.04x1065.96mm
Raport de aspect	16:9
Distanta dintre pixeli	Maximum 0.494mm
Luminozitate	Minimum 350cd/m ²
Contrast	Minimum 8000:1
Unghi de vizualizare	178° orizontal, 178° vertical
Adâncimea de culoare	1.073 (10bit)
Timp de raspuns	Maximum 8ms
Refresh	Minimum 60Hz
Orientare	Landscape si Portret
Media player	Integrat
Formate de imagine suportate	JPG
Formate video suportate	MPG (MPEG1/2/4, max res 1080p@30Hz); MP4 (MPEG2/4, H.263, H.264, HEVC/H.265, max res 3840x2160@60Hz); TS (MPEG2, H.264, HEVC/H.265, max res 3840x2160@60Hz); audio: LPCM, MP3, AAC; WMV (video H.264, Windows Media Video 9, max res 1080p@30Hz, audio WMA 9, WMA 10 Pro)
Formate audio suportate	MP3
Conectivitate	
Intrare video analogica	Minimum 1x VGA; Minimum 1x Compozit;
Intrare video digitala	Minimum 3x HDMI
Intrare audio analogica	Minimum 1x Jack 3,5mm
Control extern	Minimum 1x LAN; Minimum 1x RS232.
USB	Minimum 1x USB 2.0 Tip A (USB Media Player); Minimum 1x USB Tip C (Sursa de alimentare pentru dispozitive externe 5V/3A).
lesire audio analogica	Minimum 1x Jack 3,5mm
lesire audio digitala	Minimum 1x SPDIF
Senzori	Senzor integrat de lumina ambientala;

Difuzoare încorporate	Minimum 2x 10W
Tensiune de alimentare	100-240 V AC; 50/60 Hz;
Consum de energie	Maximum 251W
Dimensiuni	Maximum 1928 x 1100 x 84mm (W x H x D)
VESA	600x400mm
Greutate	Maximum 47kg
Temperatura de functionare	Minimum intervalul 0°C la 40°C
Accesorii incluse	Baterii, Telecomanda, Cablu alimentare, Cablu HDMI, Manual de utilizare
Garantie	Minimum 2ani