

CERINȚE MINIME	
Tip	Display LCD IPS Digital Signage
Utilizare	18/7
Diagonala	65"
Tehnologie de panou	IPS cu retroiluminare Direct LED
Rezolutie	Minimum 3840x2160pixeli
Rezolutii suportate (minimum)	1024 x 768pixeli; 1280 x 1024pixeli; 1280 x 720pixeli; 1360 x 768pixeli; 1366 x 768pixeli; 1400 x 1050pixeli; 1440 x 900pixeli; 1600 x 1200pixeli; 1650 x 1050pixeli; 1920 x 1080pixeli; 1920 x 1200pixeli; 1920 x 2160pixeli; 2560 x 1440pixeli; 2560 x 1600pixeli; 3840 x 2160pixeli; 4096 x 2160pixeli.
Raport de aspect	16:9
Luminozitate	Minimum 400cd/m ²
Contrast	Minimum 8000:1
Unghi de vizualizare	178° orizontal, 178° vertical
Adâncimea de culoare	1.073 (8bit + FRC)
HDR	HDR10; HLG; PQ
Timp de raspuns	Maximum 6ms
Refresh	Minimum 60Hz
Orientare	Landscape si portret
Media player	Integrat
Formate de imagine suportate	JPG
Formate video suportate	MPG (MPEG1/2/4, max res 1080p@30Hz); MP4 (MPEG2/4, H.263, H.264, HEVC/H.265, max res 3840x2160@60Hz); TS (MPEG2, H.264, HEVC/H.265, max res 3840x2160@60Hz); audio: LPCM, MP3, AAC; WMV (video H.264, Windows Media Video 9, max res 1080p@30Hz, audio WMA 9, WMA 10 Pro)
Formate audio suportate	MP3
Conectivitate Intrare video digitala	Minimum 1x DisplayPort 1.2 (cu HDCP); Minimum 2x HDMI 2.0 (cu HDCP).
Control	Minimum 1x LAN; Minimum 1x Mini Jack 3.5mm IR Remote ; Minimum 1x RS-232C.
Date de intrare	Minimum 1x USB 2.0 (MediaPlayer)
Iesire audio analogica	Minimum 1x Jack 3,5mm
Senzori	3x Senzori integrati de temperatura
Difuzoare încorporate	Minimum 2x 10W
Tensiune de alimentare	100-240 V AC; 50/60 Hz
Consum de energie	Maximum 265W
Dimensiuni	Maximum 1463 x 838 x 69mm (W x H x D)
VESA	400x400mm

Greutate	Maximum 30kg
Temperatura de functionare	Minimum intervalul 0°C la 40°C
Accesorii incluse	Baterii, Telecomanda, Cablu alimentare, Cablu HDMI, Manual de utilizare
Garantie	Minimum 2ani