

DL4 DURAPLEX OMNIDIRECTIONAL WATERPROOF LAVALIER MICROPHONE

SPECIFICATIONS

(SUBJECT TO CHANGE)

Microphone Capsule	MEMS
Polar Pattern	Omnidirectional
Frequency Response	20 Hz to 20 kHz
Sensitivity	-42.5 dBV (7.5 mV _{RMS}) @ 1 kHz
Self-Noise	31 dB SPL-A <i>A-weighted, Equivalent Acoustical</i>
Signal-to-Noise Ratio	63 dB
Maximum SPL	132.0 dB SPL <i>1 kHz @ 1% THD, typical</i>
Dynamic Range	101.0 dB <i>Typical</i>
Microphone Current Draw	220 µA, maximum
Bias Voltage <i>Recommended Operating Voltage</i>	5 VDC
Housing	Molded ABS
Polarity	MTQG: Positive Pressure on diaphragm produces positive voltage on Pin 3 with respect to Pin 1 LEMO: Positive pressure on diaphragm produces positive voltage on Pin 3 with respect to Pin 1
Cable Diameter	1.6 mm
Cable Length	66.0 in (1.67 m)
Net Weight	15.0 g (0.53 oz)
Capsule Dimensions <i>(L × D)</i>	14.5 mm × 5.2 mm

AVAILABLE MODELS

DL4B/O-LM3-A	DuraPlex Omnidirectional Lavalier Mic, LEMO Connector (Black)
DL4B/O-MTQG-A	DuraPlex Omnidirectional Lavalier Mic, MTQG Connector (Black)
DL4C/O-LM3-A	DuraPlex Omnidirectional Lavalier Mic, LEMO Connector (Cocoa)
DL4C/O-MTQG-A	DuraPlex Omnidirectional Lavalier Mic, MTQG Connector (Cocoa)
DL4T/O-LM3-A	DuraPlex Omnidirectional Lavalier Mic, LEMO Connector (Tan)
DL4T/O-MTQG-A	DuraPlex Omnidirectional Lavalier Mic, MTQG Connector (Tan)
DL4W/O-LM3-A	DuraPlex Omnidirectional Lavalier Mic, LEMO Connector (White)
DL4W/O-MTQG-A	DuraPlex Omnidirectional Lavalier Mic, MTQG Connector (White)

OVERVIEW

Available in lavalier or headset form, DuraPlex has been extensively tested to ensure an IP57 dust-resistant, waterproof rating. Whether shooting reality TV, mounting a professional theatrical tour, or wherever audio takes you, contending with the elements won't slow you down. As comfortable on the beach as it is in a broadcast studio, DuraPlex features a neutral, full sound quality that lives up to the highest audio standards.

The advanced 1.6 mm Shure Plex cable, first introduced with the award-winning TwinPlex subminiature microphone, lasts longer than competing cables due to a dual redundant ground which doubles as a secondary shield. It also offers virtually zero "memory effect," won't kink, and is fully paintable.

FEATURES

- 5 mm omnidirectional subminiature design for discrete placement and improved gain-before-feedback
- IP57 dust-resistant, waterproof rated
- Neutral, full sound quality for film, broadcast, speech, theater, and performance applications
- Advanced 1.6 mm Shure Plex cable:
 - Dual redundant ground in cable serves as secondary shield for unprecedented longevity
 - Immune to memory effect and kinks
 - Fully paintable with typical theater paints, pens, and polishes
- Presence Cap included for tailored frequency response provides additional vocal clarity and presence (3-4 dB boost near 10 kHz)
- Available in four colors: Black, Cocoa, Tan, White
- Available in two connector types: TA4F (mTQG) and LEMO
- Kit includes the following accessories: Case, Foam Windscreen, Snap-fit Windscreen, Single Tie Clip, Sticky Mount, TQG Locking Collar (mTQG/TA4F SKUs only)



DL4B
DuraPlex Omnidirectional Waterproof
Lavalier Microphone (Black)

DL4 DURAPLEX OMNIDIRECTIONAL WATERPROOF LAVALIER MICROPHONE

FURNISHED ACCESSORIES

Single Tie Clip

Presence Cap

Snap-Fit Windscreen

Foam Windscreen

Sticky Mount

Case

Threaded TA4F Adapter
(MTQG SKUs Only)




Lavalier Accessory Kit
For MTQG SKUs (shown in black)


REPLACEMENT ACCESSORIES

RPMDL4WS/B	Foam Windscreens, Black, Qty. 5	RPMDL4STC/T	Single Tie Clip, Tan, Qty. 3	RPMDL4SM	Sticky Mount, Qty. 3
RPMDL4WS/C	Foam Windscreens, Cocoa, Qty. 5	RPMDL4STC/W	Single Tie Clip, White, Qty. 3	RPM40TS	Sticky Mount Adhesives (15 Pieces)
RPMDL4WS/T	Foam Windscreens, Tan, Qty. 5	RPMDL4DTC/B	Dual Tie Clip, Black, Qty. 3	RPM40TS/50	Sticky Mount Adhesives (50 Pieces)
RPMDL4WS/W	Foam Windscreens, White, Qty. 5	RPMDL4DTC/C	Dual Tie Clip, Cocoa, Qty. 3	RPM400TQG	TA4F-XLR Preamp
RPMDL4SFWS/B	Snap-Fit Windscreens, Black, Qty. 3	RPMDL4DTC/T	Dual Tie Clip, Tan, Qty. 3	RPM400LEMO	LEM03-XLR Preamp
RPMDL4SFWS/C	Snap-Fit Windscreens, Cocoa, Qty. 3	RPMDL4DTC/W	Dual Tie Clip, White, Qty. 3	RPMDL4CASE	Zippered lavalier carrying pouch
RPMDL4SFWS/T	Snap-Fit Windscreens, Tan, Qty. 3	RPMDL4FC/B	Frequency Cap, Black, Qty. 5		
RPMDL4SFWS/W	Snap-Fit Windscreens, White, Qty. 3	RPMDL4FC/C	Frequency Cap, Cocoa, Qty. 5		
RPMDL4STC/B	Single Tie Clip, Black, Qty. 3	RPMDL4FC/T	Frequency Cap, Tan, Qty. 5		
RPMDL4STC/C	Single Tie Clip, Cocoa, Qty. 3	RPMDL4FC/W	Frequency Cap, White, Qty. 5		

POLAR PATTERN



FREQUENCY RESPONSE



DH5 DURAPLEX OMNIDIRECTIONAL HEADSET MICROPHONE

SPECIFICATIONS

(SUBJECT TO CHANGE)

Microphone Capsule	MEMS
Polar Pattern	Omnidirectional
Frequency Response	20 Hz to 20 kHz
Sensitivity	-42.5 dBV (7.5 mV _{RMS}) @ 1 kHz
Self-Noise	31 dB SPL-A <i>A-weighted, Equivalent Acoustical</i>
Signal-to-Noise Ratio	63.0 dB
Maximum SPL	132.0 dB SPL <i>1 kHz @ 1% THD, typical</i>
Dynamic Range	101.0 dB <i>Typical</i>
Microphone Current Draw	220 µA, maximum
Bias Voltage <i>Recommended Operating Voltage</i>	5 VDC
Housing	Molded ABS
Polarity	MTQG: Positive Pressure on diaphragm produces positive voltage on Pin 3 with respect to Pin 1 LEMO: Positive pressure on diaphragm produces positive voltage on Pin 3 with respect to Pin 1
Cable Diameter	1.6 mm
Cable Length	66.0 in (1.67 m)
Net Weight	20 g (0.7 oz)
Capsule Dimensions <i>(L × D)</i>	14.5 mm × 5.2 mm
Boom Length	13.6 cm

AVAILABLE MODELS

DH5B/O-LM3	DuraPlex Omnidirectional Headset Microphone, LEMO Connector (Black)
DH5B/O-MTQG	DuraPlex Omnidirectional Headset Microphone, MTQG Connector (Black)
DH5C/O-LM3	DuraPlex Omnidirectional Headset Microphone, LEMO Connector (Cocoa)
DH5C/O-MTQG	DuraPlex Omnidirectional Headset Microphone, MTQG Connector (Cocoa)
DH5T/O-LM3	DuraPlex Omnidirectional Headset Microphone, LEMO Connector (Tan)
DH5T/O-MTQG	DuraPlex Omnidirectional Headset Microphone, MTQG Connector (Tan)

OVERVIEW

With an easy-to-wear headset frame, DuraPlex DH5 features a neutral, full sound quality that lives up to the highest audio standards on any stage or broadcast studio. Also available as a lavalier, DuraPlex has been extensively tested to ensure an IP57 dust-resistant, waterproof rating*. The exclusive 1.6 mm Shure Plex cable with DuraPlex won't kink, offers virtually zero "memory effect," is fully paintable, and simply lasts longer due to a dual redundant ground, which doubles as a secondary shield.

In the theater, onstage, or on television, you can depend on the DuraPlex DH5 headset microphone for consistent professional sound, durability, and longevity.

FEATURES

- 5 mm omnidirectional subminiature design on a silicone boom pivot system that can be placed on the left or right ear
- IP57 dust-resistant, waterproof rated
- Neutral, full sound quality for film, broadcast, speech, theater, and performance applications
- Advanced 1.6 mm Shure Plex cable:
 - Dual redundant ground in cable serves as secondary shield for unprecedented longevity
 - Immune to memory effect and kinks
 - Fully paintable with typical theater paints, pens, and polishes
- Presence Cap included for tailored frequency response provides additional vocal clarity and presence (3-4 dB boost near 10 kHz)
- Available in three colors: Black, Cocoa, Tan
- Available in two connector types: TA4F (mTQG) and LEMO
- Kit includes the following accessories: Case, Foam Windscreen, Snap-fit Windscreen, Single Tie Clip, TQG Locking Collar (mTQG/TA4F SKUs only)



DH5T
DuraPlex Omnidirectional
Headset Microphone (Tan)

DH5 DURAPLEX OMNIDIRECTIONAL HEADSET MICROPHONE

FURNISHED ACCESSORIES

Presence Cap

Foam Windscreen

Snap-Fit Windscreen

Single Tie Clip

Case

Threaded TA4F Adapter
(MTQG SKUs Only)




Headset Accessory Kit
For MTQG SKUs (shown in tan)

REPLACEMENT ACCESSORIES

RPMDL4WS/B	Foam Windscreens, Black, Qty. 5	RPMDL4DTC/B	Dual Tie Clip, Black, Qty. 3	RPMDH5BM	Headset boom mount, Qty. 4
RPMDL4WS/C	Foam Windscreens, Cocoa, Qty. 5	RPMDL4DTC/C	Dual Tie Clip, Cocoa, Qty. 3	RPMDH5B/O-MTQG	Microphone boom, Black, MTQG
RPMDL4WS/T	Foam Windscreens, Tan, Qty. 5	RPMDL4DTC/T	Dual Tie Clip, Tan, Qty. 3	RPMDH5B/O-LM3	Microphone boom, Black, LEM03
RPMDL4SFWS/B	Snap-Fit Windscreens, Black, Qty. 3	RPMDL4FC/B	Frequency Cap, Black, Qty. 5	RPMDH5C/O-MTQG	Microphone boom, Cocoa, MTQG
RPMDL4SFWS/C	Snap-Fit Windscreens, Cocoa, Qty. 3	RPMDL4FC/C	Frequency Cap, Cocoa, Qty. 5	RPMDH5C/O-LM3	Microphone boom, Cocoa, LEM03
RPMDL4SFWS/T	Snap-Fit Windscreens, Tan, Qty. 3	RPMDL4FC/T	Frequency Cap, Tan, Qty. 5	RPMDH5T/O-MTQG	Microphone boom, Tan, MTQG
RPMDL4STC/B	Single Tie Clip, Black, Qty. 3	RPMDH5CASE	Zippered headset carrying case	RPMDH5T/O-LM3	Microphone boom, Tan, LEM03
RPMDL4STC/C	Single Tie Clip, Black, Cocoa. 3	RPMDH5F	Headset frame, Qty. 1	RPM400TQG	TA4F-XLR Preamp
RPMDL4STC/T	Single Tie Clip, Black, Tan. 3	RPMDH5PIVOT	Headset boom pivot, Qty. 5	RPM400LEMO	LEM03-XLR Preamp

POLAR PATTERN



FREQUENCY RESPONSE

