UHD Commercial TV with Essential Smart Function

Commercial TV | UT640S Series

The UT640S Series is specifically designed for diverse business environments. By providing compatibility with AV Control systems and DPM (Display Power Management) as well as its smart connectivity, simple user friendly interface, and UHD picture quality, the UT640S series enhances ease of use while facilitating communications between businesses and their target audiences.



Simple Content Management



High Visibility



Excellent Usability





Embedded Content & Group Management


The embedded Content and Group Management
System allows you to edit and play content,
schedule playlists and groups, and control
Signage via remote control, mouse and mobile
phone without the use of separate PC or software.
This makes content management
much easier and more user-friendly.

SuperSign Control

SuperSign Control is free, basic LG control software that can manage up to 100 displays through a single account and server. Power, volume, and scheduling can be remotely adjusted, and firmware updates supported.

USB Data Cloning

USB data cloning increases efficiency when anaging multiple displays, since installers don't have to set up each display one by one. Once installers copy data to a USB device from one display, it can be easily imported on other displays of the same model through the USB port.



- * These images are provided for illustrative purposes, and the actual GUI may differ.
- * All displays must be connected to the same network.





Real-Time Remote Monitoring

Malfunctions or errors can be easily handled through real-time remote care. When an error occurs, notifications can be sent via SNMP (Simple Network Management Protocol).

Easy Remote Power-On

WOL (Wake-on-LAN) enables users to turn on displays* by sending messages through the network.



AC Power

WOL

True Color, Immersive View

The large size and Ultra HD resolution of the UT640S series enhances the visibility of content and captivates viewers. The LG IPS panel provides a wide range of viewing angles so that content can be clearly seen, regardless of the viewer's position. Each pixel in the IPS panel reproduces true-to-life colors without distorting images.



Amazing Picture Quality and Color

Enjoy Full HD content in 4K Ultra HD quality, optimized by the 4K Upscaler. The 4K upscaler automatically upgrades Full HD content to Ultra HD through several upscaling processes so that images look crisp and clear in any viewing situation. This LG TV can also express intense highlights, vivid colors, and deep black hues on the screen through HDR10.



Compatibility with AV Control Systems

The UT640S series has been certified Crestron Connected®, proving that it has a higher level of compatibility with professional AV controls. This results in seamless integration and automated control*, boosting business management efficiency.


DPM (Display Power Management)

Display Power Management (DPM) can be configured to only be On when there is a TV signal present to manage power more efficiently.



* Network-based control system. May differ by region.







^{*} Dimensions & Jack Panels (Rear/Side) may differ from the above images, so please contact LG sales team to verify before ordering.


^{*}UT640S models ship with a 2 Pole stand (attachable feet). See also VESA spec for wall mounting.


86" | 75"





65" | 55" | 49" | 43"





^{*} Dimensions & Jack Panels (Rear/Side) may differ from the above images, so please contact LG sales team to verify before ordering.

UT640S s	series	86UT640S	75UT640S	65UT640S	55UT640S	49UT640S	43UT640S	
DESIGN	Stand Type	2 Pole	2 Pole	2 Pole	2 Pole	2 Pole	2 Pole	
	Front Color	Dark Meteo Titan	Dark Meteo Titan	Ceramic Black	Ceramic Black	Ceramic Black	Ceramic Black	
DISPLAY	Diagonal Class	86"	75″	65"	55"	49"	43"	
	Resolution	3840 X 2160 (UHD)	3840 X 2160 (UHD)	3840 X 2160 (UHD)	3840 X 2160 (UHD)	3840 X 2160 (UHD)	3840 X 2160 (UHD)	
	Brightness (nits)	350	350	400	400	400	300	
BROADCASTING SYSTEM	Digital	NTSC / ATSC / clear QAM	NTSC / ATSC / clear QAM	NTSC / ATSC / clear QAM	NTSC / ATSC / clear QAM	NTSC / ATSC / clear QAM	NTSC / ATSC / clear QAM	
VIDEO	HDR (10 Pro / HLG)	Yes / Yes	Yes / Yes	Yes / Yes	Yes / Yes	Yes / Yes	Yes / Yes	
AUDIO	Audio Output	10W + 10W	10W + 10W	10W + 10W	10W + 10W	10W + 10W	10W + 10W	
	Speaker System	2.0 ch	2.0 ch	2.0 ch	2.0 ch	2.0 ch	2.0 ch	
	LG Sound Sync	Bluetooth required	Bluetooth required	Bluetooth required	Bluetooth required	Bluetooth required	Bluetooth required	
SUPERSIGN SW COMPATIBILITY	Content Management Software (CMS), Control and Monitoring Software (Control/Control+), Simple Editor							
SIGNAGE FEATURES	Crestron Connected® (Network Based Control), DPM (Digital Power management), Time scheduler, RTC (Real Time Clock), NTP sync timer, BEACON, Embedded CM (contents manager), Embedded GM (Group manager)							
MART FEATURES	webOS 4.5, Smart Home (Launcher Bar), Web Browser, Pre-loaded App (YouTube only), Soft AP, WiFi (bandwidth)(ac), Screen Share (Miracast), LG TV Plus App Compatibility, DIAL, Bluetooth Audio Playback, LG Sound Sync/bluetooth, Mobile Connection Overlay							
HOSPITALITY FEATURES	Hotel Mode / PDM / Installer Menu, Lock mode (Limited), Welcome Screen (Boot Logo), Insert Image, One Channel Map, IP Channel Manager, External Speaker Out (Variable /Fixed, 3.5mm, Stereo (GND, R, L), Max1W with 8Ω), VLAN, Teleadapt/Guestlink (HDMI CEC), Moving Picture Playback (SD/HD/Plus HD), Auto Off / Sleep Timer, Smart Energy Saving, Motion Eye Care							
MAINTENANCE FEATURES	USB Cloning, WOL, SNMP, Diagnostics (Self Diagnostics (USB)), NTSC / ATSC / QAM, Simplink(HDMI-CEC)(1.4), IR Out (RS-232C), Multi-code IR							
JACK INTERFACE	Side	HDMI In 2(2.0), USB (2.0)						
				HDMI In 2(2	0), USB (2.0)			
	Rear		HDMI In (HDCP) 2.0, RF In (tu	`	ical), RS-232C (D-Sub 9pin, Control & Serv	ice), RJ45 2 (Ethernet, SNMP),		
	Rear VESA (W x H)	600×400	HDMI In (HDCP) 2.0, RF In (tu	ner), AV In (3.5mm), Digital Audio Out (Opt	ical), RS-232C (D-Sub 9pin, Control & Serv	ice), RJ45 2 (Ethernet, SNMP),	200 × 200	
		600 x 400 76.5" x 46.8" x 13.6" / 99.2 lbs 1,943 x 1,188 x 345 / 45.0 kg		ner), AV In (3.5mm), Digital Audio Out (Opt External Speaker Out (3.5mm, Stereo, N	ical), RS-232C (D-Sub 9pin, Control & Serv A ax 1W with 8Ω), Service Only (3.5mm)		200 x 200 38.3" x 24.5" x 8.5" / 17.9 lbs 973 x 623 x 216 / 8.1 kg	
MECHANICAL	VESA (W x H)	76.5" x 46.8" x 13.6" / 99.2 lbs	600 × 400 66.7" × 41.3" × 13.6" / 78 lbs	ner), AV In (3.5mm), Digital Audio Out (Opt External Speaker Out (3.5mm, Stereo, N 300 x 300 57.6" x 36" x 10.6" / 47.6 lbs	(cal), RS-232C (D-Sub 9pin, Control & Serv Max 1W with 8Ω), Service Only (3.5mm) 300 × 300 49" × 30.9" × 9.1" / 32 lbs	300 × 300 43.7" × 27.9" × 9.1" / 24.9 lbs	38.3" × 24.5" × 8.5" / 17.9 lbs	
MECHANICAL	VESA (W x H) W x H x D / Weight (with stand)	76.5" x 46.8" x 13.6" / 99.2 lbs 1,943 x 1,188 x 345 / 45.0 kg 76.5" x 43.8" x 3.7" / 97.4 lbs	600 × 400 66.7" × 41.3" × 13.6" / 78 lbs 1,693 × 1,048 × 345 / 35.4 kg 66.7" × 38.3" × 3.5" / 76.3 lbs	ner), AV In (3.5mm), Digital Audio Out (Opt External Speaker Out (3.5mm, Stereo, N 300 x 300 57.6" x 36" x 10.6" / 47.6 lbs 1,463 x 914 x 269 / 21.6 kg 57.6" x 33.3" x 3.5" / 47 lbs	(cal), RS-232C (D-Sub 9pin, Control & Serv Max 1W with 8Ω), Service Only (3.5mm) 300 × 300 49" × 30.9" × 9.1" / 32 lbs 1,244 × 786 × 231 / 14.5 kg 49" × 28.4" × 3.4" / 31.5 lbs	300 x 300 43.7" x 27.9" x 9.1" / 24.9 lbs 1,110 x 709 x 231 / 11.3 kg 43.7" x 25.4" x 3.2" / 24.5 lbs	38.3" x 24.5" x 8.5" / 17.9 lbs 973 x 623 x 216 / 8.1 kg 38.3" x 22.3" x 3.3" / 17.6 lbs	
MECHANICAL	VESA (W×H) W×H×D / Weight (with stand) W×H×D / Weight (without stand)	76.5" x 46.8" x 13.6" / 99.2 lbs 1,943 x 1,188 x 345 / 45.0 kg 76.5" x 43.8" x 3.7" / 97.4 lbs 1,943 x 1,113 x 93.3 / 44.2 kg 83.3" x 49.6" x 11.2" / 130.1 lbs	600 × 400 66.7" × 41.3" × 13.6" / 78 lbs 1,693 × 1,048 × 345 / 35.4 kg 66.7" × 38.3" × 3.5" / 76.3 lbs 1,693 × 973 × 88.8 / 34.6 kg 72.4" × 43.9" × 9.1" / 100.8 lbs	ner), AV In (3.5mm), Digital Audio Out (Opt External Speaker Out (3.5mm, Stereo, N 300 x 300 57.6" x 36" x 10.6" / 47.6 lbs 1,463 x 914 x 269 / 21.6 kg 57.6" x 33.3" x 3.5" / 47 lbs 1,463 x 845 x 87.8 / 21.3 kg 63" x 38.2" x 7.5" / 62.6 lbs	ical), RS-232C (D-Sub 9pin, Control & Serv Jax 1W with 8Ω), Service Only (3.5mm) 300 × 300 49" × 30.9" × 9.1"/32 lbs 1,244 × 786 × 231 / 14.5 kg 49" × 28.4" × 3.4"/31.5 lbs 1,244 × 721 × 87.1 / 14.3 kg 53.5" × 33" × 6.9" / 43 lbs	300 x 300 43.7" x 27.9" x 9.1" / 24.9 lbs 1,110 x 709 x 231 / 11.3 kg 43.7" x 25.4" x 3.2" / 24.5 lbs 1,110 x 645 x 81.1 / 11.1 kg 47" x 30.3" x 6.2" / 29.5 lbs	38.3" x 24.5" x 8.5" / 17.9 lbs 973 x 623 x 216 / 8.1 kg 38.3" x 22.3" x 3.3" / 17.6 lbs 973 x 567 x 85 / 8.0 kg 41.7" x 26" x 6" / 22.5 lbs	
	VESA (W x H) W x H x D / Weight (with stand) W x H x D / Weight (without stand) W x H x D / Weight (Shipping)	76.5" x 46.8" x 13.6" / 99.2 lbs 1,943 x 1,188 x 345 / 45.0 kg 76.5" x 43.8" x 3.7" / 97.4 lbs 1,943 x 1,113 x 93.3 / 44.2 kg 83.3" x 49.6" x 11.2" / 130.1 lbs 2,116 x 1,261 x 285 / 59.0 kg	600 x 400 66.7" x 41.3" x 13.6" / 78 lbs 1,693 x 1,048 x 345 / 35.4 kg 66.7" x 38.3" x 3.5" / 76.3 lbs 1,693 x 973 x 888 / 34.6 kg 72.4" x 43.9" x 9.1" / 100.8 lbs 1,839 x 1,116 x 231 / 45.7 kg	ner), AV In (3.5mm), Digital Audio Out (Opt External Speaker Out (3.5mm, Stereo, N 300 x 300 57.6" x 36" x 10.6" / 47.6 lbs 1,463 x 914 x 269 / 21.6 kg 57.6" x 33.3" x 3.5" / 47 lbs 1,463 x 845 x 87.8 / 21.3 kg 63" x 38.2" x 7.5" / 62.6 lbs 1,600 x 970 x 190 / 28.4 kg	ical), RS-232C (D-Sub 9pin, Control & Serv Jax 1W with 8Ω), Service Only (3.5mm) 300 × 300 49" × 30.9" × 9.1" / 32 lbs 1,244 × 786 × 231 / 14.5 kg 49" × 28.4" × 3.4" / 31.5 lbs 1,244 × 721 × 87.1 / 14.3 kg 53.5" × 33" × 6.9" / 43 lbs 1,360 × 835 × 175 / 19.5 kg	300 x 300 43.7" x 27.9" x 9.1" / 24.9 lbs 1,110 x 709 x 231 / 11.3 kg 43.7" x 25.4" x 3.2" / 24.5 lbs 1,110 x 645 x 81.1 / 11.1 kg 47" x 30.3" x 6.2" / 29.5 lbs 1,193 x 770 x 158 / 13.4 kg	38.3" x 24.5" x 8.5" / 17.9 lbr 973 x 623 x 216 / 8.1 kg 38.3" x 22.3" x 3.3" / 17.6 lbs 973 x 567 x 85 / 8.0 kg 41.7" x 26" x 6" / 22.5 lbs 1,060 x 660 x 152 / 10.2 kg	
MECHANICAL ELECTRICAL	VESA (W x H) W x H x D / Weight (with stand) W x H x D / Weight (without stand) W x H x D / Weight (Shipping) Voltage	76.5" x 46.8" x 13.6" / 99.2 lbs 1,943 x 1,188 x 345 / 45.0 kg 76.5" x 43.8" x 3.7" / 97.4 lbs 1,943 x 1,113 x 93.3 / 44.2 kg 83.3" x 49.6" x 11.2" / 130.1 lbs 2,116 x 1,261 x 285 / 59.0 kg AC 120 V - 50 / 60 Hz	600 x 400 66.7" x 41.3" x 13.6" / 78 lbs 1,693 x 1,048 x 345 / 35.4 kg 66.7" x 38.3" x 3.5" / 76.3 lbs 1,693 x 973 x 888 / 34.6 kg 72.4" x 43.9" x 9.1" / 100.8 lbs 1,839 x 1,116 x 231 / 45.7 kg AC 120 V - 50 / 60 Hz	ner), AV In (3.5mm), Digital Audio Out (Opt External Speaker Out (3.5mm, Stereo, N 300 × 300 57.6" × 36" × 10.6" / 47.6 lbs 1,463 × 914 × 269 / 21.6 kg 57.6" × 33.3" × 3.5" / 47 lbs 1,463 × 845 × 878 / 21.3 kg 63" × 38.2" × 7.5" / 62.6 lbs 1,600 × 970 × 190 / 28.4 kg AC 120 V - 50 / 60 Hz	(cal), RS-232C (D-Sub 9pin, Control & Serv Alax 1W with 8\Omega), Service Only (3.5mm) 300 \times 300 49" \times 30.9" \times 9.1" / 32 lbs 1,244 \times 786 \times 231 / 14.5 kg 49" \times 28.4" \times 3.4" / 31.5 lbs 1,244 \times 721 \times 87.1 / 14.3 kg 53.5" \times 33" \times 6.9" / 43 lbs 1,360 \times 835 \times 175 / 19.5 kg AC 120 V - 50 / 60 Hz	300 x 300 43.7" x 27.9" x 9.1" / 24.9 lbs 1,110 x 709 x 231 / 11.3 kg 43.7" x 25.4" x 3.2" / 24.5 lbs 1,110 x 645 x 81.1 / 11.1 kg 47" x 30.3" x 6.2" / 29.5 lbs 1,193 x 770 x 158 / 13.4 kg AC 120 V - 50 / 60 Hz	38.3" x 24.5" x 8.5" / 17.9 lb 973 x 623 x 216 / 8.1 kg 38.3" x 22.3" x 3.3" / 17.6 lbs 973 x 567 x 85 / 80 kg 41.7" x 26" x 6" / 22.5 lbs 1,060 x 660 x 152 / 10.2 kg AC 120 V ~ 50 / 60 Hz	
	VESA (W x H) W x H x D / Weight (with stand) W x H x D / Weight (without stand) W x H x D / Weight (Shipping) Voltage Power Consumption (Typical)	76.5" x 46.8" x 13.6" / 99.2 lbs 1,943 x 1,188 x 345 / 45.0 kg 76.5" x 43.8" x 3.7" / 97.4 lbs 1,943 x 1,113 x 93.3 / 44.2 kg 83.3" x 49.6" x 11.2" / 130.1 lbs 2,116 x 1,261 x 285 / 59.0 kg AC 120 V - 50 / 60 Hz	600 x 400 66.7" x 41.3" x 13.6" / 78 lbs 1,693 x 1,048 x 345 / 35.4 kg 66.7" x 38.3" x 3.5" / 76.3 lbs 1,693 x 973 x 88.8 / 34.6 kg 72.4" x 43.9" x 9.1" / 100.8 lbs 1,839 x 1,116 x 231 / 45.7 kg AC 120 V - 50 / 60 Hz	ner), AV In (3.5mm), Digital Audio Out (Opt External Speaker Out (3.5mm, Stereo, N 300 × 300 57.6" × 36" × 10.6" / 47.6 lbs 1.463 × 914 × 269 / 21.6 kg 57.6" × 33.3" × 3.5" / 47 lbs 1.463 × 845 × 878 / 21.3 kg 63" × 38.2" × 7.5" / 62.6 lbs 1.600 × 970 × 190 / 28.4 kg AC 120 V - 50 / 60 Hz	ical), RS-232C (D-Sub 9pin, Control & Serv //ax 1W with 8\Omega), Service Only (3.5mm) 300 x 300 49" x 30.9" x 9.1" / 32 lbs 1,244 x 786 x 231 / 14.5 kg 49" x 28.4" x 3.4" / 31.5 lbs 1,244 x 721 x 87.1 / 14.3 kg 53.5" x 33" x 6.9" / 43 lbs 1,360 x 835 x 175 / 19.5 kg AC 120 V - 50 / 60 Hz	300 x 300 43.7" x 27.9" x 9.1" / 24.9 lbs 1,110 x 70.9 x 23.1 / 11.3 kg 43.7" x 25.4" x 3.2" / 24.5 lbs 1,110 x 64.5 x 81.1 / 11.1 kg 47" x 30.3" x 6.2" / 29.5 lbs 1,193 x 770 x 15.8 / 13.4 kg AC 120 V - 50 / 60 Hz	38.3" x 24.5" x 8.5" / 17.9 lb: 973 x 623 x 216 / 8.1 kg 38.3" x 223" x 3.3" / 17.6 lbs 973 x 567 x 85 / 8.0 kg 41.7" x 26" x 6" / 22.5 lbs 1,060 x 660 x 152 / 10.2 kg AC 120 V - 50 / 60 Hz 99.1W	
MECHANICAL ELECTRICAL OTHER	VESA (W x H) W x H x D / Weight (with stand) W x H x D / Weight (without stand) W x H x D / Weight (Shipping) Voltage Power Consumption (Typical) Standby Power	76.5" x 46.8" x 13.6" / 99.2 lbs 1,943 x 1,188 x 345 / 45.0 kg 76.5" x 43.8" x 3.7" / 97.4 lbs 1,943 x 1,113 x 93.3 / 44.2 kg 83.3" x 49.6" x 11.2" / 130.1 lbs 2,116 x 1,261 x 285 / 59.0 kg AC 120 V - 50 / 60 Hz 301W Under 0.5W	600 x 400 66.7" x 41.3" x 13.6" / 78 lbs 1,693 x 1,048 x 345 / 35.4 kg 66.7" x 38.3" x 3.5" / 76.3 lbs 1,693 x 973 x 88.8 / 34.6 kg 72.4" x 43.9" x 9.1" / 100.8 lbs 1,839 x 1,116 x 231 / 45.7 kg AC 120 V - 50 / 60 Hz 221W Under 0.5W 3 Year Parts and Labor	ner), AV In (3.5mm), Digital Audio Out (Opt External Speaker Out (3.5mm, Stereo, N 300 × 300 57.6" × 36" × 10.6" / 47.6 lbs 1.463 × 914 × 269 / 21.6 kg 57.6" × 33.3" × 3.5" / 47 lbs 1.463 × 845 × 878 / 21.3 kg 63" × 38.2" × 7.5" / 62.6 lbs 1.600 × 970 × 190 / 28.4 kg AC 120 V - 50 / 60 Hz 180.3W Under 0.5W	ical), RS-232C (D-Sub 9pin, Control & Serv Alax 1W with 8\Omega), Service Only (3.5mm) 300 x 300 49" x 30.9" x 9.1" / 32 lbs 1,244 x 786 x 231 / 14.5 kg 49" x 28.4" x 3.4" / 31.5 lbs 1,244 x 721 x 87.1 / 14.3 kg 53.5" x 33" x 6.9" / 43 lbs 1,360 x 835 x 175 / 19.5 kg AC 120 V - 50 / 60 Hz 145W Under 0.5W 3 Year Parts and Labor	300 x 300 43.7" x 27.9" x 9.1" / 24.9 lbs 1,110 x 70.9 x 23.1 / 11.3 kg 43.7" x 25.4" x 3.2" / 24.5 lbs 1,110 x 645 x 81.1 / 11.1 kg 47" x 30.3" x 6.2" / 29.5 lbs 1,193 x 770 x 15.8 / 13.4 kg AC 120 V - 50 / 60 Hz 104W Under 0.5W	38.3" x 24.5" x 8.5" / 17.9 lbs 973 x 623 x 216 / 8.1 kg 38.3" x 22.3" x 3.3" / 17.6 lbs 973 x 567 x 85 / 8.0 kg 41.7" x 26" x 6" / 22.5 lbs 1,060 x 660 x 152 / 10.2 kg AC 120 V - 50 / 60 Hz 99.1 W Under 0.5 W	

^{*} Specifications are subject to change without notice, so please contact LG sales team to verify before ordering.

http://www.lg.com/us/business/commercial-display
http://www.twitter.com/LGCommDisplays
http://www.facebook.com/LGCommercialdisplays
http://www.linkedin.com/company/g-commercial-displays-usa
http://www.youtube.com/lgcommercialdisplayusa





