

## WIRELESS MICROPHONES

# iLive UHF Wireless Microphone Systems

iLive 2 antenna diversity wireless microphone systems.

# iLIVE 2 HEADSET

iLive 2 headset antenna diversity wireless microphone system with 32 selectable channels with automatic channel targeting and synchronization. The microphone signal receiver, body pack transmitter with head-worn, body color condenser microphone and jack/jack cable are included in each set. The system is used on the stage and in the conference rooms.



Technical Specifications	iLIVE 2 receiver
Power supply	12-15 V DC, 1.25 A
Output	Balanced XLR, unbalanced 6,3 mm TS JACK
Receiver way	Two frequency conversion super-heterodynes
Intermediate frequency	10,7 MHz
Antenna	BNC
T.H.D	< 0,7 %
Sensitivity	6 dB $\mu$ V
Image rejection	36 dB
Max. audio output	0 dB
Dimensions (H x W x D)	45 mm x 210 mm x 206 mm
Weight	1.3 kg
Material	Steel enclosure, aluminum front panel

Technical Specifications	iLIVE 2 body pack transmitter
Carrier frequency range	606 MHz - 621 MHz
Modulation	FM
Channels	32
Audio frequency response	45 Hz - 18 kHz
S/N ratio	> 105 dB
Antenna	1/4 wave antenna
Input connector	4 pin mini XLR connector
Transmitter's power	15 mW
Working range	60 m (Note: actual range depends on RF signal absorption, reflection and interference)
Polar pattern	Cardioid
Battery	2 x 1,5 V AA Alkaline battery
Dimensions (H x W x D)	110 mm x 64 mm x 25 mm
Weight	76 g
Material	Plastic

Technical Specifications	iLIVE 12 HM
Capsule type	Condenser
Impedance	200 $\Omega$
Sensitivity	-47 dB
Frequency	45 Hz - 18 kHz
Connectors	4 pin mini XLR connector
Phantom power voltage	5 V
Cable length	1 m
Weight	15 g
Colour	Skin (RAL 1014)
Accessories	Windscreen