

VM-1120

1:10 Balanced Stereo Audio Distribution Amplifier



The VM-1120 is a high-performance distribution amplifier for balanced mono audio signals on XLR connectors. It can also be configured as a 1:20 distribution amplifier for mono balanced audio signals

FEATURES

Grouped Audio Level Controls Dual Mode - Configure as 1:20 (mono) or 1:10 (stereo) DA S/N Ratio - 89.3dB Standard 19" Rack Mount Size - 2U



TECHNICAL SPECIFICATIONS

INPUTS:	2 balanced stereo or 4 balanced mono audio, +4dBu/50k Ω on XLR (F) connectors
OUTPUTS:	10 balanced stereo or 20 balanced mono audio, +4dBu/50 Ω on XLR (M) connectors
MAX. OUTPUT LEVEL:	23.8Vpp
BANDWIDTH (-3dB):	>100kHz
S/N RATIO:	89.3dB
CROSSTALK:	-78dB
CONTROLS:	Level (x4): -0.7dB to +5.1dB, mode selector switches
COUPLING:	AC (input); DC (output)
AUDIO THD + NOISE	: 0.081%
AUDIO 2nd HARMONIC:	0.006%
POWER CONSUMPTION:	230V AC, (115V AC USA), 15VA
INCLUDED ACCESSORIES:	Power cord
Product Dimensions	19" x 7.24 x 2U (43.6cm x 18.40cm x 8.80cm) W, D, H
Product Weight	3.8kg (8.3lbs) approx
Shipping Dimensions	55.00cm x 29.40cm x 16.10cm (21.65" x 11.57" x 6.34") W, D, H
Shipping Weight	4.9kg (10.8lbs) approx

