



## Installation Instructions

**MODEL:**

**KDock-1**

**USB-C Hub Multiport Adapter**



P/N:



2900-301518QS

Rev: 4



**SAFETY WARNING**

Disconnect the unit from the power supply before opening and servicing


For the latest information on our products and a list of Kramer distributors, visit our Web site where updates to these installation instructions may be found. We welcome your questions, comments, and feedback.

# KDock-1 USB-C Hub Multiport Adapter

## Introduction

Congratulations on purchasing your Kramer **KDock-1 USB-C Hub Multiport Adapter**. **KDock-1 USB-C Hub Multiport Adapter** supports HDMI™ video output, 1 USB-A port, and 1 USB-C port. It is specially designed to support mobile devices. It is an ideal accessory for MacBook, laptops equipped with USB Type-C, mobile phones, and tablets.

## Get to Know Your KDock-1



#	Feature	Function
1	USB-C Female	Power pass through 60W (5V/1A-20V/3A). Insert a device with a type C (male) plug into the type C port (to recharge it).
2	4K HDMI Connector	Connect to an HDMI acceptor.
3	1 USB-A 3.0/2.0 Connector	Connect with U disk, mouse, keyboard, or SSD. Speed: 5.0Gbps (640MB/s).
4	USB-C Male	Connect to host (PC, phone, or tablet).

## Technical Specifications

Inputs	1 USB	On a male USB-C connector.
Outputs	1 HDMI	On a female HDMI connector. 3840x2160P@30Hz.
Ports	2 USB	1 female USB-A 3.0 connector for USB link extension. <ul style="list-style-type: none"> <li>• Backward compatible with USB 2.0 data transmission up to 480Mbps(60MB/s).</li> <li>• When connected with powered device, the limited current is 1.9A from the USB 3.0 port.</li> <li>• When unconnected with powered device, the limited current is 1A from the USB 3.0 port.</li> <li>• Charging: BC1.2 (5V 1.5A).</li> <li>• Speed: 5.0Gbps (640MB/s).</li> </ul>
		1 female USB-C connector for charging.
Video	Max Bandwidth	10.2Gbps (3.4Gbps per graphic channel).
	Max Resolution	3840x2160P@30Hz resolution.
	Compliance	HDMI and HDCP 1.4.
Power	Consumption	60W.
Environmental Conditions	Operating Temperature	0° to +70°C (32° to 158°F).
	Storage Temperature	-10° to +55°C (14° to 131°F).
	Humidity	5% to 90%, RHL non-condensing.
Regulatory Compliance	Safety	CE.
	Environmental	RoHs, FCC.
Enclosure	Type	Aluminum with built-in 16cm/6.3" flexible USB-C cable.
General	Net Dimensions	7.5cm x 3.8cm x 1.5cm (3.0" x 1.5" x 0.6").
	Net Weight	40g (0.09lbs) approx.

Specifications are subject to change without notice at [www.kramerav.com](http://www.kramerav.com)

The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.