



# 5 Port HDMI 2.0 18G Switch

No.: 38244

## Description

- Connect and switch up to 5 UHD HDMI devices to 1 UHD display or projector
- Supports video resolutions up to 4K2K@60Hz 8 bit including 3D 1080p
- Supports 7.1 channel of LPCM, Dolby TrueHD and DTS-HD Master Audio digital audio signals
- HDCP 2.2 compliant for use with the latest AV equipment
- 2 year warranty

This state of the art 4K UHD HDMI 2.0 18G switch is capable of displaying resolutions up to 3840 x 2160 from 5 UHD signals in to 1 UHD signal out.

An RS232 port is included to allow switching via a PC or control software.

The Switch is also HDR (High Dynamic Range) compatible to reproduce a greater dynamic range of luminosity similar to that used in imaging and photography. HDR used on TV's allows a wider range of colours and greater contrast with whites and blacks, resulting in much higher definition pictures similar to ones seen by the human eye.

With full support for HDCP 2.2 and HDMI 2.0, you can be sure that this product is fully future proof and ready for the new and demanding audio and video signals on the market.

## Package Contents:

5 Port HDMI 2.0 18G Switch 5V Multi Country PSU with UK, US, Australian and European adapters Remote control inc battery IR receiver cable ~1.2m LINDY Manual

## **Technical details**

#### Specifications

- AV Interface: HDMI
- Interface Standard: HDMI 2.0
- Supports Bandwidth: 18 Gbps
- Maximum Resolution: 3840x2160@60Hz 4:4:4 8bit
- HDCP Support: 2.2

- Supported Audio: Audio Pass-through
   Separate Audio Ports: HDMI
- IR Support: 38kHz
- CEC Support: Pass-Through
- Serial Interface: RS232

## • Special Features: -

#### Connectors

- Input: 5 x HDMI (Female), 3.5mm (Female)

- Output: HDMI (Female)
   Control: RS232 Port
   Power: 5.5/2.1mm DC socket

#### **Physical Properties**

- Dimensions WxDxH: 211x75x25mm (8.31x2.95x0.98in)
- Housing Material: Metal
- Net Weight: 0.43kg (0.95lb)
  Operating Temperature: 0°C 50°C (32°F 122°F)
  Storage Temperature: -10°C 50°C (14°F 122°F)
  Humidity: 5 85% RH (non-condensing)
  Device Poservise Texts (DCC 14)
- Power Requirements: 5VDC 1A
- Colour: Black

#### **Miscellaneous**

- Packaging Type: Carton box
  Packaging Dimensions: 240x165x55mm (9.45x6.5x2.17in)

- Gross Weight: 0.659kg (1.45lb)
  Warranty (Years): 2
  Certificated: CE, FCC, RoHS & REACH

## **Package Contents**

- 5 Port 4K HDMI 2.0 4K 18G Switch
- IR Remote Control (inc battery)
- 1.2m (3.94ft) IR receiver cable
- Multi-Country Power Supply (EU, UK, US & AUS)
- Lindy Manual

## **Purchasing Information**

- No.: 38244
- EAN: 4002888382441

© LINDY 2019