

STEM SPEAKER

NETWORKED LOUDSPEAKER

OVERVIEW

Stem Speaker Networked Loudspeaker delivers exceptional sound experiences in any meeting room with its powerful drivers and built-in technology, while a choice of table, wall, or ceiling mounting options provide ultimate flexibility to highlight the tech or keep it low-profile in the room.

FEATURES

- $\label{lem:compatible} \mbox{Compatible with other Stem Ecosystem devices to expand sound in any meeting space.}$
- Can be used beyond video conferencing to also play program audio, background music, to listen to songs at full volume.
- LED light ring indicates device status.
- Controls on the device include Volume Up and Down. Speaker volume can also be adjusted using Stem Control Touch Controller.
- Power over Ethernet (PoE+).
- Three mounting options: Ceiling mount, wall mount, or standing.
- Kensington lock equipped.

SPECIFICATIONS (subject to change)

GENERAL

Connector Type	RJ45
Power Requirements	Power over Ethernet Plus (PoE+)
Power Consumption	22 Watts (PoE+)
Control Application	Stem Ecosystem Platform
Weight	5.6 lbs (2.5 kg)
Product Dimensions	9 x 4 in (22.9 x 10.2 cm) Diameter x Depth
Operating Temperature Range	-6.7°C (20°F) to 40°C (104°F)
Storage Temperature Range	-29°C (-20°F) to 74°C (165°F)
AUDIO	
Frequency Response	60Hz to 20kHz
Maximum Output Level (at 1 meter)	102 dB SPL

ACCESSORIES (included in the box)

CAT 6 Ethernet Cable: 15 ft. (4.6 m)	
Aluminum Ring for Ceiling Mounting	
Wall Mounting Kit (Screws and Drywall Anchors)	
Legs and Rubber Screw Head Covers for Tabletop Setup	



STEM SPEAKER Ceiling Mount



STEM SPEAKER Table Stand



shure.com