

Frame Cleaning Instructions

Materials:

- 1. Putty Knife (or preferred scraping tool)
- 2. Bucket
- 3. Hose, pressure washer, and/or warm water (water not to exceed 200°F)
 - a. WARNING: Hot and/or boiling water will cause the plastic to warp.

Instructions:

- 1. Remove the frame from the hive.
- 2. At your work station, brush off all of the dead bees and other loose debris.
- 3. Using your scrapper, use minimum amount of force required to scrape off the old comb and wax. Scrape in long strokes, always working from top to bottom.
 - a. **NOTE:** Using too much force may damage the hive.
- 4. Discard these scrapping into your bucket. Don't worry if you do not get it all.
 - a. These scraps can be melted down later for other uses.
- Next, use the hose (or pressure washer) to spray down the frames. This will remove additional comb and debris. If using warm water, make sure the water does NOT exceed 200°^F.
 - a. **WARNING:** Hot and/or boiling water will cause the plastic to warp.
- 6. Remove excess water and reinsert frames into your supers.
- 7. If desired, let the washed frames air dry and coat with a thin layer of wax before re-introducing them to your hive.



Pierco Inc.

680 Main St. Riverside, CA 92501 USA P: +1 (800) 233-2662 | F: +1 (909) 596-1452 E: info@pierco.net |W: pierco.com