

WALL PACK SERIES

LED Full Cut-Off

Adjustable from 40W to 80 Watts

WP10-80-3CCT

WP10-80-2CCT

Light up your outdoor area

PLUG-IN HAISEN
PHOTOCELL INCLUDED



DIP SWITCH, POWER AND CCT ADJUSTABLE



FEATURES


- ETL/cETL/DLC premium certificate
- Easy installation
- Wet location rated IP65
- Durable die-cast aluminum housing
- Photocell included
- UV-resistant polycarbonate refractor lens
- Viewing angle Type III

APPLICATIONS

- Full Cut-Off Wall Pack. It is a high efficient lighting solution that provides a long-lasting and energy-saving. The rugged housing offers advanced thermal management and protection against outdoor environments without compromising aesthetics.
- Outdoor wall-mount applications: building facade, commercial, industrial, retail, hospitality buildings that demand long service life and low maintenance.



LIGHT SPECIFICATIONS

SKU	WP10-80-3CCT	WP10-80-2CCT
Input power	Adjustable from 40 W to 80 Watts	
IES file 	Available upon request	

GENERAL PERFORMANCE

Efficacy (lm/w)	130LM/W (±10%)
CRI	RA ≥ 70
THD	<20%
Viewing Angle	Type III
Surge Protection	L-N: 2KV L/N-PE: 4KV
Color Temp.	3CCT adjustable: 3000K/4000K/5000K 2CCT adjustable: 2200K/3000K
Driver Brand	Weled Power
Led Brand / Type	Lumileds / 3030
Power Factor	≥ 0.9
Frequency	50/60Hz
Input voltage	120-347VAC
Additional function	0-10V / 1-10V Photocell / Power + CCT Adjustable
Life Time	L70 @ 50,000Hrs

PHYSICAL

Housing	Die-cast Aluminum
Finish	Black
Storage temperature	-40°F to 158°F (-40°C to +70°C)
Storage humidity	RH<95%
Operating temperature	-22°F to 113°F (-30°C to +45°C)
Operating Humidity	RH<90%



CERTIFICATION

Certification	cETL/ETL/DLC Premium
Environment	Wet location rated IP65
Warranty	5 years

