

ST8B Linear Strip Light

Power Selectable | Colour Selectable | 120-347V | 8 ft

Quickest row mount fixture on the market!

Ideal for shops, cove lighting, and general area lighting
Ceiling mount or cable mount, linkable, and row mountable

Power Selectable

50W / 60W / 70W



Designed for a Quick
and Easy Installation

open and closes without the use of tools



Internal Dimming

Colour Selectable

3500K / 4000K / 5000K

Light Engine Drops
on Aircraft Cables
for ease of installation

Low Glare
Frosted Lens



Plug & Play Row Mount Kit

Row Mount Kit sold separately



TECHNICAL DATA

LIGHT SPECIFICATIONS

Lumens*	10,199 lm
Efficacy*	152 lm/W
CCT	3500K/4000K/5000K
CRI	86
Beam Angle	120°
Dimmable	0-10V
L70 Life	50,000 hrs
Warranty	5-year

*Shown at 70W and 3500K


APPROVALS & LISTINGS

cUL	E482965
DLC	S-QX38KO, S-ID8G6E

ACCESSORIES (SOLD SEPARATELY)

Suspension Kit	ST-SUS-KIT
Connection Bracket	ST-CONN-BKT
Microwave Motion Sensor (12 ft max)	MS02-MW-HW-DC
Microwave Motion Sensor (25 ft max)	MS03-MW-HW-DC
Row Mounting Connector	ST-RM8
Motion Sensor Remote Control	MS02-RC

ILLUMINANCE AT A DISTANCE



ELECTRICAL

Wattage	50W/60W/70W
Voltage	120-347V
Current	0.8A
Surge Protection	2kV
Auxiliary Output	12V
Power Factor	0.91
THD	20%
Operating Temp	-20 to 45°C

CONSTRUCTION

Housing	Colour Coated Steel Plate
Lens	Polycarbonate
Finish Colour	White
IP Rating	IP20 (Damp Location)

DIMENSIONS & WEIGHTS

Product Dimensions	95.98 x 2.95 x 3.26 in
Fixture Weight	6.50 lbs
Carton Qty	1
Carton Gross Weight	6.75 lbs
Carton Dimensions	96.4 x 3.2 x 3.5 in
Master Carton Qty	4
Master Carton Gross Weight	30.60 lbs
Master Carton Dimensions	96.9 x 7.1 x 7.9 in