



NSF, NEMA 4X

Simply Brilliant



High CRI



Dimmable



NSF/ANSI 2



LISTED
E505599



Product information

FEATURES

- Power and Color Selectable UFO High Bay
- High Lumen Efficacy 150LM/w
- NSF, NEMA 4X Certified
- DLC Premium, cUL listed
- Polycarbonate Lens UGR<28
- 0-10v Dimmable
- Lumileds 2835 LEDs / Fahold driver
- 10FT cord whip, Eyebolt mount
- Quick connect to motion sensor (pre-installed base)
- IP65 Rated for wet location
- 50,000 hour life
- L/N-PE: 6kV, L-N: 6kV surge prot.
- Quick & easy installation
- No flicker, mercury free, instant on
- 5-year warranty

APPLICATION

- Healthcare
- Gymnasium
- Warehouse
- Museum
- Recreation Center



INSTALLATION

- Hook
- U-Bracket
- Pendant 3/4" NPS pipe


ADDITIONAL INFO

- Optional: a) Microwave Sensor
- b). PIR Sensor c). Remote Control
- Operating Temperature -40°C ~+50°C

DIAGRAM



PHOTOMETRICS



ITEM NO.	MODEL NO.	DLC ID	DESCRIPTION	WATTS	VOLT	LUMENS	CCT(K)	BEAM ANGLE	IP	PF	MOL (IN)	CASE QTY.
L5331-0100	ILX-UHB-ST2-100WS-3CCT-L2	S-P8B98S	ROUND HBAY 150L/W 3CCT 3M CORD	60/80/100W	120-347v	15000	35/40/50K	90°	65	0.9	11x5.7	1
L5331-0150	ILX-UHB-ST2-150WS-3CCT-L2	S-VJML7D	ROUND HBAY 150L/W 3CCT 3M CORD	100/120/150W	120-347v	22500	35/40/50K	90°	65	0.9	11x5.7	1
L5331-0240	ILX-UHB-ST2-240WS-3CCT-L2	S-V459LV	ROUND HBAY 150L/W 3CCT 3M CORD	200/220/240W	120-347v	36000	35/40/50K	90°	65	0.9	13.4x5.7	1

OPTIONAL ACCESSORIES

L5331-1510	ILX-UHB-ST2-MS	MOTION SENSOR (MICROWAVE)
L5331-1520	ILX-UHB-ST2-PIR	PIR SENSOR
L5331-1515	ILX-UHB-ST3-RC	REMOTE CONTROL WORKS FOR BOTH PIR AND MICROWAVE

ILLUMINEX TECHNOLOGIES INC.

Tel: 1-905-264-6670 Toll Free: 1-844-985-1590 Fax: 1-905-264-6671

Email: csr@illuminexled.com | Website: www.illuminexled.com

Head Office: 1-1 Keyes Court, Vaughan, ON L4H 4V6