

WATER SYSTEM ACCESSORIES CONTINUED



PRE-PRESSURIZED ACCUMULATOR TANKS

Name	Model #OEM/ (Aftermarket)	Ports	Dimensions	Total Volume	Max. PSI
24 oz. Nylon Tank (A)	182-100 (182-200)	1/2" NPSM-Male	9.1" x 4.8" x 3.8" [232 x 121 x 97 mm]	24 oz. [710 ml]	125 PSI [8.8 BAR]
2 Gallon Stainless Steel Tank (B)	3400-002 (3400-002)	1/2" NPT-Female	12" H x 9" D [23cm H x 10cm D]	2 Gal. [8 L]	100 PSI [7 BAR]

Reduce cycling pulsation and pressure spikes, increase the life of your pump—and even save battery power. Easily handles pressure requirements from 20 PSI to 125 PSI.

PRESSURE REDUCING WATER CITY ENTRIES

Name	Model # OEM/(Aftermarket)	Model # OEM/(Aftermarket)	Color
	50 PSI MODEL	65 PSI Model	
Wall Mount (A)	—	183-020-14 (183-029-14)	Chrome
Wall Mount (B)	—	183-020-16 (183-029-16)	Black
Wall Mount (C)	—	183-020-18 (183-029-18)	Gel White
In-Line (D)	(183-039-08)	N/A	Gel White

The Shurflo exclusive diaphragm design prevents high-pressure damage often caused by city water. These high performance water entries limit water pressure and include a check valve. 3/4" (19.1 mm) GHT - Female Swivel Inlet. 1/2" (13mm) NPSM - Male Outlet.

FAUCETS

Name	Model # OEM/(Aftermarket)	Voltage	Ports	Amps (Max.)	Operation	Spout Rotation	Color
Electric Faucet with Switch (A)	94-009-00 (94-009-10)	12 VDC	3/8" Barb	3	Single	360°	White
Electric Faucet with Switch	94-009-01 N/A	12 VDC	3/8" Barb	3	Single	360°	Gray
Single Touch Faucet (B)	15-045-02 (15-045-02)	N/A	1/4"	N/A	Single	Twist	Chrome
Faucet without Switch	94-009-32 (94-009-12)	N/A	3/8" Barb	N/A	Single	360°	White

The Shurflo faucets offer smooth, easy flow with a washerless ceramic disc design. Versatile 360 degree spout rotation. Easy to use with city water system. 15-045-02 single touch faucet has a 1/4" (6.35 mm) port and works perfectly with filtration systems.

